

Professional Range 30"

SPR30UGMX Stainless steel SPR



Features


Gas hob - Gas provides permanent control of the heat source and the temperature change is immediate

Touch control - Easy and intuitive timer setting with a single touch

True-convection - The best cooking performances guaranteed by ventilated circular flow.

Tangential cooling - New cooling system with tangential fan and airflow from the door to the splashback

 $\mbox{\bf Soft close}$ - The door is equipped with a specific system for silent closing



Cooktop technical features

Cooking zones
Front-left - 12000 BTU

Rear-left - 10000 BTU Rear-right - 10000 BTU Front-right - 18000 BTU

Programs / Functions

No. of cooking functions	8
Cleaning functions	VaporClean

Main oven options

Minimum Temperature	149 °F
Maximum temperature	500 °F

Main Oven Technical Features

Volume	4.56 cu. ft.
Cavity material	EverClean enamel
No. of shelves	6
Removable inner door	Yes
Total no. of door glasses	3
Soft Close system	Yes

Included accessories

Oven wire rack 2

Electrical Connection


Plug	(B) NEMA 14-50P
Circuit breaker	20 A
Voltage	208/240 V
Frequency	60 Hz

Logistic Information

Width	29 15/16 "
Depth	25 "
Height	34 13/16 "
Net weight	213 lbs



Product dimension drawing



Accessories




GRM Coffee machine support



GT3T Total-extraction telescopic guides

Product installation drawing



A 24" 610 mm B 25" 630 mm C ¹ 5 ⁷ / ₈ " 150 mm			
C^1 5 $\frac{7}{8}$ 150 mm	Α	24"	610 mm
C^1 5 $\frac{7}{8}$ " 150 mm	В	25"	630 mm
-2 0411 / 10	C^1	5 ⁷ / ₈ "	150 mm
G ² 24" 010 mm	G ²	24"	610 mm
18" 457 mm	I ³	18"	457 mm
L see user manual	L	see user manual	
M⁴ 13" 330 mm		13"	330 mm
P ⁴ 13" 330 mm	P^4	13"	330 mm