

# Professional Range 36"

SPR36UGMX Stainless steel Dual fuel



#### **Features**


 ${\bf Gas\ hob}$  -  ${\bf Gas\ provides\ permanent\ control\ of\ the\ heat\ source}$  and the temperature change is immediate

**Touch control** - Easy and intuitive timer setting with a single touch

**True-convection** - The best cooking performances guaranteed by ventilated circular flow.

**Tangential cooling** - New cooling system with tangential fan and airflow from the door to the splashback

Soft close - The door is equipped with a specific system for silent closing



### Cooktop technical features

Cooking zones 6
Front-left - 18000 BTU
Rear-left - 10000 BTU
Front-center - 10000 BTU
Rear-center - 10000 BTU
Front-right - 18000 BTU
Rear-right - 10000 BTU

#### **Aesthetic**

Series	Professional
Color	Stainless steel

#### General information

Range size	36"
Range type	Dual fuel

## Programs / Functions

No. of cooking functions	8
Cleaning functions	VaporClean

## Main oven options

Minimum Temperature	149 °F
Maximum temperature	500 °F

#### Main Oven Technical Features

Volume	4.45 cu. ft.
Cavity material	EverClean enamel
No. of shelves	5
Removable inner door	Yes
Total no. of door glasses	3
Soft Close system	Yes

#### Included accessories

Oven wire rack 2




### **Electrical Connection**

Circuit breaker	20 A
Voltage	208/240 V
Frequency	60 Hz

# **Logistic Information**

Width	35 7/8 "
Depth	26 "
Height	35 3/16 "
Net weight	238 lbs

# Product dimension drawing



### **Accessories**



GRM Coffee machine support



GT3T

Total-extraction telescopic guides




KITTKSPR36

Plinth, 3 sides, 900mm, SPR cookers 30", black



WOKGHU Cast-iron wok support

# Product installation drawing



Α	24"	610 mm
В	25"	630 mm
$\frac{C^1}{G^2}$	5 <sup>7</sup> / <sub>8</sub> "	1 <i>5</i> 0 mm
$G^2$	24"	610 mm
I <sup>3</sup>	18"	457 mm
L	see user manual	
M <sup>4</sup>	13"	330 mm
$P^4$	13"	330 mm