


# ALFA1035H-2



<b>Family</b>	Professional ovens
<b>Subfamily</b>	Convection oven 10 trays EN 600x400 mm or GN1/1
<b>Power supply</b>	Electric
<b>Oven type</b>	Convection oven with humidification
<b>Oven control</b>	Manual
<b>Trays capacity</b>	10 trays GN1/1, 10 EN 600x400 mm (min. H 20 mm)
<b>Power supply</b>	400 V 3N~ / 23A / 16 kW / 50 Hz
<b>Program storage with application</b>	Not available
<b>Humidity generation</b>	Direct in cavity
<b>Adjustable feet</b>	Yes
<b>Product dimensions WxDxH</b>	798x772x1100 mm
<b>Maximum depth with open door</b>	1536 mm



## Target

Industries	Suggested for	Bakery
Bar / Cafeterias / Bistros / Wine bars / Pubs; Hotels; Restaurants; Bakeries / Pastry shops; Butcher shops / Delicatessens; Catering; Care facilities ; Commercial food services; Grocery shops / Food retail		

## Aesthetics

<b>Door with stainless steel stripes</b>	Yes	<b>Front panel Series</b>	Yes
<b>Colour</b>	Stainless steel		Alfa

## Controls

<b>Timer setting range</b>	1-60 minutes + endless	<b>Chimney regulation</b>	Manual
----------------------------	------------------------	---------------------------	--------

## Options


<b>Right hand hinge</b>	ALFA1035HR-2	<b>Combinable hood</b>	K4610X
-------------------------	--------------	------------------------	--------

## Construction

<b>Oven materials</b>	Stainless steel / glass / plastics	<b>Humidification levels</b>	Manual
<b>Cavity dimensions (wx dx h)</b>	672x437x854 mm	<b>Exhaust position</b>	Back
<b>Gross volume</b>	289,8 lt	<b>Timer type</b>	Electric
<b>Net volume</b>	258,9 lt	<b>Temperature range</b>	50-270°C
<b>Internal net volume</b>	199,1 lt	<b>End cooking signal</b>	Yes
<b>Cavity material</b>	Stainless steel	<b>Orange light indicator t° achievement</b>	Yes
<b>Shelves number</b>	10	<b>Green light indicator time achievement</b>	Yes
<b>Tray frame support</b>	Chromed wire	<b>Safety switch with open door</b>	Yes
<b>Shelves distance</b>	77 mm	<b>Manual reset safety thermostat</b>	Yes
<b>Door construction</b>	Double glass	<b>Removable deflector</b>	Yes
<b>Door opening</b>	Lateral - left hinge	<b>Lighting</b>	3 Halogen lamps
<b>Handle type</b>	Rotating	<b>Light power</b>	40 W
<b>Glass</b>	Openable with hinge	<b>Water load pipe</b>	Yes
<b>Fan type and number</b>	3 contrarotating with timed direction reversal	<b>Water inlet pressure</b>	50-500 kPa (min-max)
<b>Fan motor power</b>	180W	<b>Power cable length</b>	170 cm
<b>Engine rpm</b>	Single speed	<b>Back panel</b>	Galvanized
<b>Motor rpm in standard speed</b>	2850 rpm	<b>IPX protection</b>	IPX3
<b>Water injection on each fan</b>	Yes		

## Logistic Information

<b>Packed product dimensions (WxDxH)</b>	1280x960x890 mm	<b>Net weight</b>	102,000 kg
<b>EAN code</b>	8017709270148	<b>Gross weight (kg)</b>	122,000 kg



## Compatible Accessories



**3743**

Flat aluminium tray (4pcs)




**3751**

Flat perforated aluminium tray (4pcs)



**3805**

Flat chrome-plated wire grid (4pcs)



**3810**

Waved grid for baguettes (4pcs)



**3927**

Air flow reducer kit for ovens ALFA410, 420, 625, 1035



**RGN11-1035-2**

Support kit for grids or flat trays GN1/1 suitable for ALFA1035 models



**RUTVL**

Wheels kit for all oven table models (4pcs)



**T11TH20**

GN1/1 non-stick tray, 20 mm height



**T11TH40**

GN1/1 non-stick tray, 40 mm height




**T11XH20**

2cm height aluminium GN1/1 tray, 20 mm height



**T11XH65**

GN1/1 aluminium tray, 65 mm height



**TF11XH2**

Perforated aluminium GN1/1 tray, 20 mm height



**TMF11TH2**

GN 1/1 non-sticking microperforated tray, 20 mm height



**TVL425D**

4-level tray holder rack for ALFA410/ALFA420/ALFA425 (stacked) or ALFA1035 ovens, dim. 800x800x504 mm (height with kit RUTVL: 602 mm)

---

## Alternative products

---



**ALFA1035HR-2**

**Colour:** Stainless steel

---

## Symbols glossary

---

 Electric

 Fan forced heating

 Fan forced heating with humidity injection

## Benefit (TT)

---

### **Mechanical control panel**

Ease of use and effortless control of the essential cooking parameters

The control panel, equipped with practical knobs, allows for simple, intuitive, and effortless management of the main functions. Using the buttons, you can adjust the cooking time, temperature, and, in selected models, the level of humidification. By turning the knob to position 1, steam will be delivered until it is released.

In multifunction ovens with a mechanical control panel, there is also a dedicated button for selecting different oven functions based on the desired cooking mode.

### **Hinged opening**

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.

### **Humidity management**

Impeccable cooking thanks to precise humidity control

Thanks to the effective management of small amounts of steam, perfect browning can be achieved while maintaining the product's softness and promoting the development of its internal structure. Different humidity levels can be set, which determine the frequency of activation cycles. Each cycle consists of two seconds of water vapour spraying inside the cooking chamber, followed by a 15-second pause.