
ALFA1035H-2



Family	Professional ovens
Subfamily	Convection oven 10 trays EN 600x400 mm, GN 1/1 (min. H 20 mm)
Power supply	Electric
Oven type	Convection oven with humidification
Oven control	Manual
Trays capacity	10 trays EN 600x400 mm, 10 trays GN1/1 (min. H 20 mm)
Default power supply	400 V 3N~ / 23A / 16 kW / 50 Hz
Program storage with application	Not available
Humidity generation	Direct in cavity
Adjustable feet	Yes
Product dimensions (WxDxH)	798x772x1100 mm
Maximum depth with open door	1536 mm

Target

Industries	Bar / Cafeterias / Bistros / Wine bars / Pubs, Hotels, Restaurants, Bakeries / Pastry shops, Butcher shops / Delicatessens, Catering, Care facilities , Commercial food services, Grocery shops / Food retail

Aesthetics

Door with stainless steel stripes	Yes	**Front panel**	Yes
Colour	Stainless Steel	**Series**	Alfa

Controls

Timer setting range	1-60 minutes + endless	**Chimney regulation**	Manual

Options

Right hand hinge version	ALFA1035HR-2	**Combinable hood**	K4610X

Electrical Connection

Potential equalisation	Yes

Construction


Oven materials	Stainless steel / glass / plastics
Cavity dimensions (WxDxH)	672x437x854 mm
Gross volume	289,8 lt
Net volume	258,9 lt
Internal net volume	199,1 lt
Cavity material	Stainless steel
Shelves number	10
Tray frame support	Chromed wire
Shelves distance	77 mm
Door construction	Double glass
Door opening	Lateral - left hinge
Handle type	Rotating
Glass	Openable with hinge
Fan type and number	3 contrarotating with timed direction reversal
Fan motor power	180 W
Engine rpm	Single speed
Motor rpm in standard speed	2850 rpm
Water injection on each fan	Yes

Humidification levels	1 Manual
Exhaust position	Back
Timer type	Electric
Temperature range	50-270°C
End cooking signal	Yes
Orange light indicator for t° achievement	Yes
Green light indicator time achievement	Yes
Safety switch with open door	Yes
Manual reset safety thermostat	Yes
Removable deflector	Yes
Lighting	3 Halogen lamps
Light power	40 W
Water load pipe	Yes
Water inlet pressure	50-500 kPa (min-max)
Power cable length	170 cm
Back panel	Galvanized
IPX protection	IPX3

Logistic Information

Packed product dimensions (WxDxH)	960x890x1280 mm
EAN code	8017709270148

Net weight	101.200 kg
Gross weight	122.200 kg



Compatible Accessories



3743

Kit of 4 flat aluminum trays EN 600×400 mm




3751

Kit of 4 flat perforated aluminium tray EN 600×400 mm



3805

Kit of 4 chrome-plated wire grids EN 600×400 mm



3810

Kit of 4 wave wire grids for baguettes EN 600×400 mm



3927

Air flow reducer kit for ovens ALFA410, 420, 625, 1035



RGN11-1035-2

Support rack for GN 1/1 flat trays, suitable for ALFA1035 models



RUTVL

Set of 4 wheels, fits all professional oven tables



T11TH20

GN1/1 non-stick tray, 20 mm height



T11TH40

GN1/1 non-stick tray, 40 mm height




T11XH20

Aluminium GN1/1 tray, 20 mm height




T11XH65

GN1/1 aluminium tray, 65 mm height



TF11XH2

GN 1/1 perforated aluminium tray, 20 mm height



TMF11TH2

GN 1/1 non-sticking microperforated tray, 20 mm height



TVL425D

4-level tray holder rack for ALFA410/ALFA420/ALFA425 (stacked) or ALFA1035 ovens, dim. (WxDxH) 800x800x504 mm (hieight with kit RUTVL: 602 mm)

Alternative products



ALFA1035HR-2

Colour: Stainless Steel

Symbols glossary

 Electric

 Fan forced heating

 Fan forced heating with humidity injection

Benefit (TT)

Mechanical control panel

Ease of use and effortless control of the essential cooking parameters

The control panel, equipped with practical knobs, allows for simple, intuitive, and effortless management of the main functions. Using the buttons, you can adjust the cooking time, temperature, and, in selected models, the level of humidification. By turning the knob to position 1, steam will be delivered until it is released.
In multifunction ovens with a mechanical control panel, there is also a dedicated button for selecting different oven functions based on the desired cooking mode.

Hinged opening

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.

Humidity management

Impeccable cooking thanks to precise humidity control

Thanks to the effective management of small amounts of humidity, perfect browning can be achieved while maintaining the product's softness and promoting the development of its internal structure. Different humidity levels can be set, which determine the frequency of activation cycles. Each cycle consists of two seconds of water vapour spraying inside the cooking chamber, followed by a 15-second pause.