

ALFA410-2



Family	Professional ovens
Subfamily	Convection oven 4 trays EN 600x400 mm or GN1/1
Power supply	Electric
Oven type	Convection oven
Oven control	Manual
Trays capacity	4 trays EN 600x400 mm, GN1/1 (min. H 20 mm)
Power supply	400 V 3N~ / 13 A / 5,3 kW / 50 Hz
Other electrical connection	230 V~ / 23 A / 5,3 kW / 50 Hz
Program storage with application	Not available
Adjustable feet	Yes
Product dimensions WxDxH	798x747x563 mm
Maximum depth with open door	1145 mm



Target

Industries	Suggested for	Bakery
Bar / Cafeterias / Bistros / Wine bars / Pubs; Hotels; Restaurants; Bakeries / Pastry shops; Butcher shops / Delicatessens; Catering; Care facilities ; Commercial food services; Grocery shops / Food retail		

Aesthetics

Door with stainless steel stripes	Yes	Front panel Series	Yes
Colour	Stainless steel		Alfa

Controls

Timer setting range	1-60 minutes + endless
----------------------------	------------------------

Options


Combinable hood	K4610X
------------------------	--------

Construction

Oven materials	Stainless steel / glass / plastics	Motor rpm in standard speed	2850 rpm
Cavity dimensions (wxhxd)	672x437x340 mm	Exhaust position	Back
Gross volume	115,6 lt	Timer type	Electric
Net volume	104,2 lt	Temperature range	50-270°C
Internal net volume	75 lt	End cooking signal	Yes
Cavity material	Stainless steel	Orange light indicator t° achievement	Yes
Shelves number	4	Green light indicator time achievement	Yes
Tray frame support	Chromed wire	Safety switch with open door	Yes
Shelves distance	77 mm	Manual reset safety thermostat	Yes
Door construction	Double glass	Removable deflector	Yes
Door opening	Tilting	Lighting	2 Halogen lamps
Handle type	Fixed	Light power	40 W
Glass	Openable with clip	Power cable length	170 cm
Fan type and number	1 fan with direction reversal	Back panel	Galvanized
Fan motor power	180W	IPX protection	IPX3
Engine rpm	Single speed		

Logistic Information

Packed product dimensions (WxDxH)	640x960x845 mm	Net weight	53,000 kg
EAN code	8017709270100	Gross weight (kg)	63,000 kg



1	ALIMENTAZIONE ELETTRICA - POWER SUPPLY
2	MORSETTO EQUIPOTENZIALE - EARTH TERMINAL
3	USCITA FUMI CALDI - HOT EXHAUST OUTLET
4	TARGHETTA CARATTERISTICHE TECNICHE - TECHNICAL SPECIFICATION LABEL

Compatible Accessories



3743

Flat aluminium tray (4pcs)




3751

Flat perforated aluminium tray (4pcs)



3805

Flat chrome-plated wire grid (4pcs)




3810

Waved grid for baguettes (4pcs)



3927

Air flow reducer kit for ovens ALFA410,
420, 625, 1035



RGN11-420-2

Support kit for grids or flat trays
GN1/1 suitable for ALFA420/425/410
models



RUTVL

Wheels kit for all oven table models
(4pcs)



SVRPP420-625

Connector kit for two stacked
ALFA420+420 or ALFA420+625
models and hood



T11TH20

GN1/1 non-stick tray, 20 mm height



T11TH40

GN1/1 non-stick tray, 40 mm height




T11XH20

2cm height aluminium GN1/1 tray, 20
mm height



T11XH65

GN1/1 aluminium tray, 65 mm height



TF11XH2

Perforated aluminium GN1/1 tray, 20
mm height



TMF11TH2

GN 1/1 non-sticking microperforated
tray, 20 mm height

Symbols glossary

 Electric

 Fan forced heating

Benefit (TT)

Mechanical control panel

Ease of use and effortless control of the essential cooking parameters

The control panel, equipped with practical knobs, allows for simple, intuitive, and effortless management of the main functions. Using the buttons, you can adjust the cooking time, temperature, and, in selected models, the level of humidification. By turning the knob to position 1, steam will be delivered until it is released.

In multifunction ovens with a mechanical control panel, there is also a dedicated button for selecting different oven functions based on the desired cooking mode.

Clip-open

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.