

# **ALFA410XAU**



Family Ovens

Subfamily Convection oven 4 trays EN 600x400

mm or GN1/1

Power supply Electric
Oven type One function
Oven control Mechanical

Trays capacity 4 trays EN 600x400 mm, GN1/1 (min.

H 20 mm)

Power supply  $230 \text{ V} \sim /50 \text{ Hz} / 15 \text{ A} / 3,1 \text{ kW}$ 

Adjustable feet Yes

Product dimensions WxDxH 798x747x563 mm

Maximum depth with open door 1145 mm



# Distribution

Industries Bar / Cafeterias / Bistros /

Wine bars / Pubs; Hotels; Restaurants; Bakeries / Pastry shops; Butcher shops / Delicatessens; Catering; Care facilities; Commercial food services; Grocery shops / Food retail Suggested for

Bars/Cafes

# **Aesthetics**

Door with stainless

steel stripes

Yes

Logo Serie Smeg printed

Alfa

Colour

Stainless steel Yes

**Controls** 

Front panel

Timer setting range 1-60 minutes + endless

**Options** 

Solutions K4610X

**Electrical Connection** 



Plug (I) Australia

# Construction

Oven materials Ever Clean enamel Engine speed Single speed **Cavity dimensions** 672x437x340mm Max standard speed 2

(lxdxh) motor rpm

Gross volume 670x560x420mm **Exhaust position** Back Net volume 670x560x420mm Timer type Electromecanical timer

Internal net volume 670x560x420mm 50-270°C Temperature range

achievement

dimensions

Removable deflector

Yes

Cavity material Stainless steel End cooking signal Yes

Shelves number Orange light indicator to Yes

Tray frame support Chrome Green light indicator to Yes Shelves distance 77 mm

achievement **Door construction** Double glass

Manual reset safety Yes Door opening **Tilting** thermostat Handle type Smeg

Openable glass Removable 2 Halogen lamps Lighting


1 contrarotating fan with Fan type and number Light power 40 W time direction reversal Power cable length 170 cm Ever Clean enamel **Engine speed** 


Back panel Galvanized


**IPX** protection Scheduled start H/12


# **Logistic Information**

Net weight 56,000 kg Height (mm) packed 640 mm Packed width 960 mm 64,000 Gross weight (kg) Packaged depth 845 mm Packed product 640x960x845











# **Compatible Accessories**



3743

Flat aluminium tray



#### 3751

Flat perforated aluminium tray



#### 3805

Flat chrome-plated wire grid



#### 3810

Corrugated grid for baquettes



## 3927

Air flow reducer kit



#### RGN11-420-2

Support rack for GN 1/1 flat trays, suitable for ALFA420/425/410 models



#### **RUTVL**

Wheels kit for all oven table models (4pcs)



#### SVRPP420-625

Connector kit for two stacked ALFA420+420 or ALFA420+625 models and hood



### T11TH20

2cm height GN1/1 non-stick tray for Galileo professional



## T11TH40

4cm height GN1/1 non-stick tray for Galileo professional



## T11XH20

2cm height aluminium GN1/1 tray for Galileo professional



#### T11XH65

6,5cm height aluminium GN1/1 tray for Galileo professional



#### TF11XH2

Perforated aluminium GN1/1 tray for Galileo professional



#### TMF11TH2

GN 1/1 non-sticking microperforated tray



# Symbols glossary



Electric





# Benefit (TT)

#### Mechanical control panel

Ease of use and effortless control of the essential cooking parameters

The control panel, equipped with practical knobs, allows for simple, intuitive, and effortless management of the main functions. Using the buttons, you can adjust the cooking time, temperature, and, in selected models, the level of humidification. By turning the knob to position 1, steam will be delivered until it is released. In multifunction ovens with a mechanical control panel, there is also a dedicated button for selecting different oven functions based on the desired cooking mode.

#### Clip-open

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.