ALFA410XUK

Product Family	Ovens
Subfamily	Convection oven 4 trays GN1/1
Power supply	Electric
Oven type	Convection oven
Oven controls	Mechanical
Tray capacity	4 teglie GN1/1
Default power supply	230 V~ / 13A / 2,7 kW / 50 Hz
App for recipe development and upload	Not available
Adjustable feet	Yes
Product dimensions WxDxH	798x747x563 mm
Maximum depth with open door	1145 mm



Target

Industries	Bar / Cafeterias / Bistros / Wine bars / Pubs, Hotels, Restaurants, Bakeries / Pastry shops, Butcher shops / Delicatessens, Catering, Care facilities, Commercial food services, Grocery shops / Food retail

Aesthetics

Door with stainless steel strip	Yes	**Front panel**	Yes
Colour	Stainless steel	**Series**	Alfa

Controls

Adjustable timer	1-60 minutes + continuous

Options

Condense hood	K4610X

Electrical Connection

Plug	UK 13 AMP

Construction


Oven material	Stainless steel/glass/plastics
Cavity dimensions (WxDxH)	672x437x340mm
Gross volume	670x560x420mm
Net volume	670x560x420mm
Internal net volume	75 lt
Cavity material	Stainless steel
No. of shelves	4
Tray support frame	Chrome
Distance between shelves	77 mm
Door construction	Yes
Door opening	Drop down
Handle type	Smeg
Inner glass	Removable
Fan type and number	1 contrarotating fan with time direction reversal
Fan motor power	180W
Fan speed	Single speed

Max motor speed (rpm)	2
Exhaust exit	Back
Time adjustment	Electromechanical timer
Temperature range	50-270°C
End of cooking alarm	Yes
Orange light indicator when t° achieved	Yes
Green light indicator when time achieved	Yes
Heating element interruption with open door	Yes
Manual safety thermostat reset	Yes
Removable deflector	Yes
No. of lights	2 Halogen lights
Light power	40 W
Power cable length	170 cm
Back panel	Galvanized
IPX protection	IPX3

Logistic Information

Packed product dimensions (WxDxH)	960x845x640 mm
EAN code	8017709358624

Net weight (kg)	51.100 kg
Gross weight (kg)	63.000 kg



Compatible Accessories



3927

Air flow reducer kit



RUTVL

Wheels kit for all oven table models (4pcs)



SVRPP420-625

Connector kit for two stacked ALFA420+420 or ALFA420+625 models and hood



T11TH20

2cm height GN1/1 non-stick tray for Galileo professional



T11TH40

4cm height GN1/1 non-stick tray for Galileo professional




T11XH20

2cm height aluminium GN1/1 tray for Galileo professional




T11XH65

6,5cm height aluminium GN1/1 tray for Galileo professional



TF11XH2

Perforated aluminium GN1/1 tray for Galileo professional



TMF11TH2

GN 1/1 non-sticking microperforated tray

Symbols glossary

 Electric

 Fan forced

Benefit

Mechanical control panel

Ease of use and effortless control of the essential cooking parameters

The control panel, equipped with practical knobs, allows for simple, intuitive, and effortless management of the main functions. Using the buttons, you can adjust the cooking time, temperature, and, in selected models, the level of humidification. By turning the knob to position 1, steam will be delivered until it is released.
In multifunction ovens with a mechanical control panel, there is also a dedicated button for selecting different oven functions based on the desired cooking mode.

Clip-open

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.