

# ALFA420E1HDS



<b>Family</b>	Professional ovens
<b>Subfamily</b>	Convection oven 4 trays EN 600x400 mm or GN1/1
<b>Power supply</b>	Electric
<b>Oven type</b>	Convection oven with humidification
<b>Oven control</b>	Electronic
<b>Trays capacity</b>	4 trays EN 600x400 mm, GN1/1 (min. H 20 mm)
<b>Power supply</b>	400 V 3N~ / 10 A / 6,9 kW / 50-60 Hz
<b>Other electrical connection</b>	230 V~ / 30 A / 6,9 kW / 50-60 Hz
<b>Program storage with application</b>	Not available
<b>Humidity generation</b>	Direct in cavity
<b>Adjustable feet</b>	Yes
<b>Product dimensions WxDxH</b>	798x747x563 mm
<b>Maximum depth with open door</b>	1145 mm



## Target

<b>Industries</b>	Bar / Cafeterias / Bistros / Wine bars / Pubs; Hotels; Restaurants; Bakeries / Pastry shops; Butcher shops / Delicatessens; Catering; Care facilities ; Commercial food services; Grocery shops / Food retail	<b>Suggested for</b>	Bakery
-------------------	--	----------------------	--------

## Aesthetics

<b>Series</b>	Alfa	<b>Digit display color</b>	White
<b>Colour</b>	Stainless steel	<b>Front panel</b>	Yes
<b>Door with stainless steel stripes</b>	Yes	<b>Logo</b>	Smeg printed
<b>Display type</b>	LCD Touch		

## Controls

<b>Storable programs number</b>	100	<b>Pre-heating</b>	Yes
<b>Timer setting range</b>	1-99 minutes + endless	<b>Chimney regulation</b>	Yes
<b>Cooking steps</b>	3 + pre-heating	<b>HACCP data</b>	Yes
<b>Delayed start</b>	Yes		

## Options


Combinable hood K4610X

## Construction


Oven materials	Stainless steel / glass / plastics	Humidification levels	5 + manual
Cavity dimensions (WxDxH)	672x437x340 mm	Exhaust position	Back
Gross volume	115,6 lt	Components cooling system	Yes
Net volume	104,2 lt	Timer type	Electrical
Internal net volume	75 lt	Temperature range	30-270°C
Cavity material	Stainless steel	End cooking signal	Yes
Shelves number	4	Safety switch with open door	Yes
Tray frame support	Chromed wire	Manual reset safety thermostat	Yes
Shelves distance	77 mm GN1/1 - EN 600X400	Predisposition for core probe	Yes
Door construction	Double glass	Removable deflector	Yes
Door opening	Tilting	Lighting	2 Halogen lamps
Handle type	Fixed	Light power	40 W
Glass	Openable with clip	USB port	Yes
Fan type and number	2 contrarotating with timed direction reversal	Water load pipe	Yes
Fan motor power	200W	Water inlet pressure	50-500 kPa (min-max)
Engine rpm	Dual speed	Power cable length	170 cm
Motor rpm in standard speed	2850 rpm	Back panel	Galvanized
Motor rpm in low speed	1450 rpm	IPX protection	IPX3
Water injection on each fan	Yes		

## Logistic Information

Net weight	63.000 kg	Height (mm) packed	640 mm
Packed width	960 mm	Gross weight (kg)	71.000
Packaged depth	845 mm	Packed product dimensions	



## Compatible Accessories



**3743**

Kit of 4 flat aluminum trays EN 600×400 mm



**3805**

Kit of 4 chrome-plated wire grids EN 600×400 mm




**3927**

Air flow reducer kit for ovens ALFA410, 420, 625, 1035



**RGN11-420-2**

Support rack for GN 1/1 flat trays, suitable for ALFA420/425/410 models



**SVRPP420-625**

Connector kit for two stacked ALFA420+420 or ALFA420+625 models and hood




**T11TH40**

GN1/1 non-stick tray, 40 mm height



**T11XH65**

GN1/1 aluminium tray, 65 mm height




**TMF11TH2**

GN 1/1 non-sticking microperforated tray, 20 mm height



**3751**

Flat perforated aluminium tray (4pcs)



**3810**

Kit of 4 wave wire grids for baguettes EN 600×400 mm



**KITSC**

Core temperature probe for EHDS oven series



**RUTVL**

Set of 4 wheels, fits all professional oven tables




**T11TH20**

GN1/1 non-stick tray, 20 mm height



**T11XH20**

Aluminium GN1/1 tray, 20 mm height



**TF11XH2**

GN 1/1 perforated aluminium tray, 20 mm height



**TVL425**

16-level tray holder rack for ALFA420/425 and ALFA625 ovens dim.800×800×900 mm (height with kit RUTVL: 998 mm)



#### **TVL425D**

4-level tray holder rack for  
ALFA420/ALFA425 (stacked) or  
ALFA1035 ovens, dim. 800x800x504  
mm (hieight with kit RUTVL: 602 mm)

---

## Symbols glossary

---



Electric



Core probe



Core probe baking by temperature difference ( $\Delta t$ )



Double speed fan



Fan forced heating



Fan forced heating with humidity injection

---

## Benefit (TT)

---

### Clip-open

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.

### Two-speed fan

Perfect ventilation for the ideal cooking of the most delicate dishes

The fan speed adjustment function allows you to tailor the ventilation intensity to the specific needs of each dish, ensuring consistently flawless results. Thanks to the dual-speed setting, you can create the perfect conditions for delicate preparations such as meringues, profiteroles, and soufflés, enveloping them in a gentler, more even airflow that preserves their lightness and structure.

### LCD Touch

Intuitive interface for simple and precise adjustment of cooking parameters

The control panel, simple and intuitive, is designed to offer a seamless and effortless user experience. Equipped with dedicated buttons, it allows precise adjustment of every cooking parameter, from temperature to duration, humidity level to fan speed. The central display provides a clear and immediate overview of the selected settings, ensuring you always have everything under control for flawless results, without compromise.

### 3 cooking stages

Flexibility and precision in every cooking stage

The ability to set multiple cooking steps in addition to preheating provides extraordinary versatility, perfectly adapting to the varying needs of each preparation. Each phase of the process can be customised with precision, optimising the cooking to achieve flawless results, whether it's a slow cook at low temperature or a perfect final browning. Thanks to this precise control of parameters, it is possible to achieve even cooking on every surface, significantly improving the quality of the finished product.

### Humidity management

Impeccable cooking thanks to precise humidity control

Thanks to the effective management of small amounts of humidity, perfect browning can be achieved while maintaining the product's softness and promoting the development of its internal structure. Different humidity levels can be set, which determine the frequency of activation cycles. Each cycle consists of two seconds of water vapour spraying inside the cooking chamber, followed by a 15-second pause.