

## **ALFA420EHDS**

Product Family Ovens

Subfamily 4 trays 600x400 mm o GN1/1
Oven type Fan with humidification

Default power supply  $400 \text{ V } 3N \sim / 10 \text{ A} / 6.9 \text{ kW} / 50-60 \text{ Hz}$ 

Other electrical connections  $230 \text{ V} \sim /30 \text{ A} / 6.9 \text{ kW} / 50-60 \text{ Hz}$ 

App for recipe development and

upload

Not available

Maximum depth with open door 1145 mm
Adjustable feet Yes
Net weight (kg) 62,000 kg

Product dimensions WxDxH 798x747x563 mm EAN code 8017709278274



### **Target**

Potential users

Bars/Cafes; Hotels; Restaurants/Catering; Bakery/Pastry making; Industrial pastry & bakery test kitchen; Butcher's

shops; QSR

Suggested for

Bars/Cafes

#### **Aesthetics**

Colour

Door with stainless

steel strip Display type Stainless steel

Yes

Yes

Digital display colour

Front panel

Logo

White Yes

Smeg printed

#### **Controls**

Number of recipes Adjustable timer

99

1 min - 99hrs + continuous

Cooking steps

**HACCP** data

9

Scheduled start H/12

## **Options**

Condense hood

K4610X

### Construction

Steam assisted levels 5 + manual

SMEG SPA 11/01/2025



Oven material Stainless

steel/glass/plastics

Cavity dimensions 672x437x340mm

(WxDxH)

 Gross volume
 670x560x420mm

 Net volume
 670x560x420mm

Internal net volume 75 lt

Cavity material Stainless steel

No. of shelves 4

Tray support frame Chrome
Distance between 77 mm

shelves

Door construction Yes

**Door opening** Drop down

Handle type Smeg

Inner glass Removable

Fan motor power 200W

Max motor speed (rpm) 2 Low motor speed (rpm) 2

Humidification system Yes

on each fan

Exhaust exit Back
Cooling system Yes

Time adjustment Electronic timer

Yes

Temperature range 50-280°C

End of cooking alarm Yes
Heating element Yes

interruption with open

door

Manual safety

thermostat reset

Core probe cooking with Yes

Δt

Removable deflector Yes


No. of lights 2 LED lights


Light power40 WUSB portYesWater connectionYes


Power cable length 170 cm

Back panel Galvanized

IPX protection Scheduled start H/12







- Q MORSETTO EQUIPOTENZIAL
- E CAVO ALIMENTAZIONE ELETTRI
- TUBO DI CARIO FILLER HOSE
- S TUBO DI SCARICO (solo su alcuni mode DRAIN HOSE (on some models only)
- TUBO DI CARICO PER DOCCETTA LA

SMEG SPA 11/01/2025



## Not included accessories



3743

Flat aluminium tray



3751

Flat perforated aluminium tray



3805

Flat chrome-plated wire grid



3810

Corrugated grid for baguettes



3927

Air flow reducer kit



**KITSC** 

Lower and upper shelf kit



RGN11-420-2

Support kit for grids or flat trays GN1/1 suitable for ALFA420/425/410 models



Conjunction kit for 2 ovens series 625/420 and hood



SMEG SPA 11/01/2025



# Symbols glossary

7 Co

Core probe



Fan forced



Fan with humidification



Double speed fan



Core probe +  $\Delta t$ 

SMEG SPA 11/01/2025