

ALFA420H-2

Family Ovens

Subfamily Convection oven 4 trays EN 600x400

mm or GN1/1

Oven type Fan with humidification

Oven control Mechanical

Trays capacity $4 \text{ trays } 600 \times 400 \text{ mm} - \text{GN1/1}$ Power supply $400 \text{ V } 3N \sim / 10 \text{ A / } 6.9 \text{ kW / } 50 \text{ Hz}$ Other electrical connection $230 \text{ V} \sim / 30 \text{ A / } 6.9 \text{ kW / } 50 \text{ Hz}$

Steam generation Direct

WiFi connection Not available
Maximum depth with open door 1145 mm
Adjustable feet Yes

Net weight 61,000 kg
Product dimensions WxDxH 798x747x563 mm

Distribution

Solutions Bars/Cafes; Hotels;

Restaurants/Catering; Bakery/Pastry making; Industrial pastry&bakery laboratories; Buthcher's

shops; QSR

Suggested for

Bars/Cafes

Aesthetics

Colour Stainless steel
Door with stainless Yes

Door with stainless Y steel stripes

Front panel Logo Yes

Smeg printed

Controls

Timer setting range 1-60 minutes + endless

Programs / Functions

Backing functions



Fan forced



Fan forced with humidification

Options

SMEG SPA 17/05/2024



Solutions

K4610X

Ever Clean enamel

672x437x340mm

Construction

Oven materials Cavity dimensions (lxdxh)

Gross volume 670x560x420mm
Net volume 670x560x420mm
Internal net volume 670x560x420mm
Cavity material Stainless steel

Shelves number Tray frame support

Shelves distance 77 mm

Door construction Double glass

Door openingTiltingHandle typeSmegOpenable glassRemovable

Fan type and number 2 contrarotating fans with time direction reversal

Chrome

Engine speed Ever Clean enamel
Engine speed Single speed

Max standard speed motor rpm

Humidification levels Manual

Exhaust position Back

Timer type Electromecanical timer

2

Yes

Yes

Yes

Temperature range 50-270°C End cooking signal Yes Orange light indicator t° Yes

achievement

Green light indicator t° achievement


Manual reset safety


thermostat

Removable deflector

Lighting 2 LED lamps
Light power 40 W
Water load pipe Yes
Power cable length 170 cm
Back panel Galvanized

IPX protection Scheduled start H/12







- Q MORSETTO EQUIPOTENZIALE EARTH TERMINAL
- E CAVO ALIMENTAZIONE ELETTRICA ELECTRICITY SUPPLY CABLE
- C TUBO DI CARICO (solo su alcuni modelli) FILLER HOSE (on some models only)

SMEG SPA 17/05/2024



Not included accessories



3805

Flat chrome-plated wire grid



3927

Air flow reducer kit



TF11XH2

Perforated aluminium GN1/1 tray for Galileo professional



3743

Flat aluminium tray



RGN11-420-2

Support kit for grids or flat trays GN1/1 suitable for ALFA420/425/410 models



TMF11TH2

GN 1/1 non-sticking microperforated tray



SVRPP625

Conjunction kit for 2 ovens series 625/420 and hood



T11XH20

2cm height aluminium GN1/1 tray for Galileo professional



SVRPP420-625

Connector kit for two stacked ALFA420+420 or ALFA420+625 models and hood



T11XH65

6,5cm height aluminium GN1/1 tray for Galileo professional



T11TH20

2cm height GN1/1 non-stick tray for Galileo professional



G11X8P

8 vertical GN1/1 chicken grid for Galileo professional



G11T

Non-stick GN1/1 tray for Galileo professional



3751

Flat perforated aluminium tray



3810

Corrugated grid for baguettes



SVRPP420

Conjunction kit between 2 ovens series 420/425 and hood



T8S11T

8 holes GN 1/1 non-sticking tray for Galileo professional



T11TH40

4cm height GN1/1 non-stick tray for Galileo professional

17/05/2024





Symbols glossary (TT)





SMEG SPA 17/05/2024