ALFA43XE

Family	Professional ovens
Subfamily	Convection oven 4 trays 435x320 mm
Oven type	Convection oven
Default power supply	230 V~ / 13 A / 3,0 kW / 50-60 Hz
Program storage with application	Not available
Adjustable feet	Yes
Product dimensions (WxDxH)	602x580x537 mm
Maximum depth with open door	993 mm



Target

Industries	Bar / Cafeterias / Bistros / Wine bars / Pubs, Hotels, Restaurants, Bakeries / Pastry shops, Food Industries, Food retail, QSR	**Destination**	Not available for EU market

Aesthetics

Door with stainless steel stripes	Yes	**Digit display color**	Red
		Front panel	Yes
Colour	Stainless Steel		

Controls

Timer setting range	1-99 minutes + endless

Options

60Hz version	Yes	**Combinable hood**	K43X

Accessories included

Aluminized tray 3820	kit of 4 pieces

Electrical Connection


Plug	(F;E) Schuko

Construction

Oven materials	Stainless steel / glass / plastics	**Motor rpm in standard speed**	2700 rpm
Cavity dimensions (WxDxH)	460x360x425 mm	**Humidification levels**	None
Internal net volume	54,5 lt	**Exhaust position**	Back
Cavity material	Ever Clean enamel	**Timer type**	Electrical
Shelves number	4	**Temperature range**	50-250°C
Tray frame support	Chromed wire	**End cooking signal**	Yes
Shelves distance	80 mm	**Manual reset safety thermostat**	Yes
Door construction	Double glass	**Removable deflector**	Yes
Door opening	Tilting	**Lighting**	1 Halogen lamp
Handle type	Fixed	**Light power**	40 W
Glass	Openable with clip	**Power cable length**	115 cm
Fan motor power	80 W	**Back panel**	Galvanized
Engine rpm	Single speed	**IPX protection**	IPX3

Logistic Information

Packed product dimensions (WxDxH)	625x695x610 mm	**Net weight**	32.800 kg
		Gross weight	34.900 kg
EAN code	8017709142872		




Compatible Accessories



3755

Kit of 4 perforated aluminum-coated sheet metal trays 435×320 mm



3780

Kit of 4 non-stick trays 435×320 mm



3926

Air flow reducer kit for ALFA43/425 ovens



4730

5-litre external tank kit for ALFA43 ovens

Symbols glossary



Fan forced heating

Benefit (TT)

Clip-open

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.