

ALFA625H-2



Family	Professional ovens
Subfamily	Convection oven 6 trays en 600x400 mm or GN1/1
Power supply	Electric
Oven type	Convection oven with humidification
Oven control	Manual
Trays capacity	6 trays EN 600x400 mm, GN1/1 (min. H 20 mm)
Power supply	400 V 3N~ / 16 A / 10,5 kW / 50 Hz
Other electrical connection	230 V 3~ / 16 A / 10,5 kW / 50 Hz
Program storage with application	Not available
Humidity generation	Direct in cavity
Adjustable feet	Yes
Product dimensions WxDxH	798x757x793 mm
Maximum depth with open door	1521 mm



Target

Industries	Bar / Cafeterias / Bistros / Wine bars / Pubs; Hotels; Restaurants; Bakeries / Pastry shops; Butcher shops / Delicatessens; Catering; Care facilities ; Commercial food services; Grocery shops / Food retail	Suggested for	Bakery
-------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------	--------

Aesthetics

Series	Alfa	Front panel	Yes
Colour	Stainless steel	Logo	Smeg printed
Door with stainless steel stripes	Yes		

Controls

Timer setting range	1-60 minutes + endless	Chimney regulation	Manual
----------------------------	------------------------	---------------------------	--------

Options




Right hand hinge	ALFA625HR-2	Combinable hood	K4610X
-------------------------	-------------	------------------------	--------

Construction

Oven materials	Stainless steel / glass / plastics	Humidification levels	1 Manual
Cavity dimensions (WxDxH)	672x437x546 mm	Exhaust position	Back
Gross volume	184,8 lt	Timer type	Electric
Net volume	165,6 lt	Temperature range	50-270°C
Internal net volume	127,3 lt	End cooking signal	Yes
Cavity material	Stainless steel	Orange light indicator for t° achievement	Yes
Shelves number	6	Green light indicator time achievement	Yes
Tray frame support	Chromed wire	Safety switch with open door	Yes
Shelves distance	77 mm GN1/1 - EN 600X400	Manual reset safety thermostat	Yes
Door construction	Double glass	Removable deflector	Yes
Door opening	Lateral - left hinge	Lighting	2 Halogen lamps
Handle type	Rotating	Light power	40 W
Glass	Openable with hinge	Water load pipe	Yes
Fan type and number	2 contrarotating with timed direction reversal	Water inlet pressure	50-500 kPa (min-max)
Fan motor power	180W	Power cable length	170 cm
Engine rpm	Single speed	Back panel	Galvanized
Motor rpm in standard speed	2850 rpm	IPX protection	IPX3
Water injection on each fan	Yes		


Logistic Information

Net weight	76,000 kg	Height (mm) packed	820 mm
Packed width	960 mm	Gross weight (kg)	93,000
Packaged depth	890 mm	Packed product dimensions	



1	ALIMENTAZIONE ELETTRICA - POWER SUPPLY
2	MORSETTO EQUIPOTENZIALE - EARTH TERMINAL
3	INGRESSO ACQUA 3/4" GAS MASCHIO - WATER INLET 3/4" GAS MALE
4	USCITA FUMI CALDI - HOT EXHAUST OUTLET
5	TARGHETTA CARATTERISTICHE TECNICHE - TECHNICAL SPECIFICATION LABEL

Compatible Accessories



3743

Kit of 4 flat aluminum trays EN 600×400 mm



3751

Flat perforated aluminium tray (4pcs)



3805

Kit of 4 chrome-plated wire grids EN 600×400 mm




3810

Kit of 4 wave wire grids for baguettes EN 600×400 mm



3927

Air flow reducer kit for ovens ALFA410, 420, 625, 1035



RGN11-625-2

Support rack for GN 1/1 flat trays, suitable for ALFA625 models



RUTVL

Set of 4 wheels, fits all professional oven tables



SVRPP420-625

Connector kit for two stacked ALFA420+420 or ALFA420+625 models and hood



T11TH20

GN1/1 non-stick tray, 20 mm height



T11TH40

GN1/1 non-stick tray, 40 mm height




T11XH20

Aluminium GN1/1 tray, 20 mm height




T11XH65

GN1/1 aluminium tray, 65 mm height



TF11XH2

GN 1/1 perforated aluminium tray, 20 mm height



TMF11TH2

GN 1/1 non-sticking microperforated tray, 20 mm height



TVL425

16-level tray holder rack for ALFA420/425 and ALFA625 ovens dim.800x800x900 mm (height with kit RUTVL: 998 mm)



TVL425D

4-level tray holder rack for ALFA420/ALFA425 (stacked) or ALFA1035 ovens, dim. 800x800x504 mm (height with kit RUTVL: 602 mm)



TVL625D

Support for stacked ALFA625 ovens, dim. 800x800x300mm

Symbols glossary



Electric



Fan forced heating



Fan forced heating with humidity injection

Benefit (TT)

Mechanical control panel

Ease of use and effortless control of the essential cooking parameters

The control panel, equipped with practical knobs, allows for simple, intuitive, and effortless management of the main functions. Using the buttons, you can adjust the cooking time, temperature, and, in selected models, the level of humidification. By turning the knob to position 1, steam will be delivered until it is released.

In multifunction ovens with a mechanical control panel, there is also a dedicated button for selecting different oven functions based on the desired cooking mode.

Hinged opening

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.

Humidity management

Impeccable cooking thanks to precise humidity control

Thanks to the effective management of small amounts of humidity, perfect browning can be achieved while maintaining the product's softness and promoting the development of its internal structure. Different humidity levels can be set, which determine the frequency of activation cycles. Each cycle consists of two seconds of water vapour spraying inside the cooking chamber, followed by a 15-second pause.