ALFA625H-2

Product Family	Ovens
Subfamily	Convection oven 6 trays en 600x400 mm or GN1/1
Power supply	Electric
Oven type	Fan with humidification
Oven controls	Mechanical
Tray capacity	6 trays EN 600x400 mm, GN1/1 (min. H 20 mm)
Default power supply	400 V 3N~ / 16 A / 10,5 kW / 50 Hz
Other electrical connections	230 V 3~ / 16 A / 10,5 kW / 50 Hz
App for recipe development and upload	Not available
Humidity generation	Direct in cavity
Adjustable feet	Yes
Product dimensions WxDxH	798x757x793 mm
Maximum depth with open door	1521 mm

Target

Industries	Bar / Cafeterias / Bistros / Wine bars / Pubs, Hotels, Restaurants, Bakeries / Pastry shops, Butcher shops / Delicatessens, Catering, Care facilities, Commercial food services, Grocery shops / Food retail

Aesthetics

Door with stainless steel strip	Yes	**Front panel**	Yes
Colour	Stainless steel	**Series**	Alfa

Controls

Adjustable timer	1-60 minutes + continuous	**Adjustable chimney**	Manual

Options

Right hand hinge	ALFA625HR-2	**Condense hood**	K4610X
Right hand hinge	ALFA1035EHDSR		

Construction

Oven material	Stainless steel/glass/plastics
Cavity dimensions (WxDxH)	672x437x546mm
Gross volume	460x360x425mm
Net volume	460x360x425mm
Internal net volume	127,3 lt
Cavity material	Stainless steel
No. of shelves	6
Tray support frame	Chrome
Distance between shelves	77 mm
Door construction	Yes
Door opening	Lateral
Handle type	New ergonomics
Inner glass	Openable
Fan type and number	2 contrarotating fans with time direction reversal
Fan motor power	180W
Fan speed	Single speed
Max motor speed (rpm)	2
Humidification system on each fan	Yes
Steam assisted levels	Manual
Exhaust exit	Back
Time adjustment	Electromechanical timer
Temperature range	50-270°C
End of cooking alarm	Yes
Orange light indicator when t° achieved	Yes
Green light indicator when time achieved	Yes
Heating element interruption with open door	Yes
Manual safety thermostat reset	Yes
Removable deflector	Yes
No. of lights	2 Halogen lights
Light power	40 W
Water connection	Yes
Water inlet pressure	50-500 kPa (min-max)
Power cable length	170 cm
Back panel	Galvanized
IPX protection	IPX3

Logistic Information

Packed product dimensions (WxDxH)	960x890x820 mm
EAN code	8017709270193
Net weight (kg)	74,600 kg
Gross weight (kg)	93,000 kg



Compatible Accessories

3743

Flat aluminium tray

3751

Flat perforated aluminium tray

3805

Flat chrome-plated wire grid



3810

Corrugated grid for baguettes

3927

Air flow reducer kit

RGN11-625-2

RUTVL

Wheels kit for all oven table models (4pcs)

SVRPP420-625

Connector kit for two stacked ALFA420+420 or ALFA420+625 models and hood

T11TH20

2cm height GN1/1 non-stick tray for Galileo professional

T11TH40

4cm height GN1/1 non-stick tray for Galileo professional

T11XH20

2cm height aluminium GN1/1 tray for Galileo professional

T11XH65

6,5cm height aluminium GN1/1 tray for Galileo professional



TF11XH2

Perforated aluminium GN1/1 tray for Galileo professional



TMF11TH2

GN 1/1 non-sticking microperforated tray

TVL425

16-level tray holder rack for ALFA410/ALFA420/425 and ALFA625 ovens dim.800x800x900 mm (hieight with kit RUTVL: 998 mm)

TVL425D

4-level tray holder rack for ALFA410/ALFA420/ALFA425 (stacked) or ALFA1035 ovens, dim. 800x800x504 mm (hieight with kit RUTVL: 602 mm)

TVL625D

Support for stacked ovens, dim. 800x800x300mm

Symbols glossary

Electric

Fan forced

Fan with humidification

Benefit

Mechanical control panel

Ease of use and effortless control of the essential cooking parameters

The control panel, equipped with practical knobs, allows for simple, intuitive, and effortless management of the main functions. Using the buttons, you can adjust the cooking time, temperature, and, in selected models, the level of humidification. By turning the knob to position 1, steam will be delivered until it is released.
In multifunction ovens with a mechanical control panel, there is also a dedicated button for selecting different oven functions based on the desired cooking mode.

Hinged opening

Easily accessible glass for effortless maintenance and cleaning

The glass panels are designed to be easily accessible and inspectable, ensuring great convenience during cleaning and maintenance operations. This feature significantly simplifies the process, making it quick and efficient, while ensuring that every intervention can be carried out with maximum comfort and complete safety.

Humidity management

Impeccable cooking thanks to precise humidity control

Thanks to the effective management of small amounts of steam, perfect browning can be achieved while maintaining the product's softness and promoting the development of its internal structure. Different humidity levels can be set, which determine the frequency of activation cycles. Each cycle consists of two seconds of water vapour spraying inside the cooking chamber, followed by a 15-second pause.