

BPW1260J-K5

Product Family	Bedpan washers
Type	Bedpan washer with manual opening
Intrastat	84222000
EAN code	8017709327521



Technical Features

Clogged drain safety system	Yes	Opening/closing door	Manual flap door
Maximum washing capacity	4 urinal bottles; 2 urinal bottles + 1 bedpan; 2 bedpans (optional)	Safety Door Lock	Yes, with electromagnetic release and automatic opening
Chemicals leaking safety control	Yes	Emergency opening system	Yes
Handle	Yes, recessed (for manual version)	Sprayer rotation control	Yes
Electrical main switch	Optional	Sky sprinkler	Yes
Door	1, swing door in stainless steel	Noise level (dbA)	<60 dBA

Programs

Standard programs stores

Urine bottles program	Bedpan normal program	Intensive bedpan program
-----------------------	-----------------------	--------------------------

Eco Standard programs stores

ECO urinal bottles program	ECO bedpan program	ECO Intensive Program for bedpans
----------------------------	--------------------	-----------------------------------

Optional programs installed in factory

Multifunctional support program	Clostridium Program
---------------------------------	---------------------

Program editing	Yes
Custom programs	Yes
Service programs	Yes

Custom programs start	Keyboard
Adjustable A0	Yes, from 60 to 6000
Standard programs start	Keyboard

Interface

Electronic control	Yes	Diagnosis	With software
WiFi connection	Optional	Display	LCD
RS232 serial port	Optional	Programme progress indicator	Yes
LAN port	Optional	End of cycle indicator	Yes
Traceability	At least the last 100 executed programs	Remaining duration display	Yes
Cycle Archive	Yes	Settable print languages	IT (Italiano), EN, DE, ES, FR, PL, PT
Download cycle	Optional through RS232 connection/ Optional, through LAN connection/ Yes, with USB pen drive	USB port	Yes

Construction

Washer Chamber Material	AISI 304; AISI 316 as optional	Integrated boiler	Yes
External material of the machine	AISI 304		

Equipments

Chemicals dosing	Standard for descaler	Descaler level sensor	Yes
Detergent level sensor	Included	Detergent compartment	Yes, for 2 x 5 liter cans
Steam Condenser	Yes	Acqua Stop	Yes
Detergent peristaltic dosing pump	Optional	Water supply pipe	3 / 4 "
Descaler peristaltic dosing pump	Yes	Drain supply pipe diameter	DN 110 mm

Options

3rd PT1000 temperature probe	Optional
Forced air vapor abatement system	Optional
Washing of two benpan in the same time	Optional
HEPA Filter	Optional
HEPA Filter Class	H14

Electrical Connection

Electrical connection	400V 3N AC 50Hz
Plug	Cable with free ends
Voltage (V)	400 V

Frequency (Hz)	50 Hz
60 Hz Possibility	Yes, on demand
Availability monophase version	Yes

Hydraulic connection

Cold water connection with acquastop	Yes
Max cold water hardness	42°f
Hot water connection with acquastop	Yes
Drain	Optional floor drain

Logistic Information

Net weight	100 kg
Width	600 mm
Depth	450 mm
Product dimensions	WxDxH 600x450x1600 mm
Product Height	1600 mm