

CPR115B3

| | |
|-------------------|--------|
| Product Family | Drawer |
| Commercial height | 14 cm |
| Type | Reheat |



Aesthetics

| | | | |
|-----------|--------------|---------------|-------------|
| Aesthetic | Linea | Front panel | Full glass |
| Colour | Black | Logo | Silk screen |
| Finishing | Glossy black | Logo position | External |
| Material | Glass | | |

Controls

| | | | |
|-----------------------------|------------------|-----------------|--------------|
| Type of control setting | Control knobs | Control knobs | Standard |
| Type of temperature control | Electro-mechanic | Controls colour | Steel effect |
| No. of controls | 1 | | |

Program / Functions

| | |
|-------------|-----|
| Defrost | Yes |
| Proofing | Yes |
| Mug warmer | Yes |
| Keep warm | Yes |
| Dish warmer | Yes |
| Reheating | Yes |

Technical Features

| | | | |
|----------------------|-----------------|---------------------|--------------|
| Opening mechanism | Push-pull | Type of heating | Fan assisted |
| Base material | Stainless steel | Minimum temperature | 30 °C |
| Max weight allowance | 15 kg | Maximum temperature | 80 °C |

| | | | |
|-------------------------------|-------|----------------------|-----------------------|
| Maximum drawer loading weight | 85 kg | Accessories included | Silicone antislip mat |
| Capacity | 21 l | | |

Electrical Connection

| | | | |
|---------------|--------------|----------------|-----------|
| Plug | (F;E) Schuko | Voltage (V) | 220-240 V |
| Nominal power | 400 W | Frequency (Hz) | 50-60 Hz |
| Current | 2 A | | |

Logistic Information

| | | | |
|------------|--------|---------------------|--------|
| Width (mm) | 597 mm | Product Height (mm) | 135 mm |
| Depth (mm) | 538 mm | | |



Compatible Accessories

KITCABLE90UK

Cable with IEC connector and UK plug