

CPV615NR

Product Family	Drawer
Commercial height	14 cm
Type	Sous-vide
Vitality system	Yes







Aesthetics

Aesthetics	Dolce Stil Novo	Glass type	Eclipse
Colour	Black	Front panel	With horizontal strip
Finishing	Gloss Black	Logo	Silk screen
Component finishing	Copper	Logo position	Inside
Material	Glass		







Controls

Type of control setting	Touch control
-------------------------	---------------

Program / Functions

Preservation cycle	
Vacuum in container cycle	
Chef function	
Welding	

Technical Features

						Opening mechanism	Push-pull	Safety solenoid valve anti oil reflux	Yes
						Base material	Stainless steel 304		
						Lid material	Tempered glass with frame		


Lid opening	65° +/- 3°	Dehumidification pump cycle	Yes, automatic
Drawer stabilisation device	Yes	Enabling vacuum bar lenght	260 mm
Drawer maximum protrusion	453 +/- 2 mm	Removable enabling vacuum bar	Yes
Max weight allowance	15 kg	Welding type	Double-phase
Maximum drawer loading weight	48 kg	Preservation cycle duration	1' - 1'20"
Capacity	6,5 l	Reachable vacuum	2-10 millibar (99,9%)
Pump flow	4 m³/h	Vacuum sensor	Yes, accuracy 10 mbar
		Accessories included	Bags for food conservation, Bags for sous-vide cooking

Electrical Connection

Plug	(F;E) Schuko	Voltage (V)	220-240 V
Nominal power	240 W	Frequency (Hz)	50-60 Hz
Current	1 A		

Logistic Information

Width (mm)	597 mm	Product Height (mm)	135 mm
Depth (mm)	570 mm		



Compatible Accessories



LIFEBOX

Set of 3 containers for vacuum drawer



VBAG1

Bags for sous-vide cooking and preservation, 20x30, 50 pieces



VBAG2

Bags for sous-vide cooking and preservation, 25x35, 50 pieces

Symbols glossary

	The Chef function alternates compression and decompression cycles and speeds up some operations, such as marinade or infusion, that otherwise would require a lot of time.		Preservation vacuum bags. These bags endure temperatures from -25°C to 70°C (for 2 hours) or 100°C (for 15 minutes). Suitable for pantry, refrigerator and freezer storage, they cannot be used for vacuum cooking.
	The vacuum in bag function guarantees to create vacuum into bags choosing among three levels. It is also possible to set the 0 level to seal the bag without creating the vacuum.		The stabilization device maintains the drawer open when used, avoiding closing it accidentally.
	Sous-vide cooking bags. These bags endure a maximum temperature of 85°C (for 75 hours), 100°C (for 4 hours) or 121°C (for 30 minutes). Suitable for pantry and refrigerator storage, they cannot be storage in the freezer.		The vacuum in container function guarantees to create vacuum into glass or plastic containers choosing among three different levels. Use only certificate containers suitable for vacuum and able to resist to a 99,9% vacuum.
	Setting the highest vacuum in bag/container level, it is reached a 99,9% vacuum.		The vacuum sensor guarantees the achievement of the maximum vacuum connected to the level set. If the value is not reached, the bag is not sealed.
	The machine can be set at three different sealing levels. Setting the maximum level is possible to seal more bags at the same time with a unique cycle.		The machine carries out a double phase welding which guarantees to seal dirty and oily bags as well.

Benefit

Push-pull door opening

Effortlessly open and close the drawer with a simple push mechanism

Preservation cycle

3 preservation cycles (delicate, preservation, sous vide)

Vacuum in container cycle

3 vacuum levels (delicate, medium, strong)

Chef function

Master impeccable marinades and infusions with the Chef Mode

Vitality System

The combined use of the steam oven, blast chiller and vacuum drawer allows the preservation of product characteristics and maximum flavour enhancement