

CVI338RX3



Family Installation Built-In Niche Defrost Cooling type Hinge type Hinge position

Wine Cooler Built-in 82-87 cm Automatic Fan assisted Standard Right



Wine cellar compartment features

Number of fixed shelves	2
Number of removable shelves	3
Shelves material	Wood
Removable shelves on telescopic guide rails	Yes
Type of internal light	Led
Air filter	Activated charcoal filter

Programs/Functions

2 LED DISPLAY			
Control setting	Touch control	Control lock	Yes
Controls	Inner, in the cellar	Lighting forced ON	In a maximum period
	compartment	Fan forced ON	Yes
Display	LED	Temperature Alarm	Yes
Functions display	Temperature alarm, Temperature value	Door open alarm	Yes
Power on lamp	Yes		

Technical Features

Adjustable temperature zones	2	Compressor type Refrigerant gas type	Low vibration compressor R600a
Independent cooling systems	2	Refrigerant Quantity (gr)	20 g
Number of door glasses	2		



Temperature range	5-20 °C	Foam agent	HFO
Type of temperature control	Electronic	Metal panel on the back of the fridge	Metal
Anti-UV door glass	Yes	Adjustable feet	2 Front + 2 Rear
Integrated heating element	Yes	Door opening type	With handle
Number of compressors	1		

Performance / Energy Label - Reg. 2019

Max Capacity (bottles 0,75lt)38Sum of the volumes of the chill compartment(s)114 IAnnual energy consumption140 kWh/aand the unfrozen compartment(s)InterformEnergy efficiency class Airborne acoustical noise emission classGClimate classSN, N, STEnergy efficiency class troal net volumeCEEI165 %Noise level38 dB(A) re 1 pW	G			
Ainductenergy140 kWi/dcompartment(s)consumptioncompartment(s)Energy efficiency classGClimate classSN, N, STAirborne acousticalCCEEI165 %noise emission classNoise level38 dB(A) re 1 pW		38	the chill compartment(s)	114
Airborne acousticalCEEI165 %noise emission classNoise level38 dB(A) re 1 pW	•••	140 kWh/a		
noise emission class Noise level 38 dB(A) re 1 pW	Energy efficiency class	G	Climate class	SN, N, ST
	Airborne acoustical	С	EEI	165 %
Total net volume 114	noise emission class		Noise level	38 dB(A) re 1 pW
	Total net volume	114		

Electrical Connection

A

Plug Electrical connection rating Current	(F;E) Schuko 40 W 0,4 A	Voltage (V) Frequency (Hz) Power supply cable length	220-240 ∨ 50 Hz 180 cm
	5566 138 458 20		
95° 95°	600 min. 300cm		



Symbols glossary



The automatic defrost system works by automatically defrosting at regular intervals eliminating the need to defrost altogether.

Energy efficiency class G



Ventilated: Forced distribution of cold air in the refrigerator compartment, which allows even temperature distribution within the fridge.



LED interior lighting: is a more energy efficient and long lasting way of illuminating the interior of the appliance.



Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button. A D



LED display: to show programmes, functions and options selected and the time to the end of the cycle.



Fingerprint proof stainless steel: Fingerprint proof stainless steel keeps stainless steel looking as good as new.



Built-in niche



Benefit (TT)

External handle

Handle with sober and elegant aesthetics, for easy door opening

UV-protected door glass

The UV-protected door glass protects the bottles from the passage of light into the wine cooler for impeccable storage

LED lights

LED lights ensure perfect multi-level visibility inside the wine cooler

Activated charcoal air filter

The activated charcoal air filter ensures excellent quality of the air and is easy to maintain

Touch Display

Touch display for an easy and accurate temperature management inside the refrigerated compartment

Low-vibration compressor

The low-vibration compressor avoids exposing the bottles to prolonged vibrations, which could compromise the quality of the wine

Telescopic guides

Telescopic sliding guides for easy extraction of wine bottles