

CVIA118RS2



| | |
|----------------|--------------|
| Family | Wine Cooler |
| Installation | Built-in |
| Built-In Niche | 45 cm |
| Defrost | Automatic |
| Cooling type | Fan assisted |
| Hinge type | Standard |
| Hinge position | Right |



Wine cellar compartment features



| | |
|---|---------------------------|
| Number of fixed shelves | 1 |
| Number of removable shelves | 2 |
| Shelves material | Wood |
| Removable shelves on telescopic guide rails | Yes |
| Type of internal light | Led |
| Air filter | Activated charcoal filter |

Programs/Functions



| | | | |
|-------------------|---|--------------------|---------------------|
| Control setting | Touch control | Control lock | Yes |
| Controls | External, in the door | Lighting forced ON | In a maximum period |
| Display | LED | Fan forced ON | Yes |
| Functions display | Temperature alarm, Temperature value | Temperature Alarm | Yes |
| Power on lamp | Yes | Door open alarm | Yes |

Technical Features

| | | | |
|------------------------------|---|---------------------------|--------------------------|
| Adjustable temperature zones | 1 | Number of compressors | 1 |
| Independent cooling systems | 1 | Compressor type | Low vibration compressor |
| Number of door glasses | 2 | Refrigerant gas type | R600a |
| | | Refrigerant Quantity (gr) | 18 g |

| | | | |
|-----------------------------|------------|---------------------------------------|-----------------------|
| Temperature range | 5-20 °C | Foam agent | Cyclopentane |
| Type of temperature control | Electronic | Metal panel on the back of the fridge | Metal |
| Anti-UV door glass | Yes | Door opening type | With push pull system |
| Integrated heating element | Yes | | |








Performance / Energy Label

| | | | |
|-------------------------------|--------------|-------------|------------------|
| Max Capacity (bottles 0,75lt) | 18 | Noise level | 38 dB(A) re 1 pW |
| Climatic class | SN, N, ST, T | | |

Electrical Connection

| | | | |
|------------------------------|-----------|---------------------------|---------------|
| Electrical connection rating | 40 W | Frequency (Hz) | 50 Hz |
| Current | 0.4 A | Power supply cable length | 150 cm |
| Voltage (V) | 220-240 V | Plug | (I) Australia |

Symbols glossary

- | | | | |
|--|---|---|--|
|  | The automatic defrost system works by automatically defrosting at regular intervals eliminating the need to defrost altogether. |  | A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed. |
|  | LED display: to show programmes, functions and options selected and the time to the end of the cycle. |  | Ventilated: Forced distribution of cold air in the refrigerator compartment, which allows even temperature distribution within the fridge. |
|  | LED interior lighting: is a more energy efficient and long lasting way of illuminating the interior of the appliance. |  | Built-in niche |
|  | Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button. | | |