# smeg

# CVIU338RX1

| | | |
|---|---|---|
| **Installation** | Built-in | |
| **Built-In Niche** | 82-87 cm | |
| **Defrost** | Automatic | |
| **Cooling type** | Fan assisted | |
| **Hinge type** | Standard | |
| **Hinge position** | Right | |

## Wine cellar compartment features

| | |
|---|---|
| **Number of fixed shelves** | 2 |
| **Number of removable shelves** | 3 |
| **Shelves material** | Wood |
| **Removable shelves on telescopic guide rails** | Yes |
| **Type of internal light** | Led |
| **Air filter** | Activated charcoal filter |

## Programs/Functions

| | | | |
|---|---|---|---|
| **Control setting** | Touch control | **Control lock** | Yes |
| **Controls** | Inner, in the cellar compartment | **Lighting forced ON** | In a maximum period |
| | | **Fan forced ON** | Yes |
| **Display** | LED | **Temperature Alarm** | Yes |
| **Functions display** | Temperature alarm, Temperature value | **Door open alarm** | Yes |
| **Power on lamp** | Yes | | |

## Technical Features

| | | | |
|---|---|---|---|
| **Adjustable temperature zones** | 2 | **Compressor type** | Low vibration compressor |
| **Independent cooling systems** | 2 | **Refrigerant gas type** | R600a |
| **Number of door glasses** | 2 | **Refrigerant Quantity (gr)** | 0.7 oz |

| | | | | |
|---|---|---|---|---|
| Temperature range | 5-20 °C | | Foam agent | HFO |
| Type of temperature control | Electronic | | Metal panel on the back of the fridge | Metal |
| Anti-UV door glass | Yes | | Adjustable feet | 2 Front + 2 Rear |
| Integrated heating element | Yes | | Door opening type | With handle |
| Number of compressors | 1 | | | |

## Performance / Energy Label - Reg. 2019

| | | | | |
|---|---|---|---|---|
| Max Capacity (bottles 0,75lt) | 38 | | Sum of the volumes of the frozen compartment(s) | 0.0 gal |
| Annual energy consumption | 130 KWh/year | | Sum of the volumes of the chill compartment(s) and the unfrozen compartment(s) | 30.6 gal |
| Airborne acoustical noise emission class | C | | | |
| Total net volume | 30.6 gal | | Climate class | SN, N, ST |
| | | | EEI | 153 % |

## Electrical Connection

| | | | | |
|---|---|---|---|---|
| Plug | (A) USA e Messico | | Voltage (V) | 115 V |
| Electrical connection rating | 40 W | | Frequency (Hz) | 50/60 Hz |
| Current | 0.4 A | | Power supply cable length | 70 7/8 " |

# Symbols glossary

The automatic defrost system works by automatically defrosting at regular intervals eliminating the need to defrost altogether.

Ventilated: Forced distribution of cold air in the refrigerator compartment, which allows even temperature distribution within the fridge.

LED interior lighting: is a more energy efficient and long lasting way of illuminating the interior of the appliance.

Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.

LED display: to show programmes, functions and options selected and the time to the end of the cycle.

Fingerprint proof stainless steel: Fingerprint proof stainless steel keeps stainless steel looking as good as new.

Built-in niche

# Benefit (TT)

### External handle

Handle with sober and elegant aesthetics, for easy door opening

### UV-protected door glass

The UV-protected door glass protects the bottles from the passage of light into the wine cooler for impeccable storage

### LED lights

LED lights ensure perfect multi-level visibility inside the wine cooler

### Activated charcoal air filter

The activated charcoal air filter ensures excellent quality of the air and is easy to maintain

### Touch Display

Touch display for an easy and accurate temperature management inside the refrigerated compartment

### Low-vibration compressor

The low-vibration compressor avoids exposing the bottles to prolonged vibrations, which could compromise the quality of the wine

### Telescopic guides

Telescopic sliding guides for easy extraction of wine bottles