

DF613PW



Product Family Dishwashers Commercial width 60 cm Commercial height 85 cm

Installation Free-standing N° baskets 3, FlexiDuo Motor Single phase **EAN** code 8017709226626



Programs















N. of programmes 5+5 quick programmes Auto sensor 45-65 Yes Washing temperatures 38, 45, 50, 65, 70 °C **ECO Quick** Yes Soak **Delicate and Quick** Yes Rapid 27' **Normal Quick** Yes Yes Glass Yes Super Yes **ECO** Yes Super Quick Yes

Options











Delay timer option 1/2 load FlexiZone

option

Options for tabs FlexiTabs

Up to 24 hours

Yes

Yes

Quick Time option Sanitizing option Hyclean

Yes Yes

Baskets





Basket colour

Basket components colour

Handle

Grey

Grey

In plastic on upper and

lower basket

Largest loadable dish in 23,5 cm

upper basket

With 4 foldable racks Lower Basket

Lower basket with anti- Yes

drip inserts



Upper Basket Height adjustment of the upper basket Upper basket with EasyGlide System

With central fixed racks On three levels (5 cm)

Yes

Largest loadable dish in 30,0 cm

lower basket

Cutlery basket 13 place settings sliding

Technical Features









Width (mm) 598 mm Depth (mm) 600 mm Display type LED (external) Product Height (mm) 848 mm Controls Electronic

Display Delayed start, Programme time indicator. Time to end

indication

Symbols and printed key Programme graphics

On/off indicator Yes Salt light indicator Light Light Rinse aid indicator **Progress indicator** Yes

End of cycle indicator On display, with acoustic

signal

Washing system Planetarium Third spray arm Single With electronic setting

Water softener

Turbidity sensor Aquatest

Flood protection system Total Acquastop

Water supply

Max water hardness Drying system

Tub material Filter

Concealed heating

element Hinges

Insulation level

Back cover

Depth of dishwasher with open door (mm)

Removable top

Top cover

Yes

Single; cold/hot water max. 60°C - energysave with hot

water up to 35%

100°fH;58°dH

Natural condenser drying

Stainless steel Stainless steel

Yes

Self balancing with fixed

hinges

Adjustable feet Just for levelling

Super

Yes, with covered counterweight

1168 mm

Yes, with optional KIT

In plastic

Electrical Connection

Connected power 1800 W Current 13 A 220-240 V Voltage Frequency (Hz) 50 Hz


Type of connection Power supply cable length

Plug

Single-phase 140 cm

(G) UK e Singapore







Compatible Accessories

KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable



KITINC

KITPLV2



Kit extension for dishwasher and washing machine: lenght mt. 2



Symbols glossary



The Aquatest sensor is an electronic sensor that measures the degree of water transparency at the end of the initial soaking phase. ased on the values measured, the sensor sets the most suitable programme, thus obtaining the best washing results with the minimum amount of water.



To improve the drying of dishes without leaving stains.



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Delay Timer: Option to postpone the start of the desired programme by up to 24 hours in order to programme the dishwasher to run at the desired time.



LED display: to show programmes, functions and options selected and the time to the end of the cycle.



EasyGlide: Convenient EasyGlide system for easy unloading of the appliance that allows reaching maximum flexibility of load of the machine.



FlexiDuo: The FlexiDuo 3rd cutlery basket allows you to arrange cutlery or small cups, ladles, or bulky utensils however you like: it consists of two separate and moveable modules.



Ideal for multi-function detergents, this option allows washing to be optimised, with full benefits from the combined-action tablets. When this option is activated, any salt and rinse aid is used.



FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.



Hyclean: When the HYCLEAN option is selected, the dishwasher performs a final 10 minute rinse at a high temperature of 70°C, eliminating virtually all bacteria to achieve the highest possible standards of cleanliness. The Hyclean option can be selected with almost all cycles at temperatures above 50°C.



Noise Level: Excellent insulation and special devices keep noise to a minimum.



The Planetarium washing system, with high rotations per minute, guarantees complete coverage of the tank, thanks to the simultaneous rotation of base and sprayers, and excellent washing results.



Auto 45°- 65°: The auto programme regulates the length of a cycle depending on the need for a pre-wash and the number of rinses required.



Delicate Quick: Program Delicate Quick is suitable for quick washing of delicate dishes.



Eco: Eco, this economic wash programme uses a low amount of water and energy in order to provide the most environmentally friendly cleaning option.



Eco: Eco, this economic wash programme uses a low amount of water and energy in order to provide the most environmentally friendly cleaning option.



Normal Quick: Program Normal Quick is suitable for quick washing of mixed dishes, for everyday use.



Soak programme: The soak programme provides a rinse to prevent dirt from drying.



PRG_STRONG_72dpi



Super Quick: The super Quick programme is suitable for removing stubborn dirt fast.





13 place settings: Number of place settings.



Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary.



System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher.