

DI262D



Product Family Width Commercial height Installation Kitchen panel N° baskets Motor EAN code Dishwashers 60 cm 82 cm Fully-integrated built-in Not supplied 2 Inverter 2.0 8017709337339



Programmes

60 ECO 50°	4UTO 50°-50°		
No. of programmes	8	ECO	Yes
Washing temperatures	50, 60 °C	Mix	Yes
Soak	Yes	Self clean	Yes
Full express - 60	Yes	Intense 60°	Yes
minutes		Auto 50°-60°	Yes
Express 50°	Yes		

Options



Delay timer option

Extreme option

Up to 24 hours, with automatic soak Yes

Crystal option	Yes
Sterilise option	Yes

Baskets

۲			
Basket colour	Grey	Lower Basket	With 2 foldable racks
Basket components colour	Grey	Lower basket with anti- drip inserts	Yes
Handle	In plastic on upper and lower basket	Largest loadable dish in lower basket	31.0 cm
Upper Basket Height adjustment of	With central fixed racks On two levels (4 cm)	Colour Inner Components	Blue
the upper basket		Cutlery basket	Yes



Largest loadable dish in 20,0 cm upper basket

Technical Features

Adultist Adultister			
Width (mm) Depth (mm) Display type Product Height (mm) Controls Display	596 mm 550 mm 3 digit 818 mm Electronic Delayed start, Programme time indicator, Time to end	Water supply Max water hardness Drying system	Single; cold/hot water max. 60°C - energysave with hot water up to 35% 90°fH; 50°dH Natural condenser drying, with Dry Assist + automatic door opening system at the end of the cycle
Programme graphics On/off indicator Salt light indicator Rinse aid indicator End of cycle indicator Washing system	On/off indicatorYesSalt light indicatorLightRinse aid indicatorLightEnd of cycle indicatorOn display, with acoustic signalWashing systemStandardWater softenerWith electronic settingTurbidity sensorYes	Steam protection Tank material Filter Concealed heating element Hinges Min. and max. frontal	In plastic Stainless steel Stainless steel Yes Self balancing, Sliding, FLEXIFIT 2 - 10 kg
Water softener Turbidity sensor Aquatest		panel weight Min. and max plinth height	40 - 175 mm
Flood protection system	Total Acquastop	Adjustable feet Additional gaskets Back cover Depth of dishwasher with open door (mm)	8cm, from 820 to 900mm Yes Yes 1230

Performance / Energy Label



Energy Efficiency Class
(Washing cycle)DEnergy consumption
[per 100 cycles, based
on the eco programme]84 KWhRated capacity (ps)13Water consumption [per
cycle]9,9 litres

Programme duration4:00 h:minAirborne acoustical46 dB(A) re 1 pWnoise emissions(spinning phase)Airborne acousticalCnoise emission classCEnergy efficiency Index49,9(EEI) (Washing cycle)C

Yes

Back feet adjustable

from front

Electrical Connection

Plug(G) UK e SingaporeFrequency (Hz)50 HzConnected power1800 WType of connectionSingle-phaseCurrent10 A10 ASingle-phase







Compatible Accessories



KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks

KITPL60N



Toekick Kit in Black colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

KITPLV2



Kit extension for dishwasher and washing machine: length mt. 2



KITPL60B

Toekick Kit in White colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

KITPL60X



Toekick Kit in Stainless Steel with adjustable height and deepness. Can be fitted over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.



Aquatest measures the clarity of the water

Symbols glossary

:::**/:::**



COMM_HEIGHT_82_72dpi

Option which improves the washing results of the selected programme. It increases the wash temperature and duration.

Anti-drip: Some models of dishwashers are

Noise Level: Excellent insulation and special devices keep noise to a minimum.

Normal programme: The normal programme is suitable for normal degrees of dirt for everyday

The symbols show the number of plate settings of the dishwasher.

This option provides special care for a delicate load. It prevents rapid changes in the wash temperature of the selected programme and

Option which provides better cleaning results by keeping the temperature between 65 and 70°C for at least 10 minutes during the last rinsing



000 9,9h System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher.

The work aimed at continuous improvement has allowed the creation of the second generation of the Inverter motor 2.0, characterised by greater efficiency and durability over time, which allows very high performance and a lower energy consumption and noise level.



Benefit

Flexifit hinge system

The Flexifit hinge system ensures smooth door movement, allowing for seamless integration into your kitchen design

The height of the plinth can vary from 5 cm to 21.5 cm, allowing it to fit perfectly into the cabinet. Thanks to this solution, the dishwasher blends harmoniously into its surroundings, with the door and plinth perfectly aligned with the other kitchen furniture.