
# DIL322BL



| | |
|---|---|
| **Product Family** | Dishwashers |
| **Width** | 60 cm |
| **Commercial height** | 82 cm |
| **Installation** | Fully-integrated built-in |
| **Kitchen panel** | Not supplied |
| **N° baskets** | 3, FlexiDuo |
| **Motor** | Inverter 2.0 |
| **EAN code** | 8017709364489 |

## Programmes

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| **No. of programmes** | 10+1 | **Auto sensor 45-65** | Yes |
| **Washing temperatures** | 38, 45, 50, 55, 65, 70, 75 °C | **Mix** | Yes |
| **Soak** | Yes | **Quiet (-2 dB)** | Yes |
| **Express 27'** | Yes | **Intense** | Yes |
| **Crystal** | Yes | **Self clean** | Yes |
| **Full express - 60 minutes** | Yes | **Hygiene 99,9%** | Yes |
| **ECO** | Yes | | |

## Options

| | | | |
|---|---|---|---|
| **Dry Assist+ option** | Yes | **1/2 load FlexiZone option (varied distribution)** | Yes |
| **Delay timer option** | Up to 24 hours, with automatic soak | **Special programs option** | Yes |

## Baskets

| | | | |
|---|---|---|---|
| **Basket colour** | Grey | **Lower Basket** | With 2 foldable racks |
| **Basket components colour** | Grey | **Lower basket accessories** | MultiLoad |
| | | **Lower basket with anti-drip inserts** | Yes |


| | |
|---|---|
| **Handle** | In plastic on upper and lower basket |
| **Upper Basket** | With 1 foldable rack |
| **Height adjustment of the upper basket** | On three levels |
| **Largest loadable dish in upper basket** | 19,0 cm |
| **Largest loadable dish in lower basket** | 30,0 cm |
| **Colour Inner Components** | Sage Leaf |

## Technical Features




| | |
|---|---|
| **Width (mm)** | 598 mm |
| **Depth (mm)** | 545 mm |
| **Display type** | 3 digit |
| **Product Height (mm)** | 818 mm |
| **Controls** | Electronic |
| **Display** | Delayed start, Programme time indicator |
| **Programme graphics** | Symbols |
| **On/off indicator** | Yes |
| **Salt light indicator** | Light |
| **Rinse aid indicator** | Light |
| **End of cycle indicator** | ActiveLight |
| **Auto switch-off** | Yes |
| **Washing system** | Orbital |
| **Third spray arm** | Single |
| **Water softener** | With electronic setting |
| **Turbidity sensor Aquatest** | Yes |
| **Flood protection system** | Total Acquastop |
| **Water supply** | Single; cold/hot water max. 60°C - energysave with hot water up to 35% |
| **Max water hardness** | 100°fH;58°dH |
| **Drying system** | Natural condenser drying, with Dry Assist + automatic door opening system at the end of the cycle |
| **Steam protection** | In plastic |
| **Tank material** | Stainless steel |
| **Filter** | Stainless steel |
| **Concealed heating element** | Yes |
| **Hinges** | Self balancing, Sliding, FLEXIFIT |
| **Min. and max. frontal panel weight** | 2 - 11 kg |
| **Min. and max plinth height** | 50 - 215 mm |
| **Adjustable feet** | 7cm, from 820 to 890 mm |
| **Back cover** | Yes |
| **Depth of dishwasher with open door (mm)** | 1146 mm |
| **Back feet adjustable from front** | Yes |
| **Top cover** | In plastic |


## Performance / Energy Label




| | |
|---|---|
| **Energy Efficiency Class (Washing cycle)** | B |
| **Energy consumption [per 100 cycles, based on the eco programme]** | 63 kWh |
| **Rated capacity (ps)** | 13 |
| **Water consumption [per cycle]** | 9,0 litres |
| **Programme duration** | 4:25 h:min |
| **Airborne acoustical noise emissions (spinning phase)** | 42 dB(A) re 1 pW |
| **Airborne acoustical noise emission class** | B |
| **Energy efficiency Index (EEI) (Washing cycle)** | 37,9 |

## Electrical Connection

| | | | |
|---|---|---|---|
| **Connected power** | 1800 W | **Type of connection** | Single-phase |
| **Current** | 13 A | **Power supply cable length** | 140 cm |
| **Voltage** | 220-240 V | | |
| **Frequency (Hz)** | 50 Hz | **Plug** | (G) UK e Singapore |



## Compatible Accessories



**KIT82CN**



**KIT82CX**



**KIT82SPRAN**



**KIT82SPRMW**




**KIT82SPRX**

**KITFLEXI**



Kit for 60cm dishwashers with FlexiFit hinges for door panel weight >11 kg (max 15 kg 82 cm and 13,5 kg 86 cm)

**KITGH**



Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks

**KITPL60B**



Toekick Kit in White colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

**KITPL60N**



Toekick Kit in Black colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

**KITPL60X**



Toekick Kit in Stainless Steel with adjustable height and deepness. Can be fitted over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.

**KITPLV2**



Kit extension for dishwasher and washing machine: length mt. 2

# Symbols glossary




Activelight is an led light which projects a red spot onto the floor beneath the dishwasher when the appliance is in use.



Anti-drip: Some models of dishwashers are equipped with special polymer nozzles anti-drip, that improve the process of drying.




COMM_HEIGHT_82_72dpi




The Dry Assist + option, in addition to saving energy, ensures perfect drying of the dishes by opening the door automatically at the end of the wash c




Models with new Flexi Fit hinges are able to be installed in kitchens with a plinth of just 5cms. With this new hinge design, the panel has a sliding movement from the bottom to the top, avoiding any possible interference of the panel with the plinth.







Noise Level: Excellent insulation and special devices keep noise to a minimum.




Auto 45°- 65°: The auto programme regulates the length of a cycle depending on the need for a pre-wash and the number of rinses required.




Eco: Eco, this economic wash programme uses a low amount of water and energy in order to provide the most environmentally friendly cleaning option.



Soak programme: The soak programme provides a rinse to prevent dirt from drying.




Ultraclean: The Ultraclean option performs a final rinse at a high temperature of 70°c eliminating virtually all bacteria.




Aquatest measures the clarity of the water during an auto program, and automatically ensures the minimum consumption of water and energy.




Energy efficiency class B



Delay Timer: The delay timer can postpone the start of the program by up to 24 hours.



FlexiDuo: The FlexiDuo 3rd cutlery basket allows you to arrange cutlery or small cups, ladles, or bulky utensils however you like: it consists of two separate and moveable modules.




FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.




The work aimed at continuous improvement has allowed the creation of the second generation of the Inverter motor 2.0, characterised by greater efficiency and durability over time, which allows very high performance and a lower energy consumption and noise level.




Orbital wash system distributes water evenly throughout the 60cm dishwasher cavity, directing water with precision to ensure an excellent wash.




Crystals: The Crystals programme is dedicated to delicate dishes such as glasses and china.




Normal programme: The normal programme is suitable for normal degrees of dirt for everyday use.




Rapid 27 Mins: The rapid 27 mins quick program takes just 27 minutes to wash a load.




The symbols show the number of plate settings of the dishwasher.

Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary.

Quick wash cycle for normally soiled mixed loads such as dishes and pans, even with dried-on residues. Dishes are washed and dried in 60 minutes.

SILENT: Wash cycle suitable for normally soiled dishes, even with dried-on residues. Ensures maximum noise reduction and is therefore ideal if you wish to run it during the night.

HYGIENE 99.9% High-temperature washing programme. The 75° rinse guarantees the removal of 99.9% of germs and bacteria, making it ideal for sanitising

System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher.

Dishwasher cleaning cycle. The cycle should be started with the machine empty, without dishes. It is recommended to run the program every 2-3 months, using special dishwasher detergents.

Allows you to enable additional programs when selected together with any wash cycle.