

DW7QSXSA-1



Product Family Dishwashers Commercial width 60 cm Commercial height 85 cm

Installation Free-standing N° baskets 3, FlexiDuo EAN code 8017709273118



Yes

Yes

Yes

Yes

Programs



















N. of programmes

Washing temperatures

Rapid 27'

Express 27'

Glass **ECO**

Green express

Normal Mix

Ultraclean

10+1

38, 45, 50, 65, 70 °C

Yes

Yes Yes

Yes

Yes

Intense

Self clean Hygiene 99,9%

1/2 load

Delicate

ECO Quick

Delicate and Quick Normal Quick

Strong and fast

Express 60' Yes

Options









Dry Assist+ option **Delay timer option**

Extra dry option

1/2 load FlexiZone

option

Yes

Up to 24 hours

Yes

Options for tabs FlexiTabs

Quick Time option

Special programs option Yes

Baskets





Basket colour Grey Largest loadable dish in 19,0 cm

upper basket

Basket components Grey
colour Lower Basket With 2 foldable racks

Handle In plastic on upper and Lower basket with anti-Yes lower basket drip inserts

Upper Basket With 1 foldable rack Largest loadable dish in 30,0 cm

Height adjustment of On three levels (5 cm) lower basket
the upper basket Colour Inner Blue anti drop inserts, Blue

Components

handles, Blue Orbital

Technical Features

Width (mm) 598 mm Water softener With electronic setting

Depth (mm) 600 mm Flood protection system Total Acquastop

Display type LED display (3 digit) Water supply Single; cold/hot water max.

Product Height (mm)848 mm60°C - energysave with hotControlsElectronic

Display

Delayed start, Programme
time indicator. Time to end

Drying system

Max water hardness
100°fH;58°dH
Drying system
Natural condenser drying

time indicator, Time to end **Drying system** Natural conder indication **Tub material** Stainless steel

Programme graphicsSymbolsFilterStainless steelOn/off indicatorYesConcealed heatingYes

Salt light indicator

Rinse aid indicator

Light

Light

Light

Hinges

Self balancing with fixed

Progress indicator
Yes

End of cycle indicator
On display, with acoustic

Adjustable feet
Just for levelling

signal Back cover Yes, with covered counterweight

Third spray arm Single Depth of dishwasher 1168 with open door (mm)

Removable top Yes, with optional KIT

Electrical Connection


Voltage

Plug(M) Sud AfricaFrequency (Hz)50 HzConnected power1800 WType of connectionSingle-phaseCurrent10 APower supply cable140 cm

220-240 V

length







Compatible Accessories

KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable



KITINC

KITPLV2



Kit extension for dishwasher and washing machine: lenght mt. 2



Symbols glossary



To improve the drying of dishes without leaving stains.





Delay Timer: Option to postpone the start of the desired programme by up to 24 hours in order to programme the dishwasher to run at the desired time.



The Dry Assist + option, in addition to saving energy, ensures perfect drying of the dishes by opening the door automatically at the end of the washing cycle.



Fingerprint proof stainless steel: Fingerprint proof stainless steel keeps stainless steel looking as good as new.



FlexiDuo: The FlexiDuo 3rd cutlery basket allows you to arrange cutlery or small cups, ladles, or bulky utensils however you like: it consists of two separate and moveable modules.



FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.



GREEN EXPRESS Washing programme with low water and energy consumption.



Noise Level: Excellent insulation and special devices keep noise to a minimum.



Orbital wash system distributes water evenly throughout the 60cm dishwasher cavity, directing water with precision to ensure an excellent wash.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



Eco: Eco, this economic wash programme uses a low amount of water and energy in order to provide the most environmentally friendly cleaning option.



Mix: The Mix programme is suitable for mixed crockery and everyday pots and pans, without any particular incrustation.



Dishwasher cleaning cycle. The cycle should be started with the machine empty, without dishes. It is recommended to run the program every 2-3 months, using special dishwasher detergents.



Soak programme: The soak programme provides a rinse to prevent dirt from drying.



Express 27': The Express 27' programme is a quick wash cycle, at low temperatures, for lightly soiled dishes.



Ultraclean: The Ultraclean option performs a final rinse at a high temperature of 70°c eliminating virtually all bacteria.



14 place settings: Number of place settings.



Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary.



System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher.



Allows you to enable additional programs when selected together with any wash cycle. After having selected the required wash cycle, press the button (



HYGIENE 99.9% High-temperature washing programme. The 75° rinse guarantees the removal of 99.9% of germs and bacteria.



Benefit (TT)

FlexiDuo

The flexible third basket provides additional space, adapting to the load to accommodate various types of dishes, ensuring optimal organization and efficient use of interior capacity

The third FlexiDuo basket consists of two separate sections that can be handled independently of each other, stacked and/or removed, offering loading flexibility for every need. Depending on the arrangement, it allows cups, tall glasses, bulky utensils and pots and pans to be placed in the upper basket.

Orbital Wash System

Even water distribution, deep cleaning and low noise thanks to the dual rotating spray arms

Orbital washing system, which, thanks to its double arm, its 7 water exit points and thanks to overlapping and simultaneous rotations and 40 rotations per minute, allows ample coverage of the tank area, thus guaranteeing optimal results in any basket-loading configuration.

DryAssist+

The Dry Assist+ system of automatic door opening at the end of the cycle ensures fast and energy-efficient drying