

DW8220



| | |
|-------------------|---------------------------|
| Product family | Dishwashers |
| Width | 24" |
| Commercial height | 82 cm |
| Installation | Fully-integrated built-in |
| N° baskets | 3, Flexi |
| EAN code | 8017709354251 |



Programs



| | | | |
|----------------------|-----------------------|-------------|-----|
| Number of programs | 10 | Express 60° | Si |
| Washing temperatures | 30, 50, 55, 70, 75 °F | Delicates | Yes |
| Express 27' | Yes | Normal | Yes |
| Automatic | Yes | Rinse | Yes |
| Intense | Yes | Eco express | Yes |
| Self Clean | Yes | Pots & Pans | Yes |

Options



| | | | |
|----------------------------|----------------|-------------------------------|-----|
| Dry Assist+ option | Yes | Intensive washing zone option | |
| Delay start | Up to 24 hours | Special programs option | Yes |
| FlexiZone half-load option | Yes | | |

Baskets




| | | | |
|---------------------------------------|-----------------------|-------------------------------------|-----------|
| Basket color | Gray | Lower basket accessories | MultiLoad |
| Upper basket | 1 foldable rack | Lower basket with anti-drip inserts | Yes |
| Upper basket height adjustment | On 3 levels | Colour Inner Components | Sage Leaf |
| Largest loadable dish in upper basket | 25,0 inches | | |
| Lower basket | With 2 foldable racks | | |

Cutlery basket

13 place settings

Technical Features



| | |
|----------------------------|---|
| Width | 23 9/16 " |
| Depth | 21 7/16 " |
| Display type | LED display (3 digits) |
| Height | 32 3/16 " |
| Display | Delay start, Program progress indicator |
| On/off indicator | Yes |
| Salt indicator | Light |
| Rinse aid indicator | Light |
| Program progress indicator | Yes |
| End-of-cycle indicator | Acoustic signal |
| Washing system | Orbital |
| Third spray arm | Single |
| Water softener | With electronic setting |

| | |
|------------------------------------|---|
| Turbidity sensor | Yes |
| Aquatest | |
| Flood protection system | Single Aquastop |
| Max water hardness | 100°FH;58°dH |
| Drying system | Natural condenser drying, with Dry Assist + automatic door opening system at the end of the cycle |
| Tub material | Stainless steel |
| Filter | Stainless steel |
| Concealed heating element | Yes |
| Hinges | Self-balancing, Sliding, FLEXIFIT |
| Min. and max. frontal panel weight | 4.4 - 24.3 lbs |
| Min. and max plinth height | 50 - 215 mm |
| Adjustable feet | 2 3/4", from 32 1/4" to 35" |
| Additional gaskets | Yes |
| Back cover | Yes |

Electrical Connection

| | | | |
|-----------------|----------------|---------------------------|--------------|
| Plug | (B) NEMA 5-15P | Frequency (Hz) | 60 Hz |
| Connected power | 1100 W | Connection type | Single-phase |
| Current | 13 A | Power supply cable length | 140 " |
| Voltage | 115 V | | |

Compatible Accessories



KIT82CN



KIT82SPRAN



KIT82SPRX



KIT82CX




KIT82SPRMW



KITFLEXI



KITJBDW



KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks



KITPL60B

Toekick Kit in White colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.



KITPL60N

Toekick Kit in Black colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.



KITPL60X























Toekick Kit in Stainless Steel with adjustable height and deepness. Can be fitted over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.



KITPLV2

Kit extension for dishwasher and washing machine: lenght mt. 2

Symbols glossary

| | | | |
|--|--|---|---|
|  | Acquastop: Some Smeg dishwashers are equipped with a simple Acquastop: float sensor in the bottom which is necessary to prevent an accidental leakage of water inside the appliance. |  | Aquatest measures the clarity of the water during an auto program, and automatically ensures the minimum consumption of water and energy. |
|  | Anti-drip: Some models of dishwashers are equipped with special polymer nozzles anti-drip, that improve the process of drying. |  | COMM_HEIGHT_82_72dpi |
|  | Delay Timer: The delay timer can postpone the start of the program by up to 24 hours. |  | Models with new Flexi Fit hinges are able to be installed in kitchens with a plinth of just 5cms. With this new hinge design, the panel has a sliding movement from the bottom to the top, avoiding any possible interference of the panel with the plinth. |
|  | FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed. |  | Inverter technology: The evolution of Smeg's driers towards more intelligent and environmentally sustainable models has led to the choice of using Inverter technology with heat pumps, which reduces significantly energy consumption. |
|  | Noise Level: Excellent insulation and special devices keep noise to a minimum. |  | Orbital wash system distributes water evenly throughout the 60cm dishwasher cavity, directing water with precision to ensure an excellent wash. |
|  | Auto 45°- 65°: The auto programme regulates the length of a cycle depending on the need for a pre-wash and the number of rinses required. |  | Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled. |
|  | PRG_RINSE_72dpi |  | Rapid 27 Mins: The rapid 27 mins quick program takes just 27 minutes to wash a load. |
|  | Ultraclean: The Ultraclean option performs a final rinse at a high temperature of 70°C eliminating virtually all bacteria. |  | The symbols show the number of plate settings of the dishwasher. |
|  | System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher. |  | ... |
|  | ... |  | ... |
|  | ... |  | The Dry Assist + option, in addition to saving energy, ensures perfect drying of the dishes by opening the door automatically at the end of the wash c |

Benefit (TT)

Orbital Wash System

Even water distribution, deep cleaning and low noise thanks to the dual rotating spray arms

Orbital washing system, which, thanks to its double arm, its 7 water exit points and thanks to overlapping and simultaneous rotations and 40 rotations per minute, allows ample coverage of the tank area, thus guaranteeing optimal results in any basket-loading configuration.

Flexifit hinge system

Smooth-running door for optimal integration into the kitchen design

The height of the plinth can vary from 5 cm to 21.5 cm, allowing it to fit perfectly into the cabinet. Thanks to this solution, the dishwasher blends harmoniously into its surroundings, with the door and plinth perfectly aligned with the other kitchen furniture.

DryAssist+

The Dry Assist+ system of automatic door opening at the end of the cycle ensures fast and energy-efficient drying