
DW8601



Product Family	Dishwashers
Commercial height	STANDARD HEIGHT
Installation	Fully-integrated built-in
Kitchen panel	Not supplied
N° baskets	2
Motor	Inverter
EAN code	8017709364359
UPC Code	812895027730

Programs

N. of programmes	8	**Auto**	Yes
Washing temperatures	45, 50, 55, 65 °F	**Super**	Yes
Light soiling	Yes	**Regular**	Yes
Ultraclean	Yes	**Intensive 65°**	Yes
Intense		**Intensive 70°**	
Delicate	Yes	**Rinse**	Yes

Options

Hi-Temp	Yes	**Delay timer option**	Up to 24 hours
Extra Fast	Yes	**Extra dry option**	Yes
Sanitize	Yes	**1/2 load FlexiZone option**	Yes
Silent	Yes		

Baskets


Basket colour	Grey	**Height adjustment of the upper basket**	On two levels (5cm)
Basket components colour	Grey	**Lower Basket**	With 4 foldable racks
Handle	In plastic on upper and lower basket	**Colour Inner Components**	Grey
Upper Basket	With 2 foldable racks	**Cutlery basket**	Yes

Technical Features

Width (mm)	23 9/16 "	**Flood protection system**	Single Acquastop
Depth (mm)	21 5/8 "	**Drying system**	Natural condenser drying
Display type	LED display (3 digit)	**Tub material**	Stainless steel
Product Height (mm)	33 7/8 "	**Filter**	Stainless steel
Controls	Electronic	**Concealed heating element**	Yes
Display	Delayed start, Programme time indicator	**Hinges**	Self balancing with fixed hinges
Programme graphics	Written in EN	**Can be installed in-column**	Yes
On/off indicator	Yes	**Adjustable feet**	5cm, from 820 to 870 mm
Rinse aid indicator	Light	**Airborne acoustical noise emissions dBA**	45 dBA
End of cycle indicator	On display, with acoustic signal	**Back feet adjustable from front**	Yes
Washing system	Standard	**Energy Star**	Yes
Turbidity sensor Aquatest	Yes		

Electrical Connection

Connected power	1400 W	**Type of connection**	Single-phase
Current	12 A	**Power supply cable length**	116 "
Voltage	120 V	**Plug**	(B) NEMA 5-15P
Frequency (Hz)	60 Hz		



Symbols glossary



Acquastop: Some Smeg dishwashers are equipped with a simple Acquastop: float sensor in the bottom which is necesary to prevent an accidental leakage of water inside the appliance.



The Aquatest sensor is an electronic sensor that measures the degree of water transparency at the end of the initial soaking phase. ased on the values measured, the sensor sets the most suitable programme, thus obtaining the best washing results with the minimum amount of water.



Installation in column: Installation in column



Delay Timer: Option to postpone the start of the desired programme by up to 24 hours in order to programme the dishwasher to run at the desired time.



FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.



Smeg's evolution towards more intelligent and eco-friendly models has led to the choice of Inverter technology, which significantly reduces consumption.



Noise Level: Excellent insulation and special devices keep noise to a minimum.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



PRG_RINSE_72dpi



PRG_STRONG_72dpi



14 place settings: Number of place settings.



EXTRA DRY This option adds a hot rinse cycle that ensures improved drying.



The Regular programme is for dishes with regular dirt, even with dried-on residues.



LIGHT SOILING Washing programme with low water and energy consumption.