

DWA615DX3



Product Family Dishwashers Commercial width 60 cm Commercial height 85 cm

Installation Free-standing N° baskets 3, FlexiDuo Motor Single phase EAN code 8017709310950



Programs

























N. of programmes 10 + 1Washing temperatures 38, 45, 50, 55, 65, 70, 75 °C Soak Express 27' Yes Crystal Yes Full express - 60 Yes minutes

Auto sensor 45-65 Yes Intense Self clean Sterilise

1/2 load **Delicate** Regular **Normal ECO**

Yes Yes Yes Yes

Yes

Yes

Yes

Options









Dry Assist option Dry Assist+ option

Delay timer option

Yes

Up to 24 hours

1/2 load FlexiZone

option

Options for tabs

FlexiTabs

Special programs option Yes

Baskets





Basket colour

Basket components

colour

Grey Grey Largest loadable dish in 19,0 cm

upper basket

Lower Basket

With completely foldable racks and glass holder

8/09/2025 **SMEG SPA**



Handle

In plastic with stainless steel insert on upper and

lower basket

Upper Basket Glass holder

With 1 foldable rack

Height adjustment of

the upper basket Upper basket with EasyGlide System

Yes

On three levels

Yes

Lower basket with anti- Yes

drip inserts

Largest loadable dish in 30,0 cm

lower basket

Colour Inner

Components

Cutlery basket 13 place settings sliding

Blue

Technical Features









Width (mm) Depth (mm) Display type

LED (external) Product Height (mm) 848 mm

Controls

Display Delayed start, Programme time indicator, Time to end

indication

Programme graphics On/off indicator Salt light indicator Rinse aid indicator **Progress indicator**

Light Light Yes End of cycle indicator

Third spray arm

600 mm

598 mm

Electronic

Symbols Yes

On display, with acoustic

sianal

Washing system Planetarium Single

Water softener With electronic setting

Turbidity sensor

Aquatest

Flood protection system Total Acquastop

Water supply

Yes

100°fH:58°dH

Single; cold/hot water max. 60°C - energysave with hot

water up to 35%

Max water hardness Drying system

Natural condenser drying, with EnerSave automatic

door opening system at the

end of the cycle

Tub material Stainless steel Filter Stainless steel

Concealed heating element

Hinges

Yes

Self balancing with fixed

hinges

Adjustable feet Just for levelling Back cover Yes, with covered counterweight

Depth of dishwasher

with open door (mm)

1168

Removable top Yes, with optional KIT

Electrical Connection

Plug

Connected power

Current Voltage (I) Australia 1800 W

10 A 220-240 V Frequency (Hz) Type of connection Power supply cable


length

50 Hz

Single-phase

140 cm







Compatible Accessories

KITGH



Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks



KITINC

a steel bar fitted on the top will block the dishwasher at the top.

KITPLV2



Kit extension for dishwasher and washing machine: lenght mt. 2



Symbols glossary



Aquatest measures the clarity of the water during an auto program, and automatically ensures the minimum consumption of water and energy.



Anti-drip: Some models of dishwashers are equipped with special polymer nozzles anti-drip, that improve the process of drying.



Delay Timer: The delay timer can postpone the start of the program by up to 24 hours.



LED display: to show programmes, functions and options selected and the time to the end of the cycle.



The Dry Assist + option, in addition to saving energy, ensures perfect drying of the dishes by opening the door automatically at the end of the wash c



EasyGlide: Convenient EasyGlide system for easy unloading of the appliance that allows reaching maximum flexibility of load of the machine.



FlexiDuo: The FlexiDuo 3rd cutlery basket allows you to arrange cutlery or small cups, ladles, or bulky utensils however you like: it consists of two separate and moveable modules.



FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.



Noise Level: Excellent insulation and special devices keep noise to a minimum.



PLANETARIUM_WASHING_SYSTEM_72dpi



Auto 45°- 65°: The auto programme regulates the length of a cycle depending on the need for a pre-wash and the number of rinses required.



Crystals: The Crystals programme is dedicated to delicate dishes such as glasses and china.



Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled.



Soak programme: The soak programme provides a rinse to prevent dirt from drying.



Rapid 27 Mins: The rapid 27 mins quick program takes just 27 minutes to wash a load.



Ultraclean: The Ultraclean option performs a final rinse at a high temperature of 70°c eliminating virtually all bacteria.



REF_PRG_NORMAL_ECO_72dpi



The symbols show the number of plate settings of the dishwasher.



Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary.





..





275

5∘



Benefit (TT)

FlexiDuo

The flexible third basket provides additional space, adapting to the load to accommodate various types of dishes, ensuring optimal organization and efficient use of interior capacity

The third FlexiDuo basket consists of two separate sections that can be handled independently of each other, stacked and/or removed, offering loading flexibility for every need. Depending on the arrangement, it allows cups, tall glasses, bulky utensils and pots and pans to be placed in the upper basket.

Planetarium Wash System

Full and deep wash coverage thanks to the advanced movement of the spray arm, an innovation patented by Smeg

Smeg's patented Planetarium Wash System guarantees impeccable cleaning. With a simultaneous double movement of the sprayer and 65 rotations per minute, it reaches every nook and cranny for extraordinary results. Dishes, glasses and utensils will be perfectly clean in no time. An intelligent system where efficiency and style meet, delivering brilliant results effortlessly.

DryAssist+

The Dry Assist+ system of automatic door opening at the end of the cycle ensures fast and energy-efficient drying