

DWA6214S4

Product Family Commercial width Commercial height Installation N° baskets Motor EAN code Dishwashers 60 cm 85 cm Free-standing 2 Single phase 8017709341732



Programs

Q45° 60 65° (75° 05°			
N. of programmes	5	Mix	Yes
Washing temperatures	45, 50, 55, 65, 70, 75 °C	Hygiene 99,9%	Yes
Crystal	Yes	Normal ECO	Yes
Full express - 60 minutes	Yes		

Options

For S			
Dry Assist+ option	Yes	Delay timer option	3-6-9 hours

Baskets

Basket colour	Grey	Lower Basket	With 2 foldable racks
Basket components colour	Grey	Lower basket with anti- drip inserts	Yes, as an accessory
Handle	In plastic on upper and lower basket	Largest loadable dish in lower basket	30,0 cm
Upper Basket	With central fixed racks	Colour Inner	Grey handles, Grey pastic
Height adjustment of the upper basket	On three levels	Components	plate for regulation second basket on three levels, Grey
Largest loadable dish in	25,0 cm		Orbital
upper basket		Cutlery basket	13 place settings sliding

Technical Features

SMEG SPA




Width (mm)	598 mm	Max water hardness	100°fH;58°dH
Depth (mm)	600 mm	Drying system	Natural condenser drying,
Product Height (mm)	848 mm		with Dry Assist + automatic
Controls	Electronic		door opening system at the end of the cycle
Programme graphics	Symbols	Child safety system	Yes
On/off indicator	Yes	(door lock)	103
Rinse aid indicator	Light	Tub material	Stainless steel
End of cycle indicator	Led on display, with	Filter	Stainless steel
	acoustic signal	Concealed heating	Yes
Washing system	Orbital	element	
Third spray arm	Single	Hinges	Self balancing with fixed
Flood protection system	Total Acquastop		hinges
Water supply	Single; cold/hot water max. 60°C - energysave with hot water up to 35%	Adjustable feet	Just for levelling
		Back cover	Yes, with covered counterweight
		Depth of dishwasher with open door (mm)	1168
		Removable top	Yes, with optional KIT

Electrical Connection

Plug
Connected power
Current
Voltage

(I) Australia 1800 W 10 A 220-240 V

Frequency (Hz) Type of connection Power supply cable length 50 Hz Single-phase 140 cm





Compatible Accessories

KITGH

racks

king

KITPLV2



Kit extension for dishwasher and washing machine: lenght mt. 2

Kit glass holder. It has to be fitted on the

first basket but only if there are foldable

KITINC

a steel bar fitted on the top will block the dishwasher at the top.

Symbols glossary



Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.



Noise Level: Excellent insulation and special devices keep noise to a minimum.



Crystals: The Crystals programme is dedicated to delicate dishes such as glasses and china.



REF_PRG_NORMAL_ECO_72dpi

Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary.



...

n 75

HYGIENE 99.9% High-temperature washing programme. The 75° rinse guarantees the removal of 99.9% of germs and bacteria, making it ideal for sanitising

Delay Timer: The delay timer can postpone the start of the program by up to 24 hours.

Orbital wash system distributes water evenly throughout the 60cm dishwasher cavity, directing water with precision to ensure an excellent wash.



 $(\mathbf{\hat{Y}})$

60

Normal programme: The normal programme is suitable for normal degrees of dirt for everyday use.



The symbols show the number of plate settings of the dishwasher.

000 System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher.

I		
l	DRY.	

The Dry Assist + option, in addition to saving energy, ensures perfect drying of the dishes by opening the door automatically at the end of the wash c



Benefit (TT)

Orbital Wash System

Even water distribution, deep cleaning and low noise thanks to the dual rotating spray arms

Orbital washing system, which, thanks to its double arm, its 7 water exit points and thanks to overlapping and simultaneous rotations and 40 rotations per minute, allows ample coverage of the tank area, thus guaranteeing optimal results in any basket-loading configuration.

DryAssist+

The Dry Assist+ system of automatic door opening at the end of the cycle ensures fast and energy-efficient drying