



DWAU615DB3



| | |
|--------------------------|-------------------------------|
| Product Family | Dishwashers |
| Commercial width | 60 cm |
| Commercial height | 82 cm |
| Installation | Partially-integrated built-in |
| Kitchen panel | Not supplied |
| N° baskets | 3, FlexiDuo |
| EAN code | 8017709310981 |



Programs



| | | | |
|----------------------------------|-------------------------------|-------------------|-----|
| N. of programmes | 10+1 | Intense | Yes |
| Washing temperatures | 38, 45, 50, 55, 65, 70, 75 °C | Self clean | Yes |
| Soak | Yes | Sterilise | Yes |
| Express 27' | Yes | 1/2 load | |
| Crystal | Yes | Delicate | Yes |
| Full express - 60 minutes | Yes | Regular | Yes |
| Auto sensor 45-65 | Yes | Normal ECO | Yes |

Options



| | | | |
|---------------------------|----------------|-----------------------------------|-----|
| Dry Assist option | | 1/2 load FlexiZone option | Yes |
| Dry Assist+ option | Yes | Options for tabs FlexiTabs | |
| Delay timer option | Up to 24 hours | Special programs option | Yes |


Baskets



| | | | |
|---------------------------------|------|----------------------------------------------|-------------------------------------------------|
| Basket colour | Grey | Largest loadable dish in upper basket | 19,0 cm |
| Basket components colour | Grey | Lower Basket | With completely foldable racks and glass holder |

| | | | |
|----------------------------------------------|------------------------------------------------------------------|----------------------------------------------|---------------------------|
| Handle | In plastic with stainless steel insert on upper and lower basket | Lower basket with anti-drip inserts | Yes |
| Upper Basket | With 1 foldable rack | Largest loadable dish in lower basket | 30,0 cm |
| Glass holder | Yes | Colour Inner Components | Blue |
| Height adjustment of the upper basket | On three levels | Cutlery basket | 13 place settings sliding |
| Upper basket with EasyGlide System | Yes | | |

Technical Features



| | | | |
|----------------------------------|-----------------------------------------------------------------|------------------------------------------------|-----------------------------------------------------------------------------------------------|
| Width (mm) | 598 mm | Water supply | Single; cold/hot water max. 60°C - energysave with hot water up to 35% |
| Depth (mm) | 570 mm | Max water hardness | 100°FH;58°dH |
| Display type | LED (external) | Drying system | Natural condenser drying, with EnerSave automatic door opening system at the end of the cycle |
| Product Height (mm) | 818 mm | Steam protection | In plastic |
| Controls | Electronic | Tube material | Stainless steel |
| Display | Delayed start, Programme time indicator, Time to end indication | Filter | Stainless steel |
| Programme graphics | Symbols | Concealed heating element | Yes |
| Rinse aid indicator | Light | Hinges | Self balancing with fixed hinges |
| Progress indicator | Yes | Min. and max plinth height | 100 - 170 mm |
| End of cycle indicator | On display, with acoustic signal | Adjustable feet | 7cm, from 820 to 890 mm |
| Auto switch-off | Yes | Additional gaskets | Yes, with stainless steel plate |
| Washing system | Planetarium | Back cover | Yes |
| Third spray arm | Single | Depth of dishwasher with open door (mm) | 1146 mm |
| Turbidity sensor Aquatest | Yes | Adjustable plinth | By height and depth |
| Flood protection system | Total Acquastop | Top cover | In plastic |

Electrical Connection

| | | | |
|------------------------|-----------|----------------------------------|---------------|
| Connected power | 1800 W | Type of connection | Single-phase |
| Current | 10 A | Power supply cable length | 140 cm |
| Voltage | 220-240 V | Plug | (I) Australia |
| Frequency (Hz) | 50 Hz | | |



Compatible Accessories

KITGH



Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks

KITPL60FABN



Toe kick Kit in Black colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.

KITPLV2



Kit extension for dishwasher and washing machine: lenght mt. 2

KITPL60FABB



























Toe kick Kit in White colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.

KITPL60FABX



Toe kick Kit in Stainless Steel with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.

Symbols glossary

| | | | |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Aquatest measures the clarity of the water during an auto program, and automatically ensures the minimum consumption of water and energy. |  | Anti-drip: Some models of dishwashers are equipped with special polymer nozzles anti-drip, that improve the process of drying. |
|  | COMM_HEIGHT_82_72dpi |  | Delay Timer: The delay timer can postpone the start of the program by up to 24 hours. |
|  | LED display: to show programmes, functions and options selected and the time to the end of the cycle. |  | The Dry Assist + option, in addition to saving energy, ensures perfect drying of the dishes by opening the door automatically at the end of the wash c |
|  | EasyGlide: Convenient EasyGlide system for easy unloading of the appliance that allows reaching maximum flexibility of load of the machine. |  | FlexiDuo: The FlexiDuo 3rd cutlery basket allows you to arrange cutlery or small cups, ladles, or bulky utensils however you like: it consists of two separate and moveable modules. |
|  | FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed. |  | Noise Level: Excellent insulation and special devices keep noise to a minimum. |
|  | PLANETARIUM_WASHING_SYSTEM_72dpi |  | Auto 45°- 65°: The auto programme regulates the length of a cycle depending on the need for a pre-wash and the number of rinses required. |
|  | Crystals: The Crystals programme is dedicated to delicate dishes such as glasses and china. |  | Delicate: Delicate washing program is designed for delicate dishes which are not heavily soiled. |
|  | Quick wash cycle for normally soiled mixed loads such as dishes and pans, even with dried-on residues. Dishes are washed and dried in 60 minutes. |  | The Regular programme is for dishes with regular dirt, even with dried-on residues. |
|  | Soak programme: The soak programme provides a rinse to prevent dirt from drying. |  | Rapid 27 Mins: The rapid 27 mins quick program takes just 27 minutes to wash a load. |
|  | Ultraclean: The Ultraclean option performs a final rinse at a high temperature of 70°C eliminating virtually all bacteria. |  | REF_PRG_NORMAL_ECO_72dpi |
|  | The symbols show the number of plate settings of the dishwasher. |  | Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary. |
|  | Dishwasher cleaning cycle. The cycle should be started with the machine empty, without dishes. It is recommended to run the program every 2-3 months, using special dishwasher detergents. |  | Allows you to enable additional programs when selected together with any wash cycle. |



STERYL 75°: Intensive wash cycle ideal for plates, pots, pans, cutting boards, feeding bottles.