

DWIFABB2



| | |
|-------------------|------------------------|
| Product Family | Dishwashers |
| Commercial width | 60 cm |
| Commercial height | 82 cm |
| Installation | Under counter built-in |
| Kitchen panel | Not supplied |
| N° baskets | 2 |
| EAN code | 8017709282813 |



Programs



| | | | |
|----------------------|-------------------|-------------------|-----|
| N. of programmes | 5 | Auto sensor 45-65 | Yes |
| Washing temperatures | 45, 50, 65, 70 °C | Super | Yes |
| Soak | Yes | Normal ECO | Yes |
| ECO | Yes | | |

Options



| | | | |
|---------------------------|---------------|----------------------------|-----|
| Enersave option | Yes | Options for tabs FlexiTabs | Yes |
| Delay timer option | Up to 9 hours | Sanitizing option Hyclean | Yes |
| 1/2 load FlexiZone option | Yes | | |

Baskets



| | | | |
|---------------------------------------|--|---------------------------------------|---------------------------|
| Basket colour | Stainless Steel | Largest loadable dish in upper basket | 25,0 cm |
| Basket components colour | Grey | Lower Basket | With 4 foldable racks |
| Handle | In plastic with stainless steel insert on upper and lower basket | Lower basket with anti-drip inserts | Yes |
| Upper Basket | With 3 foldable racks | Largest loadable dish in lower basket | 30,0 cm |
| Height adjustment of the upper basket | On three levels | Cutlery basket | 13 place settings sliding |

Upper basket with EasyGlide System Yes

Technical Features




| | |
|-------------------------|-------------------------|
| Width (mm) | 598 mm |
| Depth (mm) | 545 mm |
| Display type | LED display (1 digit) |
| Product Height (mm) | 818 mm |
| Controls | Electronic |
| Display | Delayed start |
| Programme graphics | Symbols |
| On/off indicator | Yes |
| Salt light indicator | Light |
| Rinse aid indicator | Light |
| End of cycle indicator | Acoustic signal |
| Washing system | Orbital |
| Third spray arm | Single |
| Water softener | With electronic setting |
| Turbidity sensor | Yes |
| Aquatest | |
| Flood protection system | Total Acquastop |

| | |
|---|---|
| Water supply | Single; cold/hot water max. 60°C - energysave with hot water up to 35% |
| Max water hardness | 100°FH;58°dH |
| Drying system | Natural condenser drying, with EnerSave automatic door opening system at the end of the cycle |
| Steam protection | In plastic |
| Tube material | Stainless steel |
| Filter | Stainless steel |
| Concealed heating element | Yes |
| Hinges | Self balancing with fixed hinges |
| Min. and max plinth height | 100 - 170 mm |
| Adjustable feet | 7cm, from 820 to 890 mm |
| Additional gaskets | Yes, with stainless steel plate |
| Back cover | Yes |
| Depth of dishwasher with open door (mm) | 1171 mm |
| Back feet adjustable from front | Yes |
| Top cover | In plastic |

Electrical Connection

| | | | |
|-----------------|-----------|---------------------------|---------------|
| Connected power | 1800 W | Type of connection | Single-phase |
| Current | 10 A | Power supply cable length | 140 cm |
| Voltage | 220-240 V | Plug | (I) Australia |
| Frequency (Hz) | 50 Hz | | |

Compatible Accessories



KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks



KITPL60FABN

Toekick Kit in Black colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPLV2

Kit extension for dishwasher and washing machine: lenght mt. 2



KITPL60FABB

Toekick Kit in White colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPL60FABX

Toekick Kit in Stainless Steel with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.

Symbols glossary

| | | | |
|--|--|---|---|
|  | Aquatest measures the clarity of the water during an auto program, and automatically ensures the minimum consumption of water and energy. |  | Anti-drip: Some models of dishwashers are equipped with special polymer nozzles anti-drip, that improve the process of drying. |
|  | COMM_HEIGHT_82_72dpi |  | Delay Timer: The delay timer can postpone the start of the program by up to 24 hours. |
|  | EasyGlide: Convenient EasyGlide system for easy unloading of the appliance that allows reaching maximum flexibility of load of the machine. |  | Flexitabs: Flexitabs adjusts the wash cycle to give the best possible results regardless of the type of detergent used. |
|  | FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed. |  | Hyclean: When the HYCLEAN option is selected, the dishwasher performs a final 10 minute rinse at a high temperature of 70°C, eliminating virtually all bacteria to achieve the highest possible standards of cleanliness. The Hyclean option can be selected with almost all cycles at temperatures above 50°C. |
|  | Noise Level: Excellent insulation and special devices keep noise to a minimum. |  | Orbital wash system distributes water evenly throughout the 60cm dishwasher cavity, directing water with precision to ensure an excellent wash. |
|  | Auto 45°- 65°: The auto programme regulates the length of a cycle depending on the need for a pre-wash and the number of rinses required. |  | Eco: Eco, this economic wash programme uses a low amount of water and energy in order to provide the most environmentally friendly cleaning option. |
|  | Soak programme: The soak programme provides a rinse to prevent dirt from drying. |  | PRG_STRONG_72dpi |
|  | REF_PRG_NORMAL_ECO_72dpi |  | The symbols show the number of plate settings of the dishwasher. |
|  | Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary. |  | System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher. |