

# **DWIFABP2**



**Product Family** Dishwashers Commercial width 60 cm Commercial height 82 cm

Installation Under counter built-in

Kitchen panel Not supplied

N° baskets

EAN code 8017709282790



# **Programs**











5

N. of programmes Washing temperatures

45, 50, 65, 70 °C Soak Yes **ECO** Yes

Auto sensor 45-65

Super Yes Normal ECO Yes

# **Options**











**Enersave option** Delay timer option

1/2 load FlexiZone option

Yes

Up to 9 hours

Yes

Options for tabs FlexiTabs

Sanitizing option

Hyclean

Yes

Yes

Yes

## **Baskets**





**Basket colour Basket components** 

colour Handle Stainless Steel

Grey

In plastic with stainless steel insert on upper and

lower basket

With 3 foldable racks **Upper Basket** 

Height adjustment of the upper basket

On three levels

Largest loadable dish in 25,0 cm

upper basket

With 4 foldable racks Lower Basket

Lower basket with anti- Yes

drip inserts

Largest loadable dish in 30,0 cm

lower basket

**SMEG SPA** 24/11/2025



Upper basket with EasyGlide System

Yes

Colour Inner Components Cup shelfes, Handle, Anti drop inserts, Cutlery basket: same colour of Dishwasher 13 place settings sliding

**Cutlery basket** 

## **Technical Features**







Width (mm) 598 mm Depth (mm) 545 mm

LED display (1 digit) Display type

Product Height (mm) 818 mm Controls Electronic Display Delayed start Symbols Programme graphics On/off indicator Yes Salt light indicator Light Rinse aid indicator Light

End of cycle indicator Acoustic signal

Washing system Orbital Third spray arm Single

Water softener With electronic setting

Yes

**Turbidity** sensor

Aquatest

Flood protection system Total Acquastop

Water supply Single; cold/hot water max. 60°C - energysave with hot

water up to 35%

Max water hardness 100°fH;58°dH

Drying system Natural condenser drying, with EnerSave automatic door opening system at the

end of the cycle

100 - 170 mm

Steam protection In plastic Tub material Stainless steel Filter Stainless steel

Concealed heating

element Hinges

Self balancing with fixed

hinges

Yes

Min. and max plinth

height

Adjustable feet Additional gaskets 7cm, from 820 to 890 mm Yes, with stainless steel

plate Yes

**Back cover** 

Depth of dishwasher with open door (mm) Back feet adjustable

from front

Top cover

Yes

In plastic

1171 mm

## **Electrical Connection**

Connected power 1800 W Current 10 A Voltage 220-240 V Frequency (Hz) 50 Hz

Type of connection Power supply cable length

Plug

Single-phase 140 cm

(I) Australia

**SMEG SPA** 24/11/2025



# **Compatible Accessories**

## **KITGH**



Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks

### KITPL60FABN



Toekick Kit in Black colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.

#### KITPLV2



Kit extension for dishwasher and washing machine: lenght mt. 2

### KITPL60FABB

Toekick Kit in White colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.

### KITPL60FABX

Toekick Kit in Stainless Steel with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.

SMEG SPA 24/11/2025



# Symbols glossary



Aquatest measures the clarity of the water during an auto program, and automatically ensures the minimum consumption of water and energy.



Anti-drip: Some models of dishwashers are equipped with special polymer nozzles anti-drip, that improve the process of drying.



COMM\_HEIGHT\_82\_72dpi



Delay Timer: The delay timer can postpone the start of the program by up to 24 hours.



EasyGlide: Convenient EasyGlide system for easy unloading of the appliance that allows reaching maximum flexibility of load of the machine.



Flexitabs: Flexitabs adjusts the wash cycle to give the best possible results regardless of the type of detergent used.



FlexiZone: The ½ load flexizone allows you to wash a reduced load saving energy, water and time and there are no restrictions on where the items are placed.



Hyclean: When the HYCLEAN option is selected, the dishwasher performs a final 10 minute rinse at a high temperature of 70°C, eliminating virtually all bacteria to achieve the highest possible standards of cleanliness. The Hyclean option can be selected with almost all cycles at temperatures above 50°C.



Noise Level: Excellent insulation and special devices keep noise to a minimum.



Orbital wash system distributes water evenly throughout the 60cm dishwasher cavity, directing water with precision to ensure an excellent wash.



Auto 45°- 65°: The auto programme regulates the length of a cycle depending on the need for a pre-wash and the number of rinses required.



Eco: Eco, this economic wash programme uses a low amount of water and energy in order to provide the most environmentally friendly cleaning option.



Soak programme: The soak programme provides a rinse to prevent dirt from drying.



PRG\_STRONG\_72dpi



REF\_PRG\_NORMAL\_ECO\_72dpi



The symbols show the number of plate settings of the dishwasher.



Total Acquastop: In addition to the partial Acquastop protection present in all Smeg dishwashers, some models have an electronic device fitted to the water intake hose, which monitors water levels in the machine, detects leaks in the hose and switches off the water supply immediately when necessary.

000 11,3h System WaterSave ensures the best washing results with minimal water consumption depending on the model of dishwasher.

SMEG SPA 24/11/2025