

FAB28URDRB3



Product family	Refrigerator
Installation	Free-standing
Category	Single door
Reference width	Until 60
Reference height	100 - 160
Cooling type	Fan-assisted refrigerator, static freezer
Defrost	Automatic for refrigerator, manual for freezer
Hinge	Standard
Hinge position	Right
EAN code	8017709340933



Aesthetic

Aesthetics	Retro-style	Logo color	Chromed
Color	Ruby red	Side material	Steel
Finishing	Matte	Side color	Decorated / Special
Design	Rounded	Logo	Applied
Material	Thermo-formed	Door shelf profile color	Chromed
Handle	External	Drawers profile color	Chromed
Handle	Fixed	Glass shelf profile color	Chromed
Handle color	Chromed		

Refrigerator compartment features



Number of compartments	2	Crisper drawer type	Sliding crisper
Compartment types	Low temperature compartment, Fruit and vegetable compartment	Crisper cover	Yes
		Type of crisper cover	Glass
No. of adjustable shelves	2	Refrigerator lighting	Yes
Number of fruit and vegetables drawers	1	Refrigerator lighting	LED
Type of adjustable shelves	Glass		

Refrigerator Inner Door

No. of bottle shelves	1
-----------------------	---

No. of door shelves with transparent cover	1	Door bin with wire support	Yes
Number of adjustable door shelves	1		
Adjustable door bins with wire support	Yes		


Other Refrigerator features

			
Humidity Control	Yes	Fan	Yes
MultiFlow	Yes		

Freezer features

Internal freezer compartment	Yes
------------------------------	-----

Other technical features

	
Door open alarm	Acoustic and visual
Temperature setting type	Electronic
No. of compressors	1
Refrigerant gas type	R600a
Compressor type	Inverter
Refrigerant quantity	1.2 oz
Foam agent	Cyclopentane

Performance / Energy Label

Annual energy consumption	230 KWh/year	Refrigerator compartment	8.62 cu. ft.
Total volume	9.53 cu. ft.	Total volume	0.00 cu. ft.
Freezer volume	0.92 cu. ft.	Climatic class	SN, N, ST, T

Electrical Connection

Plug	(F;E) Schuko	Voltage (V)	120 V
Electrical connection rating	90 W	Frequency (Hz)	50/60 Hz
Current	2.2 A	Power cord length	70 7/8 "

Symbols glossary



4 stars freezing compartment for better food preservation.



The automatic defrost system works by automatically defrosting at regular intervals eliminating the need to defrost altogether.



Ventilated: Forced distribution of cold air in the refrigerator compartment, which allows even temperature distribution within the fridge.



LED interior lighting: is a more energy efficient and long lasting way of illuminating the interior of the appliance.



Inverter technology: The evolution of Smeg's driers towards more intelligent and environmentally sustainable models has led to the choice of using Inverter technology with heat pumps, which reduces significantly energy consumption.



Air plus: keeps food fresher for longer.

Benefit (TT)

Plastic multiflow system

The Multiflow system ensures even distribution of cold air inside the refrigerator

Fan

The fan contributes to an even distribution of air inside the refrigerator

Refrigerant gas R600a

Environmentally friendly R600a refrigerant gas contributes to rapid cooling with lower energy consumption

Climate class

Climatic class SN-T makes the appliance suitable for working at room temperature between 10 °C and 43 °C (50 °F ~ 109 °F)

External handle

The external handle ensures practicality and ease of use of the refrigerator

Refrigerator Internal lighting

Interior lighting for perfect visibility of shelves in the refrigerator compartment

Fruit and vegetable drawer

The fruit and vegetable drawer ensures the best storage conditions for fresh food, avoiding any contamination

Inverter compressor

Inverter compressor reduces noise and vibration levels for a quiet and comfortable kitchen environment

Inverter compressor technology offers significant advantages for refrigeration systems, improving both performance and efficiency. Better temperature control ensures a more stable and constant indoor environment, preserving the freshness of food. This technology also results in reduced energy consumption, as the compressor adjusts its speed according to cooling needs.