FC84EN4HM1



Product Family	Refrigerator
Installation	Free standing
Category	Bottom Mount
Reference width	Higher than 80 cm
Reference height	160 - 200 cm
Sistema Total No - Frost	Yes
Cooling type	Total No Frost - Double Cooling system
Defrost	Automatic
Hinge type	Standard
Slot-in	Yes
Hinge position	Right
Reversible door	Yes
EAN code	8017709358648

Aesthetics

Aesthetic	Universale	**Handle colour**	Silver
Colour	Marble look	**Logo colour**	Chrome
Design	Flat	**Side material**	Steel
Finishing	Fingerproof	**Side colour**	Silver
Material	Stainless steel	**Logo**	Applied
Door steel type	Finger proof	**Display**	LCD Touch
Handle	External	**Display position**	Esterno (su porta)
Handle type	Fixed		

Refrigerator compartment features

Number of compartments	3	**Crisper Cover**	Yes
Compartment types	Low temperature compartment, Fruit and vegetable compartment	**Type of crisper/vegetable drawers cover**	Glass
No. of adjustable shelves	3	**No. of lights refrigerator compartment**	3
Number of fruit and vegetables drawers	2	**Low temperature compartment**	Yes
Shelves material	Glass	**Internal light in fridge**	Yes
Type of crisper/vegetable drawers cover	Standard	**Type of internal light (fridge)**	LED

Refrigerator Inner Door

Number of adjustable door shelves	3	**No. of bottle shelves**	1

Other Refrigerator features



Humidity Control	Yes, manual	**MultiFlow**	Yes
Accessories	Egg tray		

Freezer compartment features


No. of shelves	1	**Type of shelves**	Plastic
No. of compartments with flap	1		

Other Freezer features



Ice maker	Manual	**Fast freezing compartment**	Yes

Other technical features



Functions display	Holiday, Fast freezing, Fast cooling, Control lock, Cooling timer
Door open alarm	Yes
Temperature Alarm	Yes
Type of temperature control	Electronic
No. of compressors	1
Refrigerant gas type	R600a
Type of compressor	Inverter
Foam agent	Cyclopentane

Performance / Energy Label - Reg. 2019



Annual energy consumption	326 kWh/a	**Airborne acoustical noise emissions**	41 dB(A) re 1 pW
Energy efficiency class	E	**Temperature Rise Time**	14,30 h
Airborne acoustical noise emission class	C	**4 star - Freezing capacity**	12,0 kg/24h

Total net volume	588 l	**Climate class**	SN, T
Sum of the volumes of the frozen compartment(s)	181 l	**EEI**	100 %
Sum of the volumes of the chill compartment(s) and the unfrozen compartment(s)	407 l		

Electrical Connection

Electrical connection rating	207 W	**Frequency (Hz)**	50 Hz
Current	1,58 A	**Power supply cable length**	180 cm
Voltage (V)	220-240 V	**Plug**	(F;E) Schuko

Logistic Information

Width	840 mm	**Height**	1860 mm
Depth without handle	750 mm	**Product width with maximum doors opening**	1535 mm

Alternative products



FC84EN4HX1

Hinge position: Right
Stainless steel

Symbols glossary



The automatic defrost system works by automatically defrosting at regular intervals eliminating the need to defrost altogether.



LCD display: to optimize performance and simplify the use of the appliance.



Fingerprint proof stainless steel: Fingerprint proof stainless steel keeps stainless steel looking as good as new.



LED interior lighting: is a more energy efficient and long lasting way of illuminating the interior of the appliance.



Multiflow Cooling System: the Multiflow ventilation system allows an even distribution of cool air around the fridge cabinet.



Energy efficiency class E



Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.



Fast freezing: The fast freezing function brings the temperature of the compartment down when activated a few hours prior to usage.



Power saving mode: The power saving mode allows you to disable the refrigerator and keep the freezer working.



Smeg's evolution towards more intelligent and eco-friendly models has led to the choice of Inverter technology, which significantly reduces consumption.



Slot-in: The refrigerators with Slot-in opening can be perfectly integrated into the furniture structure, as the doors open at 90° do not go beyond the side of the product. In case of installation next to the wall, it will be necessary to consider the dimensions of the handle in order to open the door at 90 °.