

FD511DAUS

Family	Dishwasher
Subfamily	Undercounter Dishwasher
Type	Undercounter Glasswasher
Basket dimensions	500x500 mm
Panel	Easyline 2016
Filter	5-stages filter system
Rinse pump H.T.R. system	Rinse pump with atmospheric boiler
Usable load height	415 mm
Power connection	400 V 3N~ / 12 A / 6,7 kW / 50 Hz
Depth with open door	1020 mm
Maximum dishes diameter	415 mm
Product dimensions WxDxH	600x600x1290 mm



Distribution

Solutions	Bars/Cafes; Hotels; Restaurants/Catering; Butcher's shops; QSR
-----------	--

Aesthetics

Serie	Easyline	Led color	White
Control panel	Electronic		

Functions



Functionality	GN 1/1 trays washing; 5-stage filter; HTR
---------------	---

Programs

Program specifications	Boiler 85°C/Tank 60°C-1'10"; Boiler 85°C/Tank 60°C-1'30"; Boiler 85°C/Tank 60°C-2'; Boiler 85°C/Tank 60°C-2'30"; Boiler 85°C/Tank 60°C-4'
Drain and self cleaning cycle	Yes
Maximum basket/hour	60
Maximum dishes/hour	1080

Interface

Display	8 digit	Cycle progress alert	Yes
On/Off button	Yes	End-cycle alert	Yes
Rinse aid missing alert	Yes	Manual diagnostic	Yes
Detergent missing alert	Yes		

Construction

Tank	Deep drawn	Rinse spray arm	Stainless steel
Construction	Double wall	Door gasket	On 3 sides
Tank material	Stainless steel AISI 304	Rack guides	Embossed
Back panel	Galvanized	Tank capacity	11 l
Door	Double wall	Boiler capacity	6 l
Balanced door	Yes	Protection class	IPX4
Tank filter	Stainless steel	Net weight	84,000 kg
Washing spray arm	Stainless steel	Drain max. height	600 mm

Technical Features

Tank heating element	2000 W	Water cycle consumption	3,2 l
Boiler heating element	6000 W	Water inlet	Cold 15°C
Washing pump	700 W	Max temperature inlet water	60°C
Default connection	6700 W	Max water hardness	54°F - 30°dH

Electrical Connection

Plug	Australian 13 AMP	Electrical connection option	230 V 3~ / 19 A / 6,7 kW / 50 Hz; 230 V~ / 12 A / 2,7 kW / 50 Hz; 230 V~ / 16 A / 3,7 kW / 50 Hz; 230 V~ / 21 A / 4,7 kW / 50 Hz
-------------	-------------------	-------------------------------------	--

Equipments

Peristaltic detergent doser	Yes, electronic control	Rinse load	Yes, manual
Peristaltic rinse-aid doser	Yes, electronic control	Cycle counter	Yes
Chemicals level probe	Yes, optional KITSONLIV	Break tank	Yes
Boiler thermostop	Yes default ON	Partial renewal of water in the tank and built-in drain pump	Si
Soft Start	Yes	Trays washing option	Yes
Automatic start	Yes, default OFF	GN1/1 530x325mm	
Detergent load	Yes, manual	Water supply pipe diameter	16 mm
		Drain supply pipe diameter	21,5 mm

Accessories Included

Dish basket
Cutlery basket
Flat basket

PB50D01
PHOOS02
1x PB50G02

Water supply pipe
Drain pipe

In acciaio Watermark
Yes - 2m

Not included accessories



KITSONLIV

Probe level kit




WH00S01

Wire insert for 12 small dishes



PHOOS01

Single basket in polypropylene for cutlery



PB50G02

Universal basket in polypropylene 500x500



WB50T02

Wire basket for 5 trays 600x500



WB50G01

Universal wire basket with flat bottom 500x500



WB50G02

Wire basket for glasses with inclined bottom 500x500



WB50G04

Wire basket for glasses with inclined bottom 500x500



WB50G03

Wire basket for glasses with inclined bottom 500x500



WS5

Underframe for glasswashers 500mm

Symbols glossary (TT)



...



...



5 STAGE FILTER