

FD516DAUS

Family	Dishwasher
Subfamily	Undercounter Glasswasher
Type	Undercounter traywasher
Basket dimensions	500x500 mm
Control panel	Electronic
Rinse pump	Yes
Wash pump	Standard
Power connection	400 V 3N~ / 12 A / 6,73 kW / 50 Hz
Product dimensions WxDxH	600x675x1315 mm



Distribution

Industries	Hotels; Ristoranti / Catering; Bakeries / Pastry shops; Food Industries; Catering; Butcher's shops; Meet processing industry; QSR
-------------------	--

Aesthetics

Led color	Green	Serie	Easyline
------------------	-------	--------------	----------

Technical Features

Trays washing option	Yes	Water inlet	Cold 15°C
Water consumption per cycle	3,2 l	Detergent load	Yes, manual
Water inlet	8°C	Rinse load	Yes, manual
Minimum water consumption per cycle	1,8 l	Usable load height	400 mm
Max. inlet temperature	60°C	Depth with open door	1290 mm
Max water hardness	12°f - 7°dH	Maximum dishes diameter	415 mm

Programs

Programs	6 automatic programs; 1 fully programmable program; Self-cleaning programs
Program options	Extra rinse; Clean water cycle

Maximum basket/hour	60
Maximum dishes/hour	1080

Electrical Connection

Tank heating element power	2000 W	Default connection	6730 W
Boiler heating element power	6000 W	Electrical connection option	230 V~/13 A/3,0 kW/50 Hz; 230 V~/18 A/4,0 kW/50 Hz; 230 V~/22 A/5,0 kW/50 Hz
Wash pump power	730 W	Plug	Australian 13 AMP

Interface

Display	8 digit	Cycle progress alert	Yes
On/Off button	Yes	End-cycle alert	Yes
Rinse aid missing alert	Yes	Manual diagnostic	Yes
Detergent missing alert	Yes		

Construction

Tank	Deep drawn	Rack guides	Embossed
Construction	Double wall	Hood elevation system	Manual
Tank material	Stainless steel AISI 304	Filter	5-stages filter system
Back panel	Galvanized	Tank capacity	11 l
Balanced door	Yes	Boiler capacity	6 l
Upper washing system	One washing and one split rinse spray arms, stainless steel	Protection class	IPX4
Lower washing system	One washing and one split rinse spray arms, stainless steel	Adjustable feet	Yes
Tank filter	Stainless steel	Drain max. height	600 mm
Door gasket	On 3 sides		

Accessories Included

Flat basket	1x PB50G02	Water supply pipe	In acciaio Watermark
Grids	1 x PRF500	Drain pipe	Yes - 2m

Equipments

Drain pump	Yes	Option for auto daily switch on	Yes, default OFF
Peristaltic detergent dispenser	Yes, electronic control	Cycle counter	Yes
Peristaltic rinse-aid dispenser	Yes, electronic control	Break tank	Yes
Chemicals level probe	Yes, optional KITSONLIV		

Rinse boiler Thermostop system	Yes - default	Partial renewal of water in the tank and built-in drain pump	Yes
Wash tank Thermostop system	Yes	Water supply pipe diameter	16 mm
Wash pump soft start system	Yes	Drain supply pipe diameter	21,5 mm
Stand-by system	Yes	Peristaltic detergent doser	Yes, manual
		Peristaltic detergent doser	Yes, manual

Logistic Information

EAN code	8017709283889	Net weight	88,000 kg
Packed product dimensions (WxDxH)	1470x660x700 mm	Gross weight (kg)	98,000 kg

Compatible Accessories


KITSONLIV

Probe level kit



PB50D01

Basket made of polypylene for 18 plates
500x500




KIT-WG500

Support grid for tray washer, dim.
(WxD) 500x500 mm

PHOOS01

Single basket in polypropylene for
cutlery



PB50G02

Universal basket in polypropylene
500x500

WB50D01

Wire basket for 18 dishes and trays
500X500




PHOOS02

Basket in polypropylene for cutlery
with 6 compartments

WB50T02

Wire basket for 5 trays 600x500



WB50T03

Wire basket for 5 trays 600x500



WH00S01

Wire insert for 12 small dishes

Benefit (TT)

Balanced door

Effortless opening and closing

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

The presence sensor filter alerts if the filtration system is out of position, ensuring safe washes every time.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Integral double skin

Thermal and acoustic insulation guaranteed

The double wall is designed to optimise energy efficiency by reducing heat loss and accelerating water heating, resulting in lower energy consumption and faster cycle start-up times. Additionally, it provides effective acoustic insulation, helping to reduce noise and ensuring a quieter, more comfortable working environment for the staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

Raised version

Easy and fast dishwasher loading and unloading operations

The raised design facilitates loading and unloading dishes, making these tasks faster and more efficient. This results in significant time savings, especially valuable in high-intensity work environments.

The space below the dishwasher can be used to store detergents, utensils, or other accessories, providing a practical solution to optimise space usage, particularly in compact kitchens.

Hood lift

Unprecedented comfort with the patented lifting system

The new ergonomic handle, combined with the patented lifting system, minimises the effort required to open and close the hood, limiting it to just 2.5 kg. This system ensures an exceptionally smooth and lightweight operation, helping to protect the operator's health and well-being, even during extended use.