FS18EV2HX



Product Family	Refrigerator
Installation	Free standing
Category	One Door
Reference width	Until 60 cm
Cooling type	No Frost
Defrost	Automatic
Hinge type	Standard
Hinge position	Right
Reversible door	Yes
EAN code	8017709296049

Aesthetics

Aesthetic	Universale	**Handle type**	Fixed
Colour	Stainless Steel	**Handle colour**	Silver
Design	Flat	**Logo colour**	Chrome
Finishing	Fingerproof	**Side material**	Steel
Material	Stainless steel	**Side colour**	Silver
Door steel type	Finger proof	**Logo**	Applied
Handle	External		

Refrigerator compartment features

Number of compartments	3	**Crisper Cover**	Yes
Compartment types	Low temperature compartment, Fruit and vegetable compartment	**Type of crisper/vegetable drawers cover**	Glass
No. of adjustable shelves	3	**Low temperature compartment**	Yes
Number of fruit and vegetables drawers	2	**Internal light in fridge**	Yes
Shelves material	Glass	**Type of internal light (fridge)**	LED
Type of crisper/vegetable drawers cover	Standard		

Refrigerator Inner Door

Number of adjustable door shelves	4	**No. of bottle shelves**	1

Other Refrigerator features



Humidity Control	Yes, manual	**Fan**	Yes
MultiFlow	Yes		

Other technical features

Type of temperature control	Electro-mechanical
No. of compressors	1
Refrigerant gas type	R600a
Type of compressor	Standard
Refrigerant Quantity (g)	39 g
Foam agent	Cyclopentane

Performance / Energy Label - Reg. 2019



Annual energy consumption	121 kWh/a	**Sum of the volumes of the chill compartment(s) and the unfrozen compartment(s)**	390 l
Energy efficiency class	E		
Airborne acoustical noise emission class	C	**Airborne acoustical noise emissions**	40 dB(A) re 1 pW
Total net volume	389 l	**Climate class**	SN, T
		EEI	100 %

Electrical Connection

Electrical connection rating	110 W	**Frequency (Hz)**	50 Hz
Current	0,52 A	**Power supply cable length**	210 cm
Voltage (V)	220-240 V	**Plug**	(F;E) Schuko

Logistic Information

Width	595 mm	**Product width with maximum doors opening**	982 mm
Depth without handle	650 mm		
Height	1860 mm	**Product depth with doors open at 90°**	1244 mm
		Spacer depth	30 mm


1820
1860
595
1860
645
558
3
1200
90°
193
110°
597

Compatible Accessories



REFLK

connecting kit

Symbols glossary



A++: Energy efficiency class A++ helps to save up to 20% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Ventilated: Forced distribution of cold air in the refrigerator compartment, which allows even temperature distribution within the fridge.



LED interior lighting: is a more energy efficient and long lasting way of illuminating the interior of the appliance.



No Frost: The No Frost and Frost free systems prevent ice from forming so that no defrosting is required.



The automatic defrost system works by automatically defrosting at regular intervals eliminating the need to defrost altogether.



Fingerprint proof stainless steel: Fingerprint proof stainless steel keeps stainless steel looking as good as new.



Multiflow Cooling System: the Multiflow ventilation system allows an even distribution of cool air around the fridge cabinet.



Energy efficiency class E