

FS9606AS-1


Cooker size N. of cavities with energy label Cavity heat source Hob type Type of main oven Cleaning system main oven EAN code 90x60 cm 1 ELECTRICITY Gas Thermoseal Vapour Clean 8017709310615



Aesthetics

₩.			
Aesthetic	Classic	Display	Touch
Serie	Concerto	No. of controls	7
Colour	Anthracite	Serigraphy colour	Silver
Design	Standard	Handle	Smeg Classic
Door	With 2 horizontal strips	Handle Colour	Brushed stainless steel
Upstand	Yes	Glass type	eclypse
Type of pan stands	Cast Iron	Feet	Silver
Hob colour	Stainless steel	Plinth	Stainless steel
Command panel finish	Enamelled metal	Storage compartment	Door
Control knobs	Smeg Classic	Logo	Assembled
Controls colour	Stainless steel	Logo position	Facia below the oven

Programs / Functions





Hob technical features

UR

Total no. of cook zones 5Front left - Gas - Rapid - 2.90 kWRear left - Gas - Semi Rapid - 1.80 kWCentral - Gas - UR - 4.00 kWRear right - Gas - Semi Rapid - 1.80 kWFront right - Gas - Semi Rapid - 1.80 kWFront right - Gas - AUX - 1.00 kWType of gas burnersStandardAutomatic electronicYesignition

Gas safety valves Burner caps Yes Matt black enamelled

Main Oven Technical Features

1151 📃 📑 🗟 💭			
No. of lights	2	Full glass inner door	Yes
Fan number	2	Total no. of door glasses	3
Net volume of the cavity	115 l	No.of thermo-reflective	2
Gross volume, 1st cavity	126 I	door glasses	
Cavity material	Ever Clean enamel	Safety Thermostat	Yes
No. of shelves	5	Cooling system	Tangential
Type of shelves	Metal racks	Usable cavity space	371x724x418 mm
Light type	Halogen	dimensions (HxWxD)	
Light Power	40 W	Temperature control	Electro-mechanical
Cooking time setting	Stop	Lower heating element	1700 W
Light when oven door is	Yes	power	1200 \//
open		Upper heating element - Power	1200 W
Door opening	Flap down	Grill elememt	1700 W
Removable door	Yes	Large grill - Power	2900 W
		Circular heating element - Power	2 x 1550 W
		Grill type	Electric

Options Main Oven

Timer Yes End of cooking acoustic Yes alarm Minimum Temperature50 °CMaximum temperature260 °C

Accessories included for Main Oven & Hob


Rack with back and side 1 Grill mesh 1 stop



20mm deep tray1Telescopic Guide rails, 140mm deep tray1partial Extraction

Electrical Connection

Plug Electrical connection	(I) Australia 3200 W	Type of electric cable installed	Yes, Single phase
rating Current	14 A	Power supply cable length	120 cm
Voltage	220-240 V	Frequency	50/60 Hz
-		Terminal block	3 poles





Not included accessories

AIRFRY9



recreating traditional frying in the oven, but with fewer calories and less fat. It allows you to cook quickly and simply dishes such as French fries, fried vegetables and fish, ensuring perfect browning and crispiness.

Air fryer rack AIRFRY . Ideal for



SFLK1

Child lock



PRTX

Refractary pizza stone with handles. D=35cm Not suitable for microwave ovens. Suitable for gas ovens, to be put on the griddle.



KIT600SNL-9

Cover strip for hob back side, suitable for 90 cm Concerto cookers



BG6090-1

Cast iron grill plate suitable for Concerto cookers



AL90X9

Upstand suitable for 90 cm Concert cookers SX91

GTP

Partially extractable telescopic guides (1 level) Extraction: 300 mm Material: Stainless steel AISI 430 polished

PPR9

Refractary pizza stone without handles. Squared shaped stone: L64xH2,3xP37,5 cm Suitable also for gas ovens, to be put on the griddle.

BBQ9



KIT90N9

Splashback 90 cm, black, for BU & BM cookers



KIT90X9-1

Splash back, 90x60 cm, stainless steel, for Concerto cookers

PPX6090-1



Stainless steel grill plate suitable for 90 cm Concerto cookers



PALPZ

Pizza shovel with fold away handle width: 315mm length: 325mm



KITH95

Height extension kit (950 mm), stainless steel



KITPDQ

Height reduction feet (850 mm). stainless steel, for cookers

GTT

Totally extractable telescopic guides (1 level) Extraction: 433 mm Material: Stainless steel AISI 430 polished





SMOLD

Set of 7 silicone moulds for ice creams, ice lollies, pralines, ice cubes or to portion food. Usable from -60°C to +230°C

•se•smeg

Symbols glossary (TT)

