

FV25G1A

Product Family	Refrigerazione
Type	Professional Refrigerator
Intrastat	84182191
EAN code	8017709194604



Aesthetics

Control Panel	Professional	Front panel	Blue
Logo	Smeg		

Refrigerator compartment features

Internal lighting	Led
-------------------	-----

Technical Features

Capacity	250 l
Temperature range	+2/+15 °C
Standard Shelves	4
Maximum number of shelves recommended	5
Maximum number of drawers recommended	5
Lock	Standard equipment
Insulation	60 mm
Defrosting and evaporation of water condense	Automatic
Vaporisation	Ventilated
Electronic control	Elettronico a microprocessore
Battery backup for alarms electronic control unit	Optional
Datalogger	Yes
GSM module to advise with alarms via SMS	Optional
Free contacts for remote alarm	Standard equipment
LAN port	Optional
Lateral Passing Hole	Optional
Chart recorder	Optional

Refrigerant Gas	R290
CFC Free	Yes

Other technical features

Internal memory	4 MB / 46000 righe dati
-----------------	-------------------------

Options

Compatible accessories	CA1030, CA1030F, CADI1030, BTSTDA, FORODX, FOROSX, KRT80 , LANPORT , MGSMA , PREINTS , RGSTD, RPL1030, RPL1030F, TERMDIN, USPLUG , UKPLUG
------------------------	---

Performance / Energy Label

Noise level	49 dB(A)
-------------	----------

Electrical Connection

Voltage	230V, 50Hz	Frequency (Hz)	50 Hz
Plug	(F;E) Schuko		

Also available

Available version	blind door version; 60 Hz version
-------------------	-----------------------------------

Interface

Display language preference	Italian, English, French, Spanish	Audible alarm	Yes
Alarms shown on the display	Ultimi 20	Visible alarm	Yes
Display	LCD	Manual diagnosis	Yes
Type of alarm	Porta aperta, High temperature, Low temperature, Power failure, Dirty condenser, Buffer battery discharge, Faulty probes	USB port	Yes
Alarm indicator on display	Yes		

Electrical Connection

Voltage	230V, 50Hz	Frequency (Hz)	50 Hz
---------	------------	----------------	-------

Plug (F;E) Schuko

Construction

Door	Glass	Reversible door	Yes
Chamber Material	Stainless Steel AISI 304	Wheels	4
External material of the machine	Hot galvanised steel non-corrosive and non-toxic, coated with white PVC	Feet	2
Doors quantity	1	Compressors number	1

Not included accessories

LANPORT

KCAST4

4 rotating castors (2 with stop)



CADIPH1030

FOROSX

MGSMB

CADI1030

UKPLUG

RPL1030

MG SMA

CA1030F

BTSTDA

CAPH1030

RPL1030F

PREINTS

RGSTD

FORODX

CA1030

CAPH1030F

TERMDIN

USPLUG