

# HOB182DG

<b>Product Family</b>	Hob
<b>Built-in</b>	Ultra-low profile or Fully Flushed
<b>Dimensions</b>	80 cm
<b>Power supply</b>	Electric
<b>Type</b>	Induction with integrated hood
<b>Extraction</b>	Expulsion
<b>Electronic control</b>	Yes
<b>EAN code</b>	8017709331856
<b>Energy efficiency class ( EEC)</b>	A++



## Aesthetics



<b>Aesthetics</b>	Linea
<b>Colour</b>	Neptune Grey
<b>Finishing</b>	Glass
<b>Material</b>	Glass
<b>Glass Type</b>	Ceramic
<b>Glass edge</b>	Straight edge
<b>Pan stands</b>	Cast iron
<b>Type of control setting</b>	EVO Slider
<b>Slider</b>	Yes
<b>Slider</b>	White
<b>Control knobs position</b>	Front
<b>Logo</b>	Silk screen
<b>Serigraphy colour</b>	Grey

## Program / Functions



<b>No. of induction cook zones</b>	4
<b>Time-setting options</b>	Automatic switch-off
<b>No. of cooking zones with booster</b>	4
<b>No. of Flexible zones</b>	2
<b>Main on/off switch</b>	Yes
<b>Power levels</b>	9
<b>Total no. of cook zones</b>	4

## Options



<b>Multizone Option</b>	Yes	<b>Residual time indicator</b>	Yes
<b>Flexible Zone Type</b>	MultiZone	<b>Limited Power</b>	Yes advance
<b>Standard cut out</b>	482-483x765-766 mm	<b>Consumption Mode</b>	
<b>Keep warm automatic function</b>	Yes	<b>Limited Power Consumption Mode in W</b>	2800, 3500, 4500, 7400 W
<b>End cooking timer</b>	4	<b>Show Room Demo Option</b>	Yes
<b>Pause option</b>	Yes	<b>Control Lock / Child Safety</b>	Yes
<b>Minute minder</b>	1	<b>Cleaning option</b>	Yes
<b>End of cooking acoustic alarm</b>	Yes	<b>Quick start</b>	Yes
		<b>Rapid level selection</b>	Yes

## Technical Features



Front left - Induction - Multizone - 2.10 kW - Booster 3.00 kW - 21.0x19.0 cm  
 Rear left - Induction - multizone - 2.10 kW - Booster 3.00 kW - 21.0x19.0 cm  
 Rear right - 2.10 kW - Booster 3.00 kW - 21.0x19.0 cm  
 Front right - 2.10 kW - Booster 3.00 kW - 21.0x19.0 cm  
 Multizone left - Booster 3.70 kW - 39.0x21.0 cm  
 Multizone right - Booster 3.70 kW - 39.0x21.0 cm

<b>Automatic setting according to pan dimension</b>	Yes	<b>Automatic switch off when overflow</b>	Yes
<b>Automatic pan detection</b>	Yes, min 9 cm	<b>Residual heat indicator</b>	Yes
<b>Permanent Automatic Pot Detection with indication of the relative control</b>	Yes	<b>Protection against accidental start up</b>	Yes

## Accessories Included

**Other accessories**      Extraction and Filtering Kit inc tubes and Charcoal filter

## Electrical Connection

<b>Nominal power (W)</b>	7620 W	<b>Frequency (Hz)</b>	50/60 Hz
<b>Current</b>	33 A	<b>Power supply cable length</b>	120 cm
<b>Voltage (V)</b>	220-240 V	<b>Terminal Box</b>	6 poles
<b>Voltage 2 (V)</b>	380-415 V	<b>Plug</b>	No

Type of electric cable supplied	Yes, Single and Double phase
---------------------------------	------------------------------

## Controls (hood)

Hood control setting	Touch control	Display	Yes
Led colour	White		

## Programs / Functions (hood)

Delay function	Yes	Hood time setting	Delay
No. of speeds	8	Other options	Kit for Recirculation and Extraction included
Intensive speed	2		
Other functions	AUTOVENT	Auto-Vent	yes

## Technical Features (Hood)

Free outlet maximum capacity	750 m <sup>3</sup> /h	Anti-grease filters	Stainless steel
Motor power	220 W	Charcoal filters included	YES, regenerable
No. of filters	1	Filter replacement indicator	Yes

## Performance / Energy Label (hood)

Fluid Dynamic Efficiency (FDE)	37,60	Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)	51 dBA
Fluid Dynamic Efficiency class (FDEC)	A	Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	65 dBA
Lighting Efficiency (LE)	0,0 lux/W	Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)	72 dBA
Lighting Efficiency Class (LEC)	NA	Time increase factor (F)	0,6
Grease Filtering Efficiency (GFE)	85,1 %	Energy Efficiency Index per first cavity	32,8
Grease Filtering Efficiency Class (GFEC)	B	Measured air flow rate at best efficiency point (Qbep)	328 m <sup>3</sup> /h
Air flow at mininum speed (Qmin)	245 m <sup>3</sup> /h	Measured air pressure at best efficiency point (Qbep)	540 Pa
AIR FLOW AT MAXIMUM SPEED (QMAX)	505 m <sup>3</sup> /h	Measured electric power input at best efficiency point (Wbep)	131 W
Air flow at boost speed (Qboost)	700 m <sup>3</sup> /h	Sound power level at highest setting (Lwa)	65 dBA

---

## Speed 1

---

Extraction rate IEC 61591	245 m <sup>3</sup> /h
Noise level IEC 60704-2-13	51 dBA
Pressure	290 Pa
Power	35 W

---

## Speed 2

---

Extraction rate IEC 61591	285 m <sup>3</sup> /h
Noise level IEC 60704-2-13	55 dBA
Pressure	370 Pa
Power	45 W

---

## Speed 3

---

Extraction rate IEC 61591	350 m <sup>3</sup> /h
Noise level IEC 60704-2-13	57 dBA
Pressure	525 Pa
Power	65 W

---

## Speed 4

---

Extraction rate IEC 61591	380 m <sup>3</sup> /h
Noise level IEC 60704-2-13	59 dBA
Pressure	530 Pa
Power	75 W

---

## Speed 5

---

Extraction rate IEC 61591	410 m <sup>3</sup> /h
Noise level IEC 60704-2-13	62 dBA
Pressure	535 Pa
Power	85 W

---

## Speed 6

---

Extraction rate IEC 61591	445 m <sup>3</sup> /h
Noise level IEC 60704-2-13	63 dBA
Pressure	540 Pa
Power	105 W

---

## Speed 7

---

Extraction rate IEC 61591	475 m <sup>3</sup> /h
Noise level IEC 60704-2-13	64 dBA
Pressure	545 Pa
Power	115 W

---

## Speed 8

---

Extraction rate IEC 61591	505 m <sup>3</sup> /h
Noise level IEC 60704-2-13	65 dBA
Pressure	550 Pa
Power	130 W

---

## Intensive speed

---

Extraction rate (IEC 61591)	550 m <sup>3</sup> /h
Noise level IEC 60704-2-13	66 dBA
Pressure	555 Pa
Power	140 W

---

## Intensive Speed 2

---

Extraction rate IEC 61591	700 m <sup>3</sup> /h
Noise level IEC 60704-2-13	72 dBA
Pressure	560 Pa
Power	220 W



## Compatible Accessories



### CON60H

Flat duct connector for tubes 220\*60 mm. It helps to connect more tubes of the kit KITEHOBD4



### FLTHOBD4

Charcoal Anti Odour Filter regenerable as spare part suitable for HOBD482D



### KITEHOBD4

Filtering kit (lateral outlet) optional for Hobd: tube 1,5 mt and curve



### RED60H

Reducer from 90 to 60 mm suitable for rectangular tube of 220 mm. Size: 220x90x92 mm



### FLTHOBD

Ceramic Anti Odour Filter regenerable as spare part suitable for Recirculating kit (accessory KITF6HOBD) of the hob with integrated hood models HOBD682D and HOBD682R



### GRI60H


















Rectangular Louvred grille, external size 246\*80 mm and internal 226\*60\*50 mm



### KITF6HOBD

Recirculating kit for Hobd: tubes + regenerable anti-odor filter + grid in stainless steel with magnetic fix (easy to remove) that fit in a plinth of min. 6 cm

## Symbols glossary

 <p>Power booster: option allows the zone to work at full power when very intense cooking is necessary.</p>	 <p>Heavy duty cast iron pan stands: for maximum stability and strength.</p>
 <p>Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed.</p>	 <p>The slider control panel allows you to adjust the power simply by passing your finger across the touch device.</p>
 <p>Keep warm function: Keep warm function keeps the cooked food heated. In this mode the heating zone operates at a minimum capacity for 120 minutes and then turns off automatically.</p>	 <p>Multizone: allows several pans to be used at once, large or small, offering freedom of placement and greater flexibility</p>
 <p>Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids.</p>	 <p>PAUSE_72dpi</p>
 <p>Quick selection, with one touch cooking begins at the highest level, then automatically reduces after time. Ideal for dishes that require quick boiling and then continued cooking without constant control (eg beef broth).</p>	 <p>Quick Start function: the chosen temperature is reached faster. The heating element works at maximum power until the right temperature is reached.</p>
 <p>Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out.</p>	 <p>Time elapsed: shows how long the cooking zone has been in use.</p>
 <p>Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time.</p>	 <p>Permanent auto pot detection</p>
 <p>Min diameter pot detection of 9 cm</p>	 <p>Possibility to set the maximum power absorption of the hob</p>
 <p>Evolution Slider totally Back-lighted ghost effect</p>	