

HOB472D2

| | |
|---------------------------------------|------------------------------------|
| Product Family | Hob |
| Built-in | Ultra-low profile or Fully Flushed |
| Dimensions | 70 cm |
| Power supply | Electric |
| Type | Induction with integrated hood |
| Extraction | Expulsion |
| Electronic control | Yes |
| EAN code | 8017709341862 |
| Energy efficiency class (EEC) | A+ |



Aesthetics



| | |
|--------------------------------|-----------------|
| Aesthetics | Universal |
| Colour | Black |
| Finishing | Glass |
| Material | Glass |
| Glass Type | Ceramic |
| Glass edge | Straight edge |
| Pan stands | Stainless steel |
| Type of control setting | EVO Slider |
| Slider | Yes |
| Slider | Red |
| Control knobs position | Front |
| Logo | Silk screen |
| Serigraphy colour | Grey |

Program / Functions



| | |
|--|----------------------|
| No. of induction cook zones | 4 |
| Time-setting options | Automatic switch-off |
| No. of cooking zones with booster | 4 |
| No. of Flexible zones | 2 |
| Main on/off switch | Yes |
| Power levels | 9 |
| Total no. of cook zones | 4 |

Options



| | | | |
|--------------------------------------|------------|--|--------------------------|
| Multizone Option | Yes | Limited Power Consumption Mode | Yes advance |
| Flexible Zone Type | MultiZone | Limited Power Consumption Mode in W | 2800, 3500, 4500, 7400 W |
| Standard cut out | 490x560 mm | Show Room Demo Option | Yes |
| Keep warm automatic function | Yes | Control Lock / Child Safety | Yes |
| End cooking timer | 4 | Bridge option | Yes |
| Pause option | Yes | Cleaning option | Yes |
| Minute minder | 1 | Quick start | Yes |
| End of cooking acoustic alarm | Yes | Rapid level selection | Yes |
| Residual time indicator | Yes | | |

Technical Features



| | | | |
|--|---------------|---|-----|
| Front left - 2.10 kW - Booster 3.00 kW - 21.0X19.0 cm | | | |
| Rear left - 2.10 kW - Booster 3.00 kW - 21.0X19.0 cm | | | |
| Rear right - 2.10 kW - Booster 3.00 kW - 21.0X19.0 cm | | | |
| Front right - 2.10 kW - Booster 3.00 kW - 21.0X19.0 cm | | | |
| Multizone left - Booster 3.70 kW - 39.5x22.0 cm | | | |
| Multizone right - Booster 3.70 kW - 39.5x22.0 cm | | | |
| Automatic setting according to pan dimension | Yes | Automatic switch off when overflow | Yes |
| Automatic pan detection | Yes, min 9 cm | Residual heat indicator | Yes |
| Permanent Automatic Pot Detection with indication of the relative control | Yes | Protection against accidental start up | Yes |

Accessories Included

| | |
|--------------------------|--|
| Other accessories | Filtering kit and charcoal filter included |
|--------------------------|--|

Electrical Connection

| | | | |
|--------------------------|-----------|----------------------------------|----------|
| Nominal power (W) | 7620 W | Frequency (Hz) | 50/60 Hz |
| Current | 33 A | Power supply cable length | 120 cm |
| Voltage (V) | 220-240 V | Terminal Box | 6 poles |
| Voltage 2 (V) | 380-415 V | Plug | No |

| | |
|---------------------------------|------------------------------|
| Type of electric cable supplied | Yes, Single and Double phase |
|---------------------------------|------------------------------|

Controls (hood)

| | | | |
|----------------------|------------------|---------|-----|
| Hood control setting | Touch Capacitive | Display | Yes |
| Led colour | Red | | |

Programs / Functions (hood)

| | | | |
|-----------------|-----|-------------------|---------------------|
| Delay function | Yes | Hood time setting | Delay |
| No. of speeds | 8 | Other options | Filter Kit included |
| Intensive speed | 2 | Auto-Vent | yes |

Technical Features (Hood)

| | | | |
|------------------------------|-----------------------|------------------------------|------------------|
| Free outlet maximum capacity | 650 m ³ /h | Anti-grease filters | Stainless steel |
| Motor power | 220 W | Charcoal filters included | YES, regenerable |
| No. of filters | 1 | Filter replacement indicator | Yes |

Performance / Energy Label (hood)

| | | | |
|--|-----------------------|--|-----------------------|
| Fluid Dynamic Efficiency (FDE) | 32,10 | Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) | 49 dBA |
| Fluid Dynamic Efficiency class (FDEC) | A | Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) | 68 dBA |
| Lighting Efficiency (LE) | 0,0 lux/W | Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) | 73 dBA |
| Lighting Efficiency Class (LEC) | NA | Time increase factor (F) | 0,8 |
| Grease Filtering Efficiency (GFE) | 85,1 % | Energy Efficiency Index per first cavity | 44,2 |
| Grease Filtering Efficiency Class (GFEC) | B | Measured air flow rate at best efficiency point (Qbep) | 320 m ³ /h |
| Air flow at mininum speed (Qmin) | 230 m ³ /h | Measured air pressure at best efficiency point (Qbep) | 502 Pa |
| AIR FLOW AT MAXIMUM SPEED (QMAX) | 500 m ³ /h | Measured electric power input at best efficiency point (Wbep) | 139 W |
| Air flow at boost speed (Qboost) | 630 m ³ /h | Sound power level at highest setting (Lwa) | 68 dBA |

Speed 1

| | |
|----------------------------|-----------------------|
| Extraction rate IEC 61591 | 230 m ³ /h |
| Noise level IEC 60704-2-13 | 49 dBA |
| Pressure | 280 Pa |
| Power | 40 W |

Speed 2

| | |
|----------------------------|-----------------------|
| Extraction rate IEC 61591 | 270 m ³ /h |
| Noise level IEC 60704-2-13 | 51 dBA |
| Pressure | 370 Pa |
| Power | 50 W |

Speed 3

| | |
|----------------------------|-----------------------|
| Extraction rate IEC 61591 | 340 m ³ /h |
| Noise level IEC 60704-2-13 | 51 dBA |
| Pressure | 400 Pa |
| Power | 70 W |

Speed 4

| | |
|----------------------------|-----------------------|
| Extraction rate IEC 61591 | 370 m ³ /h |
| Noise level IEC 60704-2-13 | 60 dBA |
| Pressure | 570 Pa |
| Power | 90 W |

Speed 5

| | |
|----------------------------|-----------------------|
| Extraction rate IEC 61591 | 400 m ³ /h |
| Noise level IEC 60704-2-13 | 62 dBA |
| Pressure | 500 Pa |
| Power | 100 W |

Speed 6

| | |
|----------------------------|-----------------------|
| Extraction rate IEC 61591 | 435 m ³ /h |
| Noise level IEC 60704-2-13 | 63 dBA |
| Pressure | 550 Pa |
| Power | 120 W |

Speed 7

| | |
|----------------------------|-----------------------|
| Extraction rate IEC 61591 | 460 m ³ /h |
| Noise level IEC 60704-2-13 | 65 dBA |
| Pressure | 600 Pa |
| Power | 150 W |

Speed 8





| | |
|----------------------------|-----------------------|
| Extraction rate IEC 61591 | 500 m ³ /h |
| Noise level IEC 60704-2-13 | 68 dBA |
| Pressure | 620 Pa |
| Power | 170 W |

Intensive speed

| | |
|-----------------------------|-----------------------|
| Extraction rate (IEC 61591) | 540 m ³ /h |
| Noise level IEC 60704-2-13 | 70 dBA |
| Pressure | 625 Pa |
| Power | 180 W |

Intensive Speed 2

| | |
|----------------------------|-----------------------|
| Extraction rate IEC 61591 | 630 m ³ /h |
| Noise level IEC 60704-2-13 | 73 dBA |
| Pressure | 630 Pa |
| Power | 220 W |



Compatible Accessories



CON60H

Flat duct connector for tubes 220*60 mm. It helps to connect more tubes of the kit KITEHOBD4




CON90H

Connector for rectangular tubes high 90 mm. Size external 227*94*63 mm, internal 223*90*63 mm



FLTHOBD2

n.2 high-performance carbon filters regenerable up to 8 times, washing it in the dishwasher and drying it at max 70° in the oven for max 120 minutes



FLTSTDHOBD2

Anti Odour Filter not regenerable as spare part, suitable for recirculation mode.



GRI60H

Rectangular Louvred grille, external size 246*80 mm and internal 226*60*50 mm



GRILLPLATE

Universal griddle for induction, gas, ceramic and electric hobs. Non-stick surface ideal for cooking meat, cheese and vegetables. Dimensions: 410 x 240 mm.



GRIX6H

Stainless steel ventilation grille, size 426*60 mm.



KITDT50X10

tape for installation kit of HOBD*2. 10 m lenght. 50 mm width.



KITEHOBD10

Ducted kit for HOBD*2 with tubes and curve high 10 mm.



KITEHOBD4

Filtering kit (lateral outlet) optional for Hobd: tube 1,5 mt and curve



KITREBFLOW

Rectangular grid used in ventilation system. It regulates the air flow from the kitchen. Suitable for HOBD*2 models.



KITRHOB6

Mounting kit for recirculating installation: pipes and curves to be mounted in a plinth of minimum 6cm height. Available for HOBD*2 series.



KITSEBL

Squared grid used in ventilation system with backdraft Damper for regulating the air flow from the kitchen. Compatible for HOBD*2 models.



RED60H

Reducer from 90 to 60 mm suitable for rectangular tube of 220 mm. Size: 220x90x92 mm

TPKPLATE



Universal plate for induction, gas, ceramic and electric hobs. Non-stick surface ideal for cooking fish, eggs and vegetables. Dimensions: 410 X 240 mm.

Symbols glossary

| | | | |
|--|--|---|--|
|  | Permanent auto pot detection |  | Power booster: option allows the zone to work at full power when very intense cooking is necessary. |
|  | Child lock: some models are fitted with a device to lock the programme/cycle so it cannot be accidentally changed. |  | Evolution Slider totally Back-lighted ghost effect |
|  | The slider control panel allows you to adjust the power simply by passing your finger across the touch device. |  | Keep warm function: Keep warm function keeps the cooked food heated. In this mode the heating zone operates at a minimum capacity for 120 minutes and then turns off automatically. |
|  | Multizone: allows several pans to be used at once, large or small, offering freedom of placement and greater flexibility |  | Overfill protection: The special overfill protection shuts down the stove in the presence of overflow of liquids. |
|  | Min diameter pot detection of 9 cm |  | PAUSE_72dpi |
|  | Possibility to set the maximum power absorption of the hob |  | Quick selection, with one touch cooking begins at the highest level, then automatically reduces after time. Ideal for dishes that require quick boiling and then continued cooking without constant control (eg beef broth). |
|  | Quick Start function: the chosen temperature is reached faster. The heating element works at maximum power until the right temperature is reached. |  | Indication of residual heat: After the glass ceramic hob is switched off the residual heat indicator shows which of the heating zones still remains hot. When the temperature drops below 60 ° C, the indicator goes out. |
|  | Time elapsed: shows how long the cooking zone has been in use. |  | Timer: All ceramic hobs have a timer which automatically ends cooking after a preset time. |
|  | TWIN_ZONE_72dpi | | |