

HTY505DAUS

Family	Dishwasher
Subfamily	Hoodtype dishwasher
Basket dimensions	500x500 mm
Panel	Ecoline 2016
Filter	5-stages filter system
Rinse pump H.T.R. system	Rinse pump with atmospheric boiler
Usable load height	440 mm
Power connection	400 V 3N~ / 16 A / 9,7 kW / 50 Hz
Product dimensions WxDxH	620x736x1530 mm



Distribution

Solutions	Bars/Cafes; Hotels; Restaurants/Catering; Butcher's shops; Schools; QSR
-----------	--

Aesthetics

Serie	Ecoline	Led color	Red
Control panel	Electronic		

Functions



Functionality	GN 1/1 trays washing; 5-stage filter; HTR; Door clearance 440mm
---------------	---

Programs

Program specifications	Boiler 85°C/Tank 60°C-1'30"; Boiler 85°C/Tank 60°C-2'30"; Boiler 85°C/Tank 60°C-4'
Drain and self cleaning cycle	Yes
Maximum basket/hour	40
Maximum dishes/hour	720

Interface

Display	4 digit	Cycle progress alert	Yes
Number of buttons	5	End-cycle alert	Yes
On/Off button	Yes	Manual diagnostic	Yes

Construction

Tank	Deep drawn	Hood	Single wall
Construction	Double wall	Tank capacity	14 l
Tank material	Stainless steel AISI 304	Boiler capacity	8 l
Back panel	Prepainted	Protection class	IPX4
Tank filter	Stainless steel	Net weight	108,000 kg
Washing spray arm	Stainless steel	Drain max. height	1000 mm
Rinse spray arm	Stainless steel		

Technical Features

Tank heating element	2200 W	Water inlet	Cold 15°C
Boiler heating element	9000 W	Max temperature inlet water	60°C
Washing pump	700 W	Max water hardness	12°F - 7°dH
Default connection	9700 W	Water inlet	Cold 15°C
Water cycle consumption	2,7 l		

Electrical Connection

Plug	Not present	Electrical connection option	230 V~ / 29 A / 6,7 kW / 50 Hz; 400 V 3N~ / 13 A / 6,7 kW / 50 Hz
------	-------------	------------------------------	---

Equipments

Peristaltic detergent doser	Yes, electronic control	Cycle counter	Yes
Peristaltic rinse-aid doser	Yes, electronic control	Break tank	Yes
Default chemicals dosing unit of measure	gr/l	Partial renewal of water in the tank and built-in drain pump	Si
Boiler thermostat	Yes default ON	Trays washing option GN1/1 530x325mm	Yes
Soft Start	Yes	Water supply pipe diameter	16 mm
Automatic start	Yes, default OFF	Drain supply pipe diameter	21,5 mm
Detergent load	Yes, manual	Peristaltic detergent doser	Yes, manual
Rinse load	Yes, manual		

**Peristaltic detergent
doser**

Yes, manual

Accessories Included

Dish basket

PB50D01

Cutlery basket

PHOOS02

Flat basket

1x PB50G02

Water supply pipe

In acciaio Watermark

Drain pipe

Yes - 2m

Not included accessories



WT5700SR

Entry table right side 700mm



WT51200SR

Entry table right side 1200mm



WT5700SL

Entry table left side 700mm



WH00S01

Wire insert for 12 small dishes



WTX5700R

Exit table right side 700mm




WTX51200L

Exit table left side 1200mm



WB50G01

Universal wire basket with flat bottom
500x500



PB50D01

Basket made of polypropylene for 18 plates
500x500



WTX51200R

Exit table right side 1200mm



WTX51200

Exit table both sides 1200mm



PHOOS03

Basket in polypropylene with 6
compartments for cutlery for Capote



WT51200SHL

Entry table left side 1200mm



PHOOS01

Single basket in polypropylene for
cutlery



WB50T02

Wire basket for 5 trays 600x500



WT51200SHR

Entry table right side 1200mm



WT51200SL

Entry table left side 1200mm



WB50G02

Wire basket for glasses with inclined
bottom 500x500



PB50G01

Universal basket in polypropylene
500x500

**WB50G04**

Wire basket for glasses with inclined bottom 500x500

**WTX5700**

Exit table both sides 700mm

**PHOOS02**

Basket in polypropylene for cutlery with 6 compartments

**WB50D01**

Wire basket for 18 dishes and trays 500x500

**WB50G03**

Wire basket for glasses with inclined bottom 500x500

**WTX5700L**

Exit table left side 700mm

Symbols glossary (TT)



...



...



...



5 STAGE FILTER