

# KATE600CEX

Product family	Hood
Hood Type	Decorative wall hood
Design	T flat
Extraction	Extraction
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709255053
Hood width	60 cm
Aesthetic	Universale
Colour	Stainless steel
Finishing	Satin
Logo	Silk screen



## Controls

Control setting	Buttons
-----------------	---------

## Program / Functions

No. of speeds	3
---------------	---

## Technical Features



No. of lights	2	No. of filters	2
Light type	LED	Anti-grease filters	Aluminium
Light Power	2,5 W	Vent outlet	150 mm
Light color temperature scale (K)	3500 K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	612 m <sup>3</sup> /h	Minimum distance from ELECTRIC hob	500 mm
Motor power	175 W	Non return valve	Yes

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	241	46
Speed 2	370	56

Speed 3	590	65
------------	-----	----

## Accessories included



Tube reduction Yes

Charcoal filters included Yes

## Performance / Energy Label



**Annual Efficiency Consumption (AEChood)** 77 kWh/a  
**Energy efficiency class (EEC)** C  
**Fluid Dynamic Efficiency (FDE)** 20,2  
**Fluid Dynamic Efficiency class (FDEC)** C  
**Lighting Efficiency (LE)** 76,1 lux/W  
**Lighting Efficiency Class (LEC)** A  
**Grease Filtering Efficiency (GFE)** 76 %  
**Grease Filtering Efficiency Class (GFEC)** C  
**Air flow at minimum speed (Qmin)** 240 m<sup>3</sup>/h  
**Air flow at maximum speed (Qmax)** 581 m<sup>3</sup>/h

**Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)** 47 dBA  
**Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)** 68 dBA  
**Time increase factor (F)** 1,3  
**Measured air flow rate at best efficiency point (Qbep)** 336 m<sup>3</sup>/h  
**Measured air pressure at best efficiency point (Pbep)** 334 Pa  
**Measured electric power input at best efficiency point (Wbep)** 155 W  
**Nominal Power consumption of the light system (WL)** 5 W  
**Average illumination of the light on the cooking surface (Emiddle)** 381 lux  
**Sound power level at highest setting (Lwa)** 68 dBA

## Electrical Connection

**Electrical connection rating** 180 W  
**Voltage** 220-240 V  
**Frequency (Hz)** 50-60 Hz

**Power supply cable length** 1500 mm  
**Plug** Not present

## Optional accessories

**Chimney extension** KITCMNKAT



---

## Compatible Accessories

---



### KITCMNKAT

Chimney extension dimension 241 \* 231 \* 810 T-shape hood KAT & KATE  
Stainless Steel



### KITFC900

Charcoal filter. Kit 1 piece. High performances. Regenerable. To be whased after 3 months of use with hot water. To be changed after 3 years of use.



### KITFC999

Charcoal filter Kit 1 piece

---

## Symbols glossary

---



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Charcoal filters:** Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.