

KATE600CEX

Product family Hood

Hood Type Decorative wall hood

Design T flat Extraction Extraction Stainless steel Material Type of steel Brushed

EAN code 8017709255053

Hood width 60 cm



Aesthetics

Universale **Aesthetic** Finishing Satin Colour Stainless steel Logo Silk screen

Controls

Control setting **Buttons**

Programs / Functions

3 No. of speeds

Technical Features



No. of lights Anti-grease filters Aluminium 2 Light type **LED** Charcoal filters included Yes **Light Power** 2.5 W Vent outlet 150 mm Light color temperature 3500 °K Minimum distance from 650 mm GAS hob

scale (°K)

Free outlet maximum Minimum distance from 500 mm 612 m³/h capacity **ELECTRIC hob**

Motor power 175 W Non return valve Yes No. of filters 2



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	241	46
Speed 2	370	56
Speed 3	590	65

Accessories Included

Tube reduction Yes

Performance / Energy Label

C

Annual Efficiency 77 kWh/a Airbourne acouistical A- 47 dB(A) Consumption (AEChood) weighted sound Power **Emission at minimum** Energy efficieency class C speed (SPEmin) (EEC) Airborne acoustical A-68 dB(A) Fluid Dynamic Efficiency 20.2 weighted sound Power (FDE) Emission at maximum Fluid Dynamic Efficiency C speed (SPEmax) class (FDEC) Time increase factor (F) 1.3 Lighting Efficiency (LE) 76.1 lux/W Measured air flow rate 336 m³/h Lighting Efficiency Class A at best efficiency point (LEC) (Qbep) **Grease Filtering** 76 % Measured air pressure 334 Pa Efficiency (GFE) at best efficiency point **Grease Filtering** (Pbep) Efficiency Class (GFEC) Measured electric 155 W Air flow at minumum 240 m³/h power input at best speed (Qmin) efficiency point (Wbep) Air flow at maximum 581 m³/h **Nominal Power** 5 W speed (Qmax) consumption of the light system (WL) Average illumination of 381 lux the light on the cooking surface (Emiddle) Sound power level at 68 dB(A) highest setting (Lwa)


Electrical Connection

Electrical connection 180 W Frequency (Hz) 50-60 Hz rating Power supply cable 1500 mm Voltage 220-240 V length



Optional accessories

Chimney extension KITCMNKAT





Not included accessories



KITFC900

Charcoal filter Kit 1 piece high perfrmances washable



KITCMNKAT

Chimney extension dimension 241 * 231 * 810 T-shape hood KAT & KATE Stainless Steel

KITFC999



Charcoal filter Kit 1 piece



Symbols glossary (TT)



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



C: Product energy rating



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.