

# KATE900EX

Product family Hood

Hood Type Chimney Cooker Hoods

Design T flat

**Extraction** Ducted out or re-circulation possible

MaterialStainless steelType of steelBrushed

**EAN code** 8017709235147

Hood width 90 cm



### **Aesthetics**

AestheticsUniversalSerigraphy colourBlackColourStainless steelLogoSilk screen

Finishing Brushed

### **Controls**

Control setting Buttons

## **Programs / Functions**

No. of speeds 3

### **Technical Features**



Motor power

No. of lights 2 No. of filters 3

Light typeLEDAnti-grease filtersAluminiumLight power2.5 WVent outlet150 mmLight colour3500 °KMinimum distance from<br/>650 mm

temperature scale (°K) GAS hob

175 W

Free outlet maximum 612 m³/h Minimum distance from 500 mm

capacity ELECTRIC hob

. Non return valve Yes



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	241	46
Speed 2	370	56
Speed 3	590	67

### Performance / Energy Label

C

**Annual Efficiency** 77 KWh/year Airbourne acouistical A- 47 dB(A) Consumption (AEChood) weighted sound Power Emission at minimum Energy efficiency class ( C speed (SPEmin) EEC) Airborne acoustical A-68 dB(A) Fluid Dynamic Efficiency 20,2 weighted sound Power (FDE) Emission at maximum Fluid Dynamic Efficiency C speed (SPEmax) class (FDEC) Time increase factor (F) Lighting Efficiency (LE) 76,1 lux/W Measured air flow rate Lighting Efficiency Class A at best efficiency point (LEC)

Lighting Efficiency Class A
(LEC)

Grease Filtering

Grease Filtering

Grease Filtering

Grease Filtering

C

Efficiency Class (GFEC)

Measured air flow rate at best efficiency point (Qbep)

Measured air pressure at best efficiency point (Qbep)

Efficiency Class (GFEC) Measured electric 155 W Air flow at minumum 240 m<sup>3</sup>/h power input at best speed (Qmin) efficiency point (Wbep) Maximum extraction 581 m<sup>3</sup>/h Normal Power of the 5 W rate light system (WI) Average illumination of 381 lux

the light on the cooking surface (Emiddle)

Sound power level at 68 dB(A) highest setting (Lwa)


**Electrical Connection** 

Nominal power 180 W Frequency (Hz) 50-60 Hz Voltage 220-240 V Power supply cable 1500 mm length

Optional accessories

Charcoal filter KITFC900 - KITFC999 Chimney extension KITCMNKAT







## Not included accessories



#### KITFC900

Charcoal filter Kit 1 piece high perfrmances washable



### **KITCMNKAT**

Chimney extension dimension 241 \* 231 \* 810 T-shape hood KAT & KATE Stainless Steel

### KITFC999



Charcoal filter Kit 1 piece



# Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



C: Product energy rating



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.