

KBT110BL

Product family	Hood
Hood Type	Chimney Cooker Hoods
Design	T flat
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Material	Stainless steel
Type of steel	Polished
EAN code	8017709358839
Hood width	110 cm
Aesthetics	Universal
Colour	Black
Finishing	Gloss
Logo	Silk screen




Controls

Control setting	Electronic buttons
------------------------	--------------------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	

Technical Features



No. of lights	2	Anti-grease filters	Aluminium
Light type	LED	Filter replacement indicator	Yes
Light power	2.5 W	Vent outlet	150 mm
Light colour	3000 K	Minimum distance from GAS hob	650 mm
temperature scale (K)		Minimum distance from ELECTRIC hob	500 mm
Free outlet maximum capacity	704 m³/h	Non return valve	Yes
Motor power	230 W		
No. of filters	3		

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	257	44
Speed 2	360	55
Speed 3	438	60
Intensive speed	704	68

Accessories Included

Tube reduction Yes


Performance / Energy Label

	Annual Efficiency Consumption (AEChood)	52 kWh/year	Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin)	44 dBA
	Energy efficiency class (A EEC)		Airborne acoustical A- weighted sound Power Emission at maximum speed (SPEmax)	60 dBA
	Fluid Dynamic Efficiency (FDE)	29.7	Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)	68 dBA
	Fluid Dynamic Efficiency class (FDEC)	A	Time increase factor (F)	0.49
	Lighting Efficiency (LE)	54 lux/W	Energy Efficiency Index per first cavity	51.7
	Lighting Efficiency Class (LEC)	A	Measured air flow rate at best efficiency point (Qbep)	373 m ³ /h
	Grease Filtering Efficiency (GFE)	69.4 %	Measured air pressure at best efficiency point (Qbep)	438 Pa
	Grease Filtering Efficiency Class (GFEC)	D	Measured electric power input at best efficiency point (Wbep)	152.8 W
	Air flow at minimum speed (Qmin)	257 m ³ /h	Normal Power of the light system (WI)	2.6 W
	Maximum extraction rate	463 m ³ /h	Average illumination of the light on the cooking surface (Emiddle)	141 lux
	Intensive extraction rate	704 m ³ /h	Sound power level at highest setting (Lwa)	68 dBA

Electrical Connection

Voltage 220-240 V


Frequency (Hz)	50-60 Hz	Power supply cable length	1500 mm
		Plug	No



Compatible Accessories




KITCEKBTMB



KITFCKBT

1 pcs of activated carbon filter for
hood models KBT* / KBCT*



KITFCKBTR

1 pcs of Charcoal filter Regenerable*
suitable for all the KBT/KBCT models. * It
can be washed in the dishwasher up to
12 times and dry in the oven at max 90°
for 60 min. dimension 237,5(H)x245x10
mm

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



A: Product drying performance, measured from A+++ to D / G depending on the product family



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.