

KBT110BL

Product family Hood

Hood Type Chimney Cooker Hoods

Design

Extraction Ducted out or re-circulation possible

Electronic control Yes

Material Stainless steel Type of steel Polished

EAN code 8017709358839

Hood width 110 cm **Aesthetics** Universal Colour Black **Finishing** Gloss Logo Silk screen



Controls

Control setting Electronic buttons

Program / Functions

No. of speeds Intensive speed

24h air filter function

Time-setting options







Technical Features







No. of lights 2 Light type LED Light power 2,5 W Light colour 3000 K

temperature scale (K)

Free outlet maximum 704 m³/h

capacity

230 W Motor power No. of filters 3

Anti-grease filters

Filter replacement indicator

Vent outlet Minimum distance from

GAS hob

Minimum distance from

ELECTRIC hob

Aluminium Yes

150 mm 650 mm

500 mm

Non return valve Yes

SMEG SPA 28/11/2025



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	257	44
Speed 2	360	55
Speed 3	438	60
Intensive speed	704	68

Accessories Included

Tube reduction Yes

Performance / Energy Label

/	A'''
	D

Airbourne acouistical A- 44 dBA **Annual Efficiency** 52 kWh/year Consumption (AEChood) weighted sound Power Emission at minimum Energy efficiency class (A speed (SPEmin) Airborne acoustical A-60 dBA Fluid Dynamic Efficiency 29,7 weighted sound Power (FDE) **Emission at maximum** Fluid Dynamic Efficiency A speed (SPEmax) class (FDEC) Airbourne acoustical A- 68 dBA Lighting Efficiency (LE) 54 lux/W weighted sound power Lighting Efficiency Class A emission at boost speed (LEC) (SPEboost) **Grease Filtering** 69.4 % Time increase factor (F) Efficiency (GFE) **Energy Efficiency Index** 51.7 **Grease Filtering** D per first cavity Efficiency Class (GFEC) Measured air flow rate 373 m³/h Air flow at minumum 257 m³/h at best efficiency point speed (Qmin) (Qbep) Maximum extraction 463 m³/h Measured air pressure 438 Pa rate at best efficiency point Intensive extraction rate 704 m³/h (Qbep) Measured electric 152.8 W power input at best efficiency point (Wbep) Normal Power of the 2.6 W light system (WI) Average illumination of 141 lux the light on the cooking

Electrical Connection

Voltage 220-240 V

SMEG SPA 28/11/2025

surface (Emiddle) Sound power level at

highest setting (Lwa)

68 dBA



Frequency (Hz)

50-60 Hz

Power supply cable length

1500 mm

SMEG SPA 28/11/2025



Compatible Accessories



KITCEKBTMB



KITFCKBT

1 pcs of activated carbon filter for hood models KBT* / KBCT*





1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

SMEG SPA 28/11/2025



Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



A: Product drying performance, measured from A+++ to D / G depending on the product family



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.

SMEG SPA 28/11/2025