

KBT110BL




Product family	Hood
Hood Type	Decorative wall hood
Design	T flat
Extraction	Extraction
Electronic control	Yes
Material	Stainless steel
Type of steel	Polished
EAN code	8017709358839
Hood width	110 cm
Aesthetic	Universale
Colour	Black
Finishing	Glossy
Logo	Silk screen



Controls

Control setting	Electronic buttons
-----------------	--------------------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	

Technical Features

				
No. of lights	2		Anti-grease filters	Aluminium
Light type	LED		Filter replacement indicator	Yes
Light Power	2.5 W		Vent outlet	150 mm
Light color temperature scale (K)	3000 K		Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	704 m³/h		Minimum distance from ELECTRIC hob	500 mm
Motor power	230 W		Non return valve	Yes
No. of filters	3			

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	257	44
Speed 2	360	55
Speed 3	438	60
Intensive speed	704	68

Accessories included

Tube reduction Yes

Performance / Energy Label



Annual Efficiency Consumption (AEChood) 52 kWh/a
Energy efficiency class (EEC) A
Fluid Dynamic Efficiency (FDE) 29.7
Fluid Dynamic Efficiency class (FDEC) A
Lighting Efficiency (LE) 54 lux/W
Lighting Efficiency Class (LEC) A
Grease Filtering Efficiency (GFE) 69.4 %
Grease Filtering Efficiency Class (GFEC) D
Air flow at minumum speed (Qmin) 257 m³/h
Air flow at maximum speed (Qmax) 463 m³/h
Air flow at boost speed (Qboost) 704 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) 44 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 60 dBA
Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) 68 dBA
Time increase factor (F) 0.49
Energy Efficiency Index 51.7
Measured air flow rate at best efficiency point (Qbep) 373 m³/h
Measured air pressure at best efficiency point (Pbep) 438 Pa
Measured electric power input at best efficiency point (Wbep) 152.8 W
Nominal Power consumption of the light system (WL) 2.6 W
Average illumination of the light on the cooking surface (Emiddle) 141 lux
Sound power level at highest setting (Lwa) 68 dBA

Electrical Connection

Voltage 220-240 V




Frequency (Hz)	50-60 Hz	Power supply cable length	1500 mm
		Plug	Not present

Compatible Accessories




KITCEKBTMB



KITFCKBT








1 pc of charcoal filter for the hood models KBT* / KBCT*



KITFCKBTR

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

Symbols glossary

	24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.		Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.
	Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.		Energy efficiency class A
	Warning light(s): to advise when filters need changing.		Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.
	Intensive/turbo setting: when extra fast extraction is required.		