

# KBT110BL

Product family Hood

Hood Type Decorative wall hood

Design T flat
Extraction Extraction
Electronic control Yes

MaterialStainless steelType of steelPolished

**EAN code** 8017709358839

Hood width 110 cm
Aesthetic Universale
Colour Black
Finishing Glossy
Logo Silk screen



### **Controls**

Control setting Electronic buttons

## **Program / Functions**

No. of speeds Intensive speed

24h air filter function

Time-setting options







## **Technical Features**







No. of lights 2 Light type LED Light Power 2,5 W Light color temperature 3000 K

scale (K)

Free outlet maximum 704 m³/h

capacity

Motor power 230 W No. of filters 3 Anti-grease filters Filter replacement

Yes

Vent outlet Minimum distance from

GAS hob

indicator

Minimum distance from

**ELECTRIC hob** 

Non return valve

500 mm

150 mm

650 mm

Aluminium

Yes



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	257	44
Speed 2	360	55
Speed 3	438	60
Intensive speed	704	68

### Accessories included

Tube reduction Yes

## Performance / Energy Label

/	K
	Ď

Airbourne acouistical A- 44 dBA **Annual Efficiency** 52 kWh/a Consumption (AEChood) weighted sound Power Emission at minimum Energy efficieency class A speed (SPEmin) (EEC) Airborne acoustical A-60 dBA Fluid Dynamic Efficiency 29,7 weighted sound Power (FDE) **Emission at maximum** Fluid Dynamic Efficiency A speed (SPEmax) class (FDEC) Airbourne acoustical A- 68 dBA Lighting Efficiency (LE) 54 lux/W weighted sound power Lighting Efficiency Class A emission at boost speed (LEC) (SPEboost) **Grease Filtering** 69.4 % Time increase factor (F) 0,49 Efficiency (GFE) **Energy Efficiency Index** 51.7 **Grease Filtering** D Measured air flow rate 373 m<sup>3</sup>/h Efficiency Class (GFEC) at best efficiency point Air flow at minumum 257 m<sup>3</sup>/h (Qbep) speed (Qmin) Measured air pressure 438 Pa Air flow at maximum 463 m<sup>3</sup>/h at best efficiency point speed (Qmax) (Pbep) Air flow at boost speed 704 m<sup>3</sup>/h Measured electric 152.8 W (Qboost) power input at best efficiency point (Wbep) **Nominal Power** 2,6 W consumption of the light system (WL) Average illumination of 141 lux the light on the cooking

## **Electrical Connection**

Voltage 220-240 V

SMEG SPA 12/9/2025

surface (Emiddle) Sound power level at

highest setting (Lwa)

68 dBA



Frequency (Hz)

50-60 Hz

Power supply cable length

Plug

1500 mm

Not present



# **Compatible Accessories**



#### **KITCEKBTMB**



#### **KITFCKBT**

1 pc of charcoal filter for the hood models KBT\* / KBCT\*





1 pcs of Charcoal filter Regenerable\* suitable for all the KBT/KBCT models. \* It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm



## Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Energy efficiency class A



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.