

# KBT1200XE

**Product family** Hood

**Hood Type** Decorative wall hood

Design T flat Extraction Extraction Yes **Electronic control** 

Material Stainless steel Type of steel Brushed

EAN code 8017709286637

Hood width 120 cm **Aesthetic** Universale Colour Stainless steel

**Finishing** Satin Logo Silk screen



#### **Controls**

Control setting **Electronic buttons** 

### **Program / Functions**

No. of speeds Intensive speed

24h air filter function

Time-setting options







### **Technical Features**









No. of lights 2 Light type LED **Light Power** 1,3 W 3000 K Light color temperature

scale (K)

Free outlet maximum 610 m<sup>3</sup>/h

capacity

230 W Motor power No. of filters 4

Anti-grease filters Filter replacement

indicator

Vent outlet Minimum distance from

**GAS** hob

Minimum distance from

**ELECTRIC hob** 

Non return valve

Aluminium Yes

150 mm 650 mm

650 mm

Yes

**SMEG SPA** 15/12/2025



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	251	48
Speed 2	345	56
Speed 3	454	62
Intensive speed	690	72

## Accessories included

Tube reduction Yes

## Performance / Energy Label

-	****
	4
	'n

Annual Efficiency Consumption (AEChood)	55 kWh/a	Airbourne acouistical A- weighted sound Power	47 dBA
Energy efficicency class (EEC)	Α	Emission at minimum speed (SPEmin)	
Fluid Dynamic Efficiency (FDE)	30,2	Airborne acoustical A- weighted sound Power	61 dBA
Fluid Dynamic Efficiency class (FDEC)	Α	Emission at maximum speed (SPEmax)	
Lighting Efficiency (LE)	58,8 lux/W	Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)	71 dBA
Lighting Efficiency Class (LEC)	Α		
Grease Filtering	79,6 %	Time increase factor (F)	0,9
Efficiency (GFE)		Energy Efficiency Index	52,1
Grease Filtering Efficiency Class (GFEC)	С	Measured air flow rate at best efficiency point	387 m³/h
Air flow at minumum speed (Qmin)	251 m³/h 454 m³/h	(Qbep)	
Air flow at maximum speed (Qmax)		Measured air pressure at best efficiency point (Pbep)	452 Pa
Air flow at boost speed (Qboost)	690 m³/h	Measured electric power input at best efficiency point (Wbep)	161 W
		Nominal Power consumption of the light system (WL)	3 W
		Average illumination of the light on the cooking surface (Emiddle)	153 lux

## **Electrical Connection**

SMEG SPA 15/12/2025

Sound power level at

highest setting (Lwa)

72 dBA



**Electrical connection** 

230 W

rating

Voltage

Frequency (Hz)

220-240 V

50-60 Hz


Power supply cable

length

Plug

1500 mm

Not present



SMEG SPA 15/12/2025



## **Compatible Accessories**



#### **KITCEKBT**

Chimney extension, dimensions 261,5 \* 260 \* 830 mm suitable for T-shape hood KBT\* & KBCT\*, max hight 1380 mm Stainless Steel



#### **KITFCKBT**

1 pc of charcoal filter for the hood models KBT\* / KBCT\*

#### **KITFCKBTR**



1 pcs of Charcoal filter Regenerable\* suitable for all the KBT/KBCT models. \* It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

SMEG SPA 15/12/2025



## Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Energy efficiency class A



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.

SMEG SPA 15/12/2025