

KBT600BL

Product family

Hood

Hood Type

Decorative wall hood

Design

T flat

Extraction

Extraction

Electronic control

Yes

Material

Stainless steel

EAN code

8017709347246

Hood width

60 cm

Aesthetic

Universale

Colour

Black

Logo

Silk screen



Controls

Control setting

Electronic buttons

Program / Functions

No. of speeds

3

Intensive speed



24h air filter function



Time-setting options



Technical Features



No. of lights

2

Anti-grease filters

Aluminium

Light type

LED

Filter replacement indicator

Yes

Light Power

1,3 W

Vent outlet

150 mm

Light color temperature scale (K)

3000 K

Minimum distance from GAS hob

650 mm

Free outlet maximum capacity

820 m³/h

Minimum distance from ELECTRIC hob

500 mm

Motor power

230 W

Non return valve

Yes

No. of filters

2

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	260	49
Speed 2	358	57
Speed 3	473	64
Intensive speed	686	72

Accessories included

Tube reduction Yes

Performance / Energy Label




Annual Efficiency Consumption (AEChood) 53 kWh/a
Energy efficicency class (EEC) A
Fluid Dynamic Efficiency (FDE) 29,8
Fluid Dynamic Efficiency class (FDEC) A
Lighting Efficiency (LE) 70,4 lux/W
Lighting Efficiency Class (LEC) A
Grease Filtering Efficiency (GFE) 79,7 %
Grease Filtering Efficiency Class (GFEC) C
Air flow at minumum speed (Qmin) 261 m³/h
Air flow at maximum speed (Qmax) 473 m³/h
Air flow at boost speed (Qboost) 686 m³/h

Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin) 48 dBA
Airborne acoustical A- weighted sound Power Emission at maximum speed (SPEmax) 64 dBA
Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost) 71 dBA
Time increase factor (F) 0,9
Energy Efficiency Index 52,0
Measured air flow rate at best efficiency point (Qbep) 395 m³/h
Measured air pressure at best efficiency point (Pbep) 451 Pa
Measured electric power input at best efficiency point (Wbep) 159 W
Nominal Power consumption of the light system (WL) 3 W
Average illumination of the light on the cooking surface (Emiddle) 156 lux
Sound power level at highest setting (Lwa) 70 dBA


Electrical Connection

Electrical connection rating	230 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	Not present
Frequency (Hz)	50-60 Hz		



Compatible Accessories

KITCEKBTBL



KITFCKBT

1 pc of charcoal filter for the hood models KBT* / KBCT*

KITFCKBTR



1 pcs of Charcoal filter Regenerable*
suitable for all the KBT/KBCT models. * It
can be washed in the dishwasher up to
12 times and dry in the oven at max 90°
for 60 min. dimension 237,5(H)x245x10
mm

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Energy efficiency class A



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.