

KBT600MB

Product family	Hood
Hood Type	Chimney Cooker Hoods
Design	T flat
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Material	Stainless steel
EAN code	8017709347239
Hood width	60 cm
Aesthetics	Universal
Colour	Matte Black
Logo	Silk screen



Controls

Control setting	Electronic buttons
-----------------	--------------------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	

Technical Features



No. of lights	2	Anti-grease filters	Aluminium
Light type	LED	Filter replacement indicator	Yes
Light power	1,3 W	Vent outlet	150 mm
Light colour temperature scale (K)	3000 K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	820 m ³ /h	Minimum distance from ELECTRIC hob	500 mm
Motor power	230 W	Non return valve	Yes
No. of filters	2		

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	260	49
Speed 2	358	57
Speed 3	473	64
Intensive speed	686	72

Accessories Included

Tube reduction Yes

Performance / Energy Label



Annual Efficiency Consumption (AEChood) 53 kWh/year

Energy efficiency class (EEC) A

Fluid Dynamic Efficiency (FDE) 29,8

Fluid Dynamic Efficiency class (FDEC) A

Lighting Efficiency (LE) 70,4 lux/W

Lighting Efficiency Class (LEC) A

Grease Filtering Efficiency (GFE) 79,7 %

Grease Filtering Efficiency Class (GFEC) C

Air flow at minimum speed (Qmin) 261 m³/h

Maximum extraction rate 473 m³/h

Intensive extraction rate 686 m³/h

Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) 48 dBA

Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 64 dBA

Airborne acoustical A-weighted sound power emission at boost speed (SPEboost) 71 dBA

Time increase factor (F) 0,9

Energy Efficiency Index per first cavity 52,0

Measured air flow rate at best efficiency point (Qbep) 395 m³/h

Measured air pressure at best efficiency point (Qbep) 451 Pa

Measured electric power input at best efficiency point (Wbep) 159 W

Normal Power of the light system (WI) 3 W

Average illumination of the light on the cooking surface (Emiddle) 156 lux

Sound power level at highest setting (Lwa) 70 dBA

Electrical Connection

Nominal power 230 W

Voltage	220-240 V	Power supply cable length	1500 mm
Frequency (Hz)	50-60 Hz	Plug	No

Compatible Accessories



KITCEKBTMB



KITFCKBT








1 pcs of activated carbon filter for hood models KBT* / KBCT*



KITFCKBTR

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

Symbols glossary

-  24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.
-  Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.
-  Warning light(s): to advise when filters need changing.
-  Intensive/turbo setting: when extra fast extraction is required.
-  Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.
-  A: Product drying performance, measured from A+++ to D / G depending on the product family
-  Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.